

sentinel-3

→ COPERNICUS MEDIUM RESOLUTION LAND AND OCEAN MISSION





sentinel-3

→ COPERNICUS MEDIUM RESOLUTION LAND AND OCEAN MISSION

Last update August 2013

MISSION OBJECTIVES

European global land and ocean monitoring mission. It provides 2 day global coverage Earth observation data (with 2 satellites) for sea and land applications with real-time products delivery in less than 3 hours.

These services include applications such as:

- › sea and land colour data, in continuation of MERIS (Envisat)
- › sea and land surface temperature, in continuation of AATSR (Envisat)
- › sea-surface and land-ice topography, in continuation of Envisat altimetry
- › along-track SAR for coastal zones, in-land water and sea ice topography
- › vegetation products through synergy between optical instruments

MISSION PROFILE

- › Launch: 2014
- › Launch vehicle:
 - S3A: Rockot from Plesetsk; S3B: Vega from Kourou
- › 7 year lifetime (consumables for 12 years)
- › Sun-synchronous orbit @ 814.5 km over geoid
- › Mean LST: 10:00 at Descending Node
- › 27-days repeat cycle (14+7/27 orbits per day)
- › Inclination 98.65°
- › Operational configuration comprises 2 satellites

SATELLITE PLATFORM

- › Gyroless, 3 axis stabilized platform with 3 star tracker heads, 4 reaction wheels and magnetic off-loading
- › Geodetic pointing and yaw steering
- › 8x1N hydrazine thrusters for in-plane & out-of-plane manoeuvres
- › 3 m accuracy real-time onboard orbit determination based on GPS and Kalman filtering
- › Launch Mass: 1250 kg (with maturity and system margins, and fuel)
- › Stowed dimensions (mm): (H) 3710, (W) 2202, (L) 2207
- › Power: 2.1 kW rotary wing with 10 m² triple junction GaAs European solar cells; Li Ion Battery Capacity: 160 Ah
- › Communication links:
 - › 64 kbps uplink, 1 Mbps downlink S-band command and control link (with ranging)
 - › 2 x 280 Mbps X-band science data downlink
 - › 384 Gbit solid state mass memory
- › Autonomy: position timeline and onboard sun ephemeris for greater than 2 weeks nominal autonomous operations

SATELLITE PAYLOAD

OLCI (Ocean and Land Colour Instrument)

- › Swath width: 1270 km, with 5 tilted cameras
- › Spatial sampling: 300 m @ SSP
- › Spectrum: 21 bands [0.4-1.02] μ m
- › Radiometric accuracy: 2% abs, 0.1% rel

SLSTR (Sea and Land Surface Temperature Radiometer)

- › Swath width: dual view scan, 1420 km (nadir) / 750 km (backwards)
- › Spatial sampling: 500 m (VIS, SWIR), 1 km (MWIR, TIR)
- › Spectrum: 9 bands [0.55-12] μ m
- › Noise equivalent ΔT : 50 mK (TIR) at 270K

SRAL (Sentinel-3 Ku/C Radar Altimeter)

- › Radar measurement modes: LRM and SAR
- › Tracking modes: closed and open-loop
- › Pulse repetition frequency: 1.9 KHz (LRM), 17.8 KHz (SAR)
- › Total range error: 3 cm

MWR (MicroWave Radiometer)

- › dual 23.8/36.5 GHz
- › Radiometric accuracy 3K absolute (0.6 K relative)

POD (Precise Orbit Determination)

- › GPS, LRR and DORIS (3 cm final accuracy after processing)