

isc Silicon NPN RF Transistor

2SC2026

DESCRIPTION

- Low Noise
NF= 3.0dB TYP. @ f= 500MHz
- High Power Gain
G_{pe}= 15dB TYP. @ f= 500MHz
- High Gain Bandwidth Product
f_T= 2.0GHz TYP.



APPLICATIONS

- Designed for use in low noise amplifiers in the VHF~UHF band.

ABSOLUTE MAXIMUM RATINGS(T_a=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V _{CBO}	Collector-Base Voltage	30	V
V _{CEO}	Collector-Emitter Voltage	14	V
V _{EBO}	Emitter-Base Voltage	3	V
I _C	Collector Current-Continuous	50	mA
P _C	Collector Power Dissipation @T _C =25°C	0.25	W
T _J	Junction Temperature	150	°C
T _{stg}	Storage Temperature Range	-55~150	°C

TO-92 package



DIM	mm	
	MIN	MAX
A	4.33	4.83
B	4.33	4.83
C	14.0	15.0
D	0.36	0.56
E	2.54	
F	1.27	
G	0.92	1.12
H	3.40	3.60



isc Silicon NPN RF Transistor

2SC2026

ELECTRICAL CHARACTERISTICS

 $T_C=25^{\circ}\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
I_{CBO}	Collector Cutoff Current	$V_{CB}=15\text{V}; I_E=0$			0.1	μA
I_{EBO}	Emitter Cutoff Current	$V_{EB}=2\text{V}; I_C=0$			0.1	μA
h_{FE}	DC Current Gain	$I_C=10\text{mA}; V_{CE}=10\text{V}$	25		200	
f_T	Current-Gain—Bandwidth Product	$I_C=10\text{mA}; V_{CE}=10\text{V}$	15	2.0		GHz
C_{OB}	Output Capacitance	$I_E=0; V_{CB}=10\text{V}; f=1.0\text{MHz}$		0.75	1.1	pF
G_{pe}	Power Gain	$V_{CE}=10\text{V}; I_C=10\text{mA}; f=500\text{MHz}$	13	15		dB
NF	Noise Figure	$V_{CE}=10\text{V}; I_C=3\text{mA}; f=500\text{MHz}; R_G=50\Omega$		3	4	dB