

Package ‘MiscMath’

September 27, 2026

Type Package

Title Miscellaneous Mathematical Tools

Version 1.2

Description Some basic math calculators for finding angles for triangles and for finding the greatest common divisor of two numbers and so on.

LazyLoad true

License GPL (>= 2)

Depends randomForest, numbers

NeedsCompilation yes

Author W.J. Braun [aut, cre]

Maintainer W.J. Braun <john.braun@ubc.ca>

Repository CRAN

Date/Publication 2026-09-27 02:30:14 UTC

Contents

MiscMath-package	2
DecToBin	2
EratosthenesSieve	3
gcd	3
IntDecToBin	4
LawofCosines	5
LawofSines	5
Matpower	6
MaxRunLength	7
mCracker	8
microLASSO	9
rAlias	9
rlincong	10
rMWC	11
RNGtest	11
rngV	12
shuffle	13

Index**14**

MiscMath-package	<i>Miscellaneous Mathematical Tools and Facts</i>
------------------	---

Description

A random assortment of elementary mathematical formulas and calculators.

Examples

```
# Find the greatest common divisor of 57, 93 and 117.
gcd(c(57, 93, 117))
```

DecToBin	<i>Convert Decimal to Binary</i>
----------	----------------------------------

Description

Convert a given decimal constant in the interval (0, 1) to the corresponding binary representation.

Usage

```
DecToBin(x, m = 32, format = "character")
```

Arguments

x	a numeric vector of values in the interval (0, 1)
m	a numeric constant specifying the number of binary digits to use in the output
format	a character string constant specifying the form of the output

Details

Default format is as a character string. Alternatives are plain which prints results to the device, and vector which output a binary vector.

Value

a vector containing the binary representation

Examples

```
x <- c(.81, .57, .333)
DecToBin(x) # character output
DecToBin(x, format="vector") # binary vector output
DecToBin(x, format="plain")
```

EratosthenesSieve	<i>Sieve of Eratosthenes</i>
-------------------	------------------------------

Description

The sieve of Eratosthenes is an ancient method for listing all prime numbers up to a given value n .

Usage

EratosthenesSieve(n)

Arguments

n a numeric vector consisting of a single positive integer.

Details

The algorithm scans through the vector from 2 through n , eliminating all multiples of 2, then eliminating all multiples of the next smallest integer (3), and so on, until only the prime numbers less than n remain.

Value

a numeric vector containing all primes less than n .

Examples

EratosthenesSieve(100)

gcd	<i>Greatest Common Divisor</i>
-----	--------------------------------

Description

Greatest common divisor or factor for all elements of a positive-integer-valued vector.

Usage

gcd(x)

Arguments

x a numeric vector consisting of at least two positive integer values.

Details

The gcd is calculated using the Euclidean algorithm applied to successive pairs of the elements of `x`.

Value

a numeric constant containing the greatest common divisor.

Examples

```
x <- c(81, 57, 333)
gcd(x)
```

IntDecToBin

Binary Expansion of Positive Integers

Description

Convert positive integers to their corresponding binary representation.

Usage

```
IntDecToBin(x, m = 31)
```

Arguments

<code>x</code>	an integer vector
<code>m</code>	a numeric constant specifying the number of binary digits to use in the output

Value

a matrix containing the binary representations

Examples

```
x <- c(81, 57, 333)
IntDecToBin(as.integer(x))
```

`LawofCosines`*Law of Cosines*

Description

Use of the ancient law of cosines to determine the angle between two sides of a triangle, given lengths of all three sides. This is a generalization of Pythagoras' Theorem.

Usage

```
LawofCosines(sides)
```

Arguments

`sides` a numeric vector of length 3, containing the side lengths.

Value

a numeric constant giving the angle in between the sides corresponding to the first two components in `sides`. Result is expressed in degrees.

Examples

```
LawofCosines(c(3, 4, 5))
```

`LawofSines`*Law of Sines*

Description

Use of the ancient law of sines to determine the angle opposite one side of a triangle, given the length of the opposite side as well as the angle opposite another side whose length is also known. Alternatively, one can find the length of the side opposite a given angle.

Usage

```
LawofSines(sides, angles, findAngle)
```

Arguments

`sides` a numeric vector of length 1 or 2, containing the side lengths.
`angles` a numeric vector of length 1 or 2, containing the angles (in degrees).
`findAngle` a logical constant

Details

If findAngle is TRUE, sides should be of length 2 and the function will compute angle opposite the side with length given by the second element of sides. Otherwise, angles should be of length 2, and the function will calculate the length of the side opposite the angle corresponding to the second element of angles.

Value

a numeric constant giving the angle opposite the given side, if findAngle is TRUE, or giving the length of the side opposite the given angle, if findAngle is FALSE.

Examples

```
LawofSines(c(3, 4), 50) # find angle opposite the side of length 4.  
LawofSines(3, c(70, 50), findAngle = FALSE) # find length of side opposite the 50 degree angle
```

Matpower	<i>Matrix Power</i>
----------	---------------------

Description

Implementation of efficient algorithm to compute the pth power of a matrix.

Usage

```
Matpower(X, p)
```

Arguments

- X numeric square matrix
- p integer: nonnegative exponent.

Value

a matrix containing the pth power of X.

References

Golub and Van Loan (1983) Matrix Computations. Algorithm 11.2-1. p. 393.

MaxRunLength

Maximum Run Length

Description

Calculate the maximum run length of 0's in a binary vector.

Usage

```
MaxRunLength(x)
```

Arguments

x a binary vector

Value

the maximum run length of 0's

Examples

```
x <- c(0L, 1L, 1L, 1L, 0L, 0L, 1L, 1L, 0L, 0L, 1L)
MaxRunLength(x) # should be 2
MaxRunLength(1L - x) # should be 3
# Test of Mersenne Twister

RNGkind("Mers") # ensure that default generator is in use
N <- 10000
x <- runif(N)
y <- DecToBin(x, format = "vector", m = 40)
MaxHeadRunsM <- apply(y, 1, MaxRunLength) # 0 run lengths (Heads)
MaxTailRunsM <- apply(1-y, 1, MaxRunLength) # 1 run lengths (Tails)
# distributions of Max 0 run lengths and Max 1 run lengths should match
boxplot(MaxHeadRunsM, MaxTailRunsM, axes=FALSE, main="Maximum Run Length")
axis(side=1, at=c(1, 2), label=c("Heads", "Tails"))
axis(2)
box()

# Comparison with Wichmann-Hill Generator

RNGkind("Wich")
x <- runif(N)
y <- DecToBin(x, format = "vector", m = 40)
MaxHeadRunsW <- apply(y, 1, MaxRunLength)
MaxTailRunsW <- apply(1-y, 1, MaxRunLength)
boxplot(MaxHeadRunsW, MaxTailRunsW, axes=FALSE, main="Maximum Run Length")
axis(side=1, at=c(1, 2), label=c("Heads", "Tails"))
axis(2)
box()
RNGkind("Mers") # restore default generator
```

mCracker

Modulus Cracker

Description

Infers the modulus m for a congruential random number generator.

Usage

```
mCracker(U, par = 1e6, maxit = 100)
```

Arguments

U	a numeric vector consisting of n (say 10000) uniform(0,1) pseudorandom numbers of the form $x_1/m, x_2/m, \dots, x_n/m$.
par	an integer guess as to an upper bound on the smallest integer in the sequence $x_1, x_2, \dots, x_n$.
maxit	maximum number of iterations allowed.

Details

Basic idea: Let $x(1)$ denote the minimum order statistic in $x_1, x_2, \dots, x_n$. Then the set $(x_1/m)/(x(1)/m) \cdot (1:par)$ must contain at least one integer, and m is in that set, if par has been set correctly.

Value

a list consisting of

m	the integer value of m
firstInteger	the minimum order statistic of the set $x_1, x_2, \dots, x_m$

Examples

```
# set.seed(33663)
x <- runif(1000000)
Y <- mCracker(x)$m
log(Y, 2) # should be 32
```

microLASSO

*Simplest Case of LASSO Regression***Description**

Simple linear regression estimators for slope, intercept and noise standard deviation with absolute value penalty on slope.

Usage

```
microLASSO(x, y, lambda)
```

Arguments

x	a numeric vector of covariate values
y	a numeric vector of response values
lambda	a numeric constant which should be nonnegative

Value

a list consisting of

Coefficients	a numeric vector containing intercept and slope estimates
RMSE	a numeric constant containing the (penalized) maximum likelihood estimate of the noise standard deviation

Examples

```
x <- runif(30)
y <- x + rnorm(30)
microLASSO(x, y, lambda = 0.5)
```

rAlias

*Alias Method for Generating Discrete Random Variates***Description**

Efficient method for generating discrete random variates from any distribution with a finite number (N) of states. The method is described in detail in Section 10.1 of the given reference.

Usage

```
rAlias(n, P)
```

Arguments

n numeric, constant number of variates to be simulated

P numeric, probability mass function, assuming states from 1 through N

Value

numeric vector of containing n simulated values from the given discrete distribution

References

S. Ross (1990) A Course in Simulation, MacMillan.

Examples

```
x <- rAlias(n = 100, P = c(1:5)/15)
table(x)/100
```

rlincong

Linear Congruential Generator

Description

Basic implementation of the linear congruential random number generator.

Usage

```
rlincong(n, seed, par)
```

Arguments

n numeric: number of variates to generate.

seed numeric: initial seed.

par an integer vector containing parameters for the generator: a, cc, m.

Value

a vector of n uniform random numbers

Examples

```
x <- rlincong(1000, 6976, c(171, 0, 30269))
summary(x)
```

rMWC

Multiply-With-Carry Random Number Generator

Description

Basic implementation of the multiply-with-carry generator.

Usage

```
rMWC(n, par)
```

Arguments

n numeric: number of variates to generate.
par an integer vector containing parameters for the generator: X, C, A, B.

Value

a vector of n uniform random numbers

References

Marsaglia, G. (2003) Random Number Generators. *Journal of Modern Applied Statistical Methods*. 2(1):2.

Examples

```
x <- rMWC(58, c(5, 3, 6, 10))
summary(x)
```

RNGtest

Pseudorandom Number Testing via Random Forest

Description

Given a sequence of pseudorandom numbers, this function constructs a random forest prediction model for successive values, based on previous values up to a given lag. The ability of the random forest model to predict future values is inversely related to the quality of the sequence as an approximation to locally random numbers.

Usage

```
RNGtest(u, m=5)
```

Arguments

u	numeric, a vector of pseudorandom numbers to test
m	numeric, number of lags to test

Value

Side effect is a two way layout of graphs showing effectiveness of prediction on a training and a testing subset of data. Good predictions indicate a poor quality sequence.

Author(s)

W. John Braun

Examples

```
x <- runif(200)
RNGtest(x, m = 4)
```

rngV

Vectorized Congruential Random Number Generator

Description

Basic vectorized implementation of the linear congruential generator for simulating uniform random numbers on the interval (0, 1).

Usage

```
rngV(n, seed, par)
```

Arguments

n	numeric: number of variates to generate.
seed	numeric: initial seed.
par	an integer vector containing parameters for the generator: a, cc, m, L.

Value

a vector of n uniform random numbers

References

Anderson, S.L. (1990) Random number generators on vector supercomputers and other advanced architectures. *SIAM Review*, 32(2):221-251.

Examples

```
x <- rngV(1000, 6976, c(171, 0, 30269, 10))
summary(x)
```

`shuffle`*Shuffling Algorithm*

Description

Implementation of a simple shuffling algorithm that can be used to randomly permute a given set of simulated random numbers.

Usage

```
shuffle(n, k = 100, x = runif(n))
```

Arguments

<code>n</code>	numeric: number of variates to be output.
<code>k</code>	numeric: a tuning parameter for the shuffler.
<code>x</code>	a vector containing a sequence to be randomly permuted with the shuffler.

Value

a numeric vector

Index

- * **graphics**
 - rAlias, [9](#)
 - RNGtest, [11](#)
- * **math**
 - DecToBin, [2](#)
 - EratosthenesSieve, [3](#)
 - gcd, [3](#)
 - IntDecToBin, [4](#)
 - LawofCosines, [5](#)
 - LawofSines, [5](#)
 - Matpower, [6](#)
 - MaxRunLength, [7](#)
 - mCracker, [8](#)
 - rlincong, [10](#)
 - rMWC, [11](#)
 - rngV, [12](#)
 - shuffle, [13](#)
- * **models**
 - microLASSO, [9](#)
- * **package**
 - MiscMath-package, [2](#)

DecToBin, [2](#)

EratosthenesSieve, [3](#)

gcd, [3](#)

IntDecToBin, [4](#)

LawofCosines, [5](#)

LawofSines, [5](#)

Matpower, [6](#)

MaxRunLength, [7](#)

mCracker, [8](#)

microLASSO, [9](#)

MiscMath (MiscMath-package), [2](#)

MiscMath-package, [2](#)

rAlias, [9](#)

rlincong, [10](#)

rMWC, [11](#)

RNGtest, [11](#)

rngV, [12](#)

shuffle, [13](#)