

Package ‘NeutroIBDAnalysis’

September 26, 2026

Type Package

Title Neutrosophic Analysis of Incomplete Block Designs

Version 0.1.2

Maintainer Vinaykumar L.N. <vinaymandya123@gmail.com>

Description Provides methods for neutrosophic analysis of variance (NANOVA) and neutrosophic analysis of covariance (NANCOVA) for interval-valued data arising from incomplete block design experiments. The package supports balanced incomplete block designs (BIBDs), partially balanced incomplete block designs (PBIBDs), and lattice designs. Functions are included for treatment comparisons, least significant difference (LSD) tests, and interval-based statistical inference under neutrosophic environments.

License GPL (>= 2)

Encoding UTF-8

Depends R (>= 4.0.0)

Imports MASS, stats

NeedsCompilation no

Author Neethu R.S. [aut, ctb],
Cini Varghese [aut, ctb],
Mohd Harun [aut, ctb],
Anindita Datta [aut, ctb],
Vinaykumar L.N. [aut, cre]

Repository CRAN

Date/Publication 2026-09-26 06:10:02 UTC

Config/roxygen2/version 8.0.0

Contents

IBDnsANCOVA	2
IBDnsANOVA	4
LDnsANCOVA	5
LDnsANOVA	8

IBDnsANCOVA	<i>Neutrosophic ANCOVA for Incomplete Block Designs</i>
-------------	---

Description

Performs neutrosophic analysis of covariance for incomplete block designs using interval-valued responses and covariates.

Usage

```
IBDnsANCOVA(  
  Lower_y,  
  Upper_y,  
  Lower_z,  
  Upper_z,  
  design,  
  alpha = 0.05,  
  verbose = FALSE  
)
```

Arguments

Lower_y	Matrix of lower interval responses.
Upper_y	Matrix of upper interval responses.
Lower_z	Matrix of lower interval covariates.
Upper_z	Matrix of upper interval covariates.
design	Incomplete block design matrix.
alpha	Significance level for LSD test and F-test (default = 0.05).
verbose	Logical. If TRUE, prints the neutrosophic ANCOVA table, significance codes, LSD interval and pairwise treatment comparisons. Default = FALSE.

Details

The rows of the response and design arrays represent blocks, while the columns represent treatment allocations within blocks.

Value

- A list containing:
- STAR_NANCOVA : Neutrosophic ANCOVA table.
 - LSD : Neutrosophic LSD interval.
 - Comparison : Pairwise treatment comparison table.

Examples

```
Lower_y <- matrix(c(
  46.46436719, 49.56056768, 47.21541951,
  47.41402083, 51.24762662, 50.95734839,
  50.7492564, 51.250892, 50.01772519,
  51.72202304, 53.83285904, 54.53288749,
  53.71983091, 55.3957797, 53.85646279,
  55.29951886, 57.48888886, 56.81959243,
  56.01454397, 57.64266115, 56.15643552
), nrow = 7, byrow = TRUE)
```

```
Upper_y <- matrix(c(
  49.53563281, 52.43943232, 52.78458049,
  52.58597917, 54.75237338, 53.04265161,
  53.2507436, 56.749108, 55.98227481,
  54.27797696, 58.16714096, 59.46711251,
  56.28016909, 60.6042203, 58.14353721,
  58.70048114, 60.51111114, 59.18040757,
  59.98545603, 62.35733885, 61.84356448
), nrow = 7, byrow = TRUE)
```

```
Lower_z <- matrix(c(
  87.6024962, 49.87728481, 21.20537996,
  74.19109283, 70.90050743, 69.79918837,
  118.3567216, 84.52944492, 87.2387685,
  116.5444728, 127.5038727, 122.3890764,
  104.4945972, 117.9310944, 126.206537,
  101.9435439, 91.18240208, 81.56378309,
  92.28882349, 86.13485988, 83.04950126
), nrow = 7, byrow = TRUE)
```

```
Upper_z <- matrix(c(
  90.3975038, 60.12271519, 32.79462004,
  81.80890717, 73.09949257, 72.20081163,
  127.6432784, 97.47055508, 102.7612315,
  131.4555272, 136.4961273, 135.6109236,
  119.5054028, 122.0689056, 133.793463,
  116.0564561, 102.8175979, 96.43621691,
  99.71117651, 93.86514012, 92.95049874
), nrow = 7, byrow = TRUE)
```

```
design <- matrix(c(
  1, 2, 4,
  2, 3, 5,
  3, 4, 6,
  4, 5, 7,
  5, 6, 1,
  6, 7, 2,
  7, 1, 3
), nrow = 7, byrow = TRUE)
```

```
IBDnsANCOVA(
```

```

Lower_y = Lower_y,
Upper_y = Upper_y,
Lower_z = Lower_z,
Upper_z = Upper_z,
design = design,
verbose = TRUE
)

```

IBDnsANOVA

Neutrosophic ANOVA for Incomplete Block Designs

Description

Performs neutrosophic analysis of variance for incomplete block designs using interval-valued observations.

Usage

```
IBDnsANOVA(Lower_y, Upper_y, design, alpha = 0.05, verbose = FALSE)
```

Arguments

Lower_y	Matrix of lower interval responses.
Upper_y	Matrix of upper interval responses.
design	Incomplete block design matrix.
alpha	Significance level for LSD test and F-test (default = 0.05).
verbose	Logical. If TRUE, prints the neutrosophic ANOVA table, LSD interval, significance codes and pairwise treatment comparisons. Default = FALSE.

Details

The rows of the response and design arrays represent blocks, while the columns represent treatment allocations within blocks.

Value

A list containing:

- STAR_NANOVA : Neutrosophic ANOVA table.
- LSD : Neutrosophic LSD interval.
- Comparison : Pairwise treatment comparison table.

Examples

```

Lower_y <- matrix(c(
  46.46436719, 49.56056768, 47.21541951,
  47.41402083, 51.24762662, 50.95734839,
  50.74925640, 51.25089200, 50.01772519,
  51.72202304, 53.83285904, 54.53288749,
  53.71983091, 55.39577970, 53.85646279,
  55.29951886, 57.48888886, 56.81959243,
  56.01454397, 57.64266115, 56.15643552
), nrow = 7, byrow = TRUE)

Upper_y <- matrix(c(
  49.53563281, 52.43943232, 52.78458049,
  52.58597917, 54.75237338, 53.04265161,
  53.25074360, 56.74910800, 55.98227481,
  54.27797696, 58.16714096, 59.46711251,
  56.28016909, 60.60422030, 58.14353721,
  58.70048114, 60.51111114, 59.18040757,
  59.98545603, 62.35733885, 61.84356448
), nrow = 7, byrow = TRUE)

design <- matrix(c(
  1, 2, 4,
  2, 3, 5,
  3, 4, 6,
  4, 5, 7,
  5, 6, 1,
  6, 7, 2,
  7, 1, 3
), nrow = 7, byrow = TRUE)

IBDnsANOVA( Lower_y, Upper_y, design, verbose = TRUE )

```

LDnsANCOVA

*Neutrosophic ANCOVA for Lattice Designs***Description**

Performs neutrosophic analysis of covariance for lattice designs using interval-valued responses and covariates.

Usage

```

LDnsANCOVA(
  Lower_y,
  Upper_y,
  Lower_z,
  Upper_z,

```

```

    design,
    alpha = 0.05,
    verbose = FALSE
  )

```

Arguments

Lower_y	Matrix of lower interval responses.
Upper_y	Matrix of upper interval responses.
Lower_z	Matrix of lower interval covariates.
Upper_z	Matrix of upper interval covariates.
design	Lattice design matrix.
alpha	Significance level for LSD test and F-test (default = 0.05).
verbose	Logical. If TRUE, prints the neutrosophic ANCOVA table, significance codes, LSD interval and pairwise treatment comparisons. Default = FALSE.

Details

The rows of the response and design arrays represent blocks, while the columns represent treatment allocations within blocks.

Value

A list containing:

- STAR_NANCOVA : Neutrosophic ANCOVA table.
- LSD : Neutrosophic LSD interval.
- Comparison : Pairwise treatment comparison table.

Examples

```

Lower_y <- matrix(c(
  86.81, 81.44, 89.83,
  76.14, 72.77, 72.93,
  92.17, 58.56, 70.48,
  111.43, 78.95, 56.87,
  84.71, 74.19, 98.10,
  78.91, 90.49, 87.52,
  99.76, 80.10, 94.54,
  62.05, 86.81, 63.06,
  67.52, 70.05, 68.24
), nrow = 9, byrow = TRUE)

```

```

Upper_y <- matrix(c(
  89.19, 88.56, 94.17,
  79.86, 79.23, 79.07,
  95.83, 65.44, 79.52,
  118.57, 85.05, 63.13,
  89.29, 77.81, 105.90,

```

```

      85.09,99.51,92.48,
      104.24,87.90,99.46,
      65.95,91.19,70.94,
      72.48,79.95,75.76
    ), nrow = 9, byrow = TRUE)

```

```

Lower_z <- matrix(c(
  27.04,24.47,20.28,
  32.31,37.02,23.16,
  12.58,8.35,22.37,
  7.31,20.02,25.12,
  9.93,33.58,12.50,
  17.74,37.01,24.99,
  22.28,4.65,22.52,
  21.71,18.47,20.41,
  35.65,17.27,23.22
), nrow = 9, byrow = TRUE)

```

```

Upper_z <- matrix(c(
  36.96,27.53,26.72,
  37.69,40.98,26.84,
  17.42,15.65,32.03,
  16.69,29.78,28.28,
  16.07,36.42,21.50,
  22.26,40.99,30.01,
  25.72,13.35,30.08,
  25.49,27.53,29.19,
  44.35,24.73,30.98
), nrow = 9, byrow = TRUE)

```

```

design <- matrix(c(
  1,2,3,
  7,9,8,
  6,4,5,
  1,7,4,
  8,5,2,
  3,6,9,
  1,8,6,
  4,2,9,
  3,5,7
), nrow = 9, byrow = TRUE)

```

```

LDnsANCOVA(
  Lower_y = Lower_y,
  Upper_y = Upper_y,
  Lower_z = Lower_z,
  Upper_z = Upper_z,
  design = design,
  verbose = TRUE
)

```

LDnsANOVA

*Neutrosophic ANOVA for Lattice Designs***Description**

Performs neutrosophic analysis of variance for lattice designs using interval-valued observations.

Usage

```
LDnsANOVA(Lower_y, Upper_y, design, alpha = 0.05, verbose = FALSE)
```

Arguments

Lower_y	Matrix of lower interval responses.
Upper_y	Matrix of upper interval responses.
design	Lattice design matrix.
alpha	Significance level for LSD test and F-test (default = 0.05).
verbose	Logical. If TRUE, prints the neutrosophic ANOVA table, significance codes, LSD interval and pairwise treatment comparisons. Default = FALSE.

Details

The rows of the response and design arrays represent blocks, while the columns represent treatment allocations within blocks.

Value

A list containing:

- STAR_NANOVA : Neutrosophic ANOVA table.
- LSD : Neutrosophic LSD interval.
- Comparison : Pairwise treatment comparison table.

Examples

```
Lower_y <- matrix(c(
  86.81, 81.44, 89.83,
  76.14, 72.77, 72.93,
  92.17, 58.56, 70.48,
  111.43, 78.95, 56.87,
  84.71, 74.19, 98.10,
  78.91, 90.49, 87.52,
  99.76, 80.10, 94.54,
  62.05, 86.81, 63.06,
  67.52, 70.05, 68.24
), nrow=9, byrow=TRUE)
```

```
Upper_y <- matrix(c(
  89.19,88.56,94.17,
  79.86,79.23,79.07,
  95.83,65.44,79.52,
  118.57,85.05,63.13,
  89.29,77.81,105.90,
  85.09,99.51,92.48,
  104.24,87.90,99.46,
  65.95,91.19,70.94,
  72.48,79.95,75.76
), nrow=9, byrow=TRUE)

design <- matrix(c(
  1,2,3,
  7,9,8,
  6,4,5,
  1,7,4,
  8,5,2,
  3,6,9,
  1,8,6,
  4,2,9,
  3,5,7
), nrow=9, byrow=TRUE)

LDnsANOVA(Lower_y, Upper_y,design,verbose = TRUE )
```

Index

IBDnsANCOVA, [2](#)

IBDnsANOVA, [4](#)

LDnsANCOVA, [5](#)

LDnsANOVA, [8](#)