

Package ‘PROJ’

July 10, 2026

Title Generic Coordinate System Transformations Using 'PROJ'

Version 0.7.0

Description A wrapper around the generic coordinate transformation software 'PROJ' that transforms coordinates from one coordinate reference system ('CRS') to another. This includes cartographic projections as well as geodetic transformations. The intention is for this package to be used by user-packages such as 'reproj', and that the older 'PROJ.4' and version 5 pathways be provided by the 'proj4' package.

Depends R (>= 3.0.2)

License GPL-3

Encoding UTF-8

LazyData true

Imports lifecycle, wk (>= 0.9.2)

LinkingTo wk (>= 0.9.2)

Suggests testthat (>= 3.0.0), spelling, knitr, rmarkdown, sf

URL <https://github.com/hypertidy/PROJ>,
<https://hypertidy.github.io/PROJ/>

BugReports <https://github.com/hypertidy/PROJ/issues>

Language en-US

VignetteBuilder knitr

SystemRequirements PROJ (>= 6.3.1)

Config/testthat/edition 3

Config/roxygen2/version 8.0.0

NeedsCompilation yes

Author Michael D. Sumner [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-2471-7511>>),
Jeroen Ooms [ctb] (provided PROJ library support on Windows, and
assistance with Windows configuration),
Simon Urbanek [cph, ctb] (wrote original code versions for PROJ version

6),
Dewey Dunnington [ctb] (key code contributions),
Anthony North [ctb]
Maintainer Michael D. Sumner <mdsumner@gmail.com>
Repository CRAN
Date/Publication 2026-07-10 07:10:02 UTC

Contents

ok_proj6	2
proj_crs_text	3
proj_factors	4
proj_trans	5
proj_trans_create	6
proj_version	7
xymap	7
Index	8

ok_proj6	<i>Is 'PROJ' library >= 6' available</i>
----------	---

Description

[Deprecated]
Test for availability of 'PROJ' system library version 6 or higher.

Usage

ok_proj6()

Details

On unix-alikes, this function is run in .onLoad() to check that version 6 functionality is available. On Windows, the load process sets the data file location with the version 6 API, and that is used as a test instead.

If 'PROJ' library version 6 is not available, the package still compiles and installs but is not functional.

The lack of function can be simulated by setting options(reproj.mock.noproj6 = TRUE), designed for use with the reproj package.

Value

logical, TRUE if the system library 'PROJ >= 6'

Examples

```
ok_proj6()
```

proj_crs_text	<i>Generate a projection string.</i>
---------------	--------------------------------------

Description

Input any accepted format of 'PROJ' coordinate reference system specification. Return value is a string in the requested format.

Usage

```
proj_crs_text(source, format = 0L)
```

Arguments

source	input projection specification one of ('PROJ4', 'WKT2', 'EPSG', 'PROJJSON', ... see the library documentation link in Details)
format	integer, 0 for 'WKT', 1 for 'PROJ', 2 for 'PROJJSON'

Details

This function requires PROJ version 6.0 or higher to be useful. If not, this function simply returns 'NA'.

See the [library documentation](#) for details on input and output formats.

Value

character string in requested format

warning

Note that a PROJ string is not a full specification, in particular this means that a string like "+proj=laea" cannot be converted to full WKT, because it is technically a transformation step not a crs. To get the full WKT form use a string like "+proj=laea +type=crs".

Examples

```
cat(proj_crs_text("EPSG:4326", format = 0L))
proj_crs_text("EPSG:4326", format = 1L)
south55 <- "+proj=utm +zone=55 +south +ellps=GRS80 +units=m +no_defs +type=crs"
proj_crs_text(proj_crs_text(south55), 1L)
```

proj_factors

*Compute map projection factors for coordinates***Description**

Computes map projection factors (distortion measures) for a set of geographic coordinates and a given projected CRS. Returns a matrix with one row per input coordinate and one column per factor.

Usage

```
proj_factors(lp, crs)
```

Arguments

lp	A two-column numeric matrix of geographic coordinates (longitude, latitude) in decimal degrees.
crs	A PROJ CRS definition string for the target projection (e.g. a PROJ string, WKT, or authority code such as "EPSG:3112"). Using a CRS (rather than a '+proj=' operation string) requires PROJ >= 8.2.

Details

Rows for coordinates where the factors computation fails (for example latitudes outside +/-90) are filled with NaN. Missing input coordinates give NA output.

Value

A numeric matrix with `nrow(lp)` rows and the following columns:

- meridional_scale** Meridional scale factor (h)
- parallel_scale** Parallel scale factor (k)
- areal_scale** Areal scale factor (s)
- angular_distortion** Angular distortion (omega), in radians
- meridian_parallel_angle** Meridian-parallel angle (theta prime), in radians
- meridian_convergence** Meridian convergence (conv), in radians
- tissot_semimajor** Tissot semimajor axis (a)
- tissot_semiminor** Tissot semiminor axis (b)
- dx_dlam** Partial derivative dx/dlambda
- dx_dphi** Partial derivative dx/dphi
- dy_dlam** Partial derivative dy/dlambda
- dy_dphi** Partial derivative dy/dphi

References

[PROJ PJ_FACTORS documentation](#)

Examples

```
# Lambert Azimuthal Equal Area
proj_factors(cbind(147, -42), "+proj=laea +lon_0=147 +lat_0=-42 +type=crs")

# Multiple coordinates
pts <- cbind(c(130, 147, 160), c(-20, -42, -35))
proj_factors(pts, "EPSG:3112")
```

proj_trans	<i>Transform coordinates</i>
------------	------------------------------

Description

Transforms all coordinates in `x` using `wk::wk_handle()` and `proj_trans_create()`.

Usage

```
proj_trans(x, target_crs, source_crs = NULL, ..., use_z = NA, use_m = NA)
```

Arguments

<code>x</code>	Input geometry/geography. May take any of the following forms: • A coordinate matrix containing 2, 3 or 4 columns. If named, expects column names "x", "y" and optionally "z" and/or "m". If not named, columns are assumed in xyzm order. Non-coordinate columns are removed. • A data.frame containing coordinates as columns. Expects names "x", "y" and optionally "z" and/or "m". Non-coordinate columns are retained. • A data.frame containing a geometry vector which is readable by <code>wk::wk_handle()</code>, including <code>sfc</code> columns. • A geometry vector which is readable by <code>wk::wk_handle()</code>, including <code>sfc</code> columns.
<code>source_crs, target_crs</code>	Source/Target CRS definition, coerced with <code>wk::wk_crs_proj_definition()</code>
<code>...</code>	Additional parameters forwarded to <code>wk::wk_handle()</code>
<code>use_z, use_m</code>	Used to declare the output type. Use TRUE to ensure the output has that dimension, FALSE to ensure it does not, and NA to leave the dimension unchanged.

Details

Values that are detected out of bounds by library PROJ are allowed, we return Inf in this case, rather than the error "tolerance condition error".

Value

Transformed geometries whose format is dependent on input.

References

see the [PROJ library documentation](#) for details on the underlying functionality

Examples

```
proj_trans(cbind(147, -42), "+proj=laea +type=crs", "EPSG:4326")
proj_trans(cbind(147, -42, -2), "+proj=laea +type=crs", "EPSG:4326")
proj_trans(cbind(147, -42, -2, 1), "+proj=laea +type=crs", "EPSG:4326")
proj_trans(wk::xy(147, -42, crs = "EPSG:4326"), "+proj=laea +type=crs")
proj_trans(wk::wkt("POLYGON ((1 1, 0 1, 0 0, 1 0, 1 1))", crs = "EPSG:4326"), 3112)
```

proj_trans_create	Create a transformation object
-------------------	--------------------------------

Description

Creates a transformation object that transforms coordinates in a wk pipeline.

Usage

```
proj_trans_create(source_crs, target_crs, use_z = NA, use_m = NA)
```

Arguments

source_crs, target_crs	Source/Target CRS definition, coerced with <code>wk::wk_crs_proj_definition()</code>
use_z, use_m	Used to declare the output type. Use TRUE to ensure the output has that dimension, FALSE to ensure it does not, and NA to leave the dimension unchanged.

Value

A PROJ transformation object

Examples

```
(trans <- proj_trans_create("EPSG:4326", "EPSG:3857"))
wk::wk_transform(wk::xy(1:5, 1:5), trans)

library(wk)
(invtrans <- wk_trans_inverse(trans))

h <- 1852 * 60
## the stretch of Mercator to a square
wk::wk_transform(wk::xy(c(-h * 180, 0, h * 180), c(-h * 180, 0, h * 180)), invtrans)
```

proj_version	<i>Report PROJ library version</i>
--------------	------------------------------------

Description

This function returns NA if PROJ lib is not available.

Usage

```
proj_version()
```

Value

character string (major.minor.patch)

Examples

```
proj_version()
```

xymap	<i>xymap data for testing</i>
-------	-------------------------------

Description

A copy of the xymap data set from the quadmesh package.

Details

A matrix of longitude/latitude values of the world coastline.

Index

ok_proj6, [2](#)

proj_crs_text, [3](#)

proj_factors, [4](#)

proj_trans, [5](#)

proj_trans_create, [6](#)

proj_trans_create(), [5](#)

proj_version, [7](#)

wk::wk_crs_proj_definition(), [5](#), [6](#)

wk::wk_handle(), [5](#)

xymap, [7](#)