

Package ‘apollo’

July 13, 2026

Type Package

Title Tools for Choice Model Estimation and Application

Version 0.3.9

Description Choice models are a widely used technique across numerous scientific disciplines. The Apollo package is a very flexible tool for the estimation and application of choice models in R. Users are able to write their own model functions or use a mix of already available ones. Random heterogeneity, both continuous and discrete and at the level of individuals and choices, can be incorporated for all models. There is support for both standalone models and hybrid model structures. Both classical and Bayesian estimation is available, and multiple discrete continuous models are covered in addition to discrete choice. Multi-threading processing is supported for estimation and a large number of pre and post-estimation routines, including for computing posterior (individual-level) distributions are available. For examples, a manual, and a support forum, visit <https://www.ApolloChoiceModelling.com>. For more information on choice models see Train, K. (2009) <isbn:978-0-521-74738-7> and Hess, S. & Daly, A.J. (2014) <isbn:978-1-781-00314-5> for an overview of the field.

License GPL-2

URL <https://www.ApolloChoiceModelling.com>

BugReports <https://www.ApolloChoiceModelling.com/forum/>

Encoding UTF-8

LazyData true

Depends R (>= 4.3.0), stats, utils

Imports Rcpp (>= 1.0.0), maxLik, mnormt, mvtnorm, graphics, randtoolbox, numDeriv, parallel, Deriv, matrixStats, coda, tibble, stringr, bgw (>= 0.1.4), cli, Rsolnp, rstudioapi, MCMCpack

LinkingTo Rcpp, RcppArmadillo, RcppEigen

Suggests knitr, rmarkdown, testthat

VignetteBuilder knitr

RoxygenNote 7.3.3

NeedsCompilation yes

Author Stephane Hess [aut, cre],
David Palma [aut],
Thomas Hancock [ctb]

Maintainer Stephane Hess <S.Hess@leeds.ac.uk>

Repository CRAN

Date/Publication 2026-07-13 10:10:10 UTC

Contents

.onAttach	4
apollo_addCovariance	5
apollo_attach	5
apollo_avgInterDraws	6
apollo_avgIntraDraws	8
apollo_basTest	9
apollo_bootstrap	10
apollo_checkArguments	12
apollo_choiceAnalysis	13
apollo_classAlloc	14
apollo_cnl	15
apollo_combineModels	17
apollo_combineResults	20
apollo_compareInputs	21
apollo_conditionals	21
apollo_deltaMethod	22
apollo_detach	24
apollo_dft	24
apollo_diagnostics	27
apollo_drugChoiceData	28
apollo_dVdB	29
apollo_dVdBOLD	30
apollo_el	30
apollo_emdc	32
apollo_emdc1	34
apollo_emdc2	35
apollo_estimate	37
apollo_estimateHB	39
apollo_expandLoop	40
apollo_firstRow	41
apollo_fitsTest	42
apollo_fmnl	43
apollo_fnl	45
apollo_initialise	47

apollo_insertComponentName	48
apollo_insertFunc	48
apollo_insertOLList	49
apollo_insertRows	50
apollo_insertRRMQuotes	50
apollo_insertScaling	51
apollo_keepRows	51
apollo_lc	52
apollo_lcConditionals	53
apollo_lcEM	54
apollo_lcEM_new	56
apollo_lcUnconditionals	57
apollo_llCalc	58
apollo_loadModel	59
apollo_longToWide	59
apollo_lrTest	60
apollo_makeCluster	61
apollo_makeDraws	62
apollo_makeGrad	63
apollo_makeHessian	64
apollo_makeLogLike	64
apollo_mdcev	66
apollo_mdcev2	68
apollo_mdcnev	70
apollo_mixConditionals	73
apollo_mixEM	74
apollo_mixUnconditionals	75
apollo_mlhs	76
apollo_mnl	77
apollo_modeChoiceData	79
apollo_modelOutput	81
apollo_modifyUserDefFunc	82
apollo_nl	83
apollo_normalDensity	86
apollo_ol	88
apollo_op	90
apollo_outOfSample	92
apollo_ownModel	94
apollo_panelProd	96
apollo_prediction	98
apollo_preEstimate	99
apollo_prepareProb	101
apollo_preprocess	103
apollo_print	104
apollo_readBeta	105
apollo_rrm	106
apollo_saveOutput	108
apollo_searchStart	110

apollo_setRows 112

apollo_setWorkDir 113

apollo_sharesTest 113

apollo_sink 115

apollo_speedTest 115

apollo_swissRouteChoiceData 117

apollo_timeUseData 118

apollo_tobit 119

apollo_unconditionals 121

apollo_validate 122

apollo_validateControl 123

apollo_validateData 125

apollo_validateHBControl 125

apollo_validateInputs 127

apollo_varcov 130

apollo_varList 132

apollo_weighting 132

apollo_writeF12 134

apollo_writeTheta 134

aux_validateRows 135

print.apollo 136

summary.apollo 136

Index 137

.onAttach	<i>Prints package startup message</i>
-----------	---------------------------------------

Description

This function is only called by R when attaching the package.

Usage

.onAttach(libname, pkgname)

Arguments

- libname Name of library.
- pkgname Name of package.

Value

Nothing

apollo_addCovariance *Adds covariance matrix to Apollo model*

Description

Receives an estimated model object, calculates its Hessian, and classical and robust covariance matrix, and returns the same model object, but with these additional elements.

Usage

```
apollo_addCovariance(model, apollo_inputs)
```

Arguments

`model` Model object. Estimated model object as returned by function [apollo_estimate](#).
`apollo_inputs` List grouping most common inputs. Created by function [apollo_validateInputs](#).

Value

`model`.

apollo_attach *Attaches predefined variables.*

Description

Attaches parameters and data to allow users to refer to individual variables by name without reference to the object that contains them.

Usage

```
apollo_attach(apollo_beta, apollo_inputs)
```

Arguments

`apollo_beta` Named numeric vector. Names and values for parameters.
`apollo_inputs` List grouping most common inputs. Created by function [apollo_validateInputs](#).

Details

This function should be called at the beginning of `apollo_probabilities` to make writing the log-likelihood more user-friendly. If used, then [apollo_detach](#) should be called at the end of `apollo_probabilities`, or more conveniently, using [on.exit](#) after the initial call to `apollo_attach`. `apollo_attach` attaches `apollo_beta`, `database`, `draws`, and the output of `apollo_randCoeff` and `apollo_lcPars`, if they are defined by the user.

Value

Nothing.

apollo_avgInterDraws *Averages across inter-individual draws.*

Description

Averages individual-specific likelihood across inter-individual draws.

Usage

```
apollo_avgInterDraws(P, apollo_inputs, functionality)
```

Arguments

- | | |
|---------------|--|
| P | List of vectors, matrices or 3-dim arrays. Likelihood of the model components. |
| apollo_inputs | List grouping most common inputs. Created by function apollo_validateInputs . |
| functionality | <p>Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call <code>apollo_probabilities</code>, though the user can also call <code>apollo_probabilities</code> manually with a given functionality for testing/debugging. Possible values are:</p> <ul style="list-style-type: none"> • "components": For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations. • "conditionals": For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws. • "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws. • "gradient": For model estimation, produces analytical gradients of the likelihood, where possible. • "hessian": For model estimation, produces analytical Hessians of the likelihood, where possible. • "output": Prepares output for post-estimation reporting. • "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws. • "preprocess": Prepares likelihood functions for use in estimation. • "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws. • "report": Prepares output summarising model and choiceset structure. • "shares_LL": Produces overall model likelihood with constants only. • "utilities": Returns utilities at provided parameter values. |

- "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "zero_LL": Produces overall model likelihood with all parameters at zero.

Value

Argument P with (for most functionalities) the original contents averaged over inter-individual draws. Shape depends on argument functionality.

- "components": Returns P without changes.
- "conditionals": Returns P without averaging across draws. Drops all components except "model".
- "estimate": Returns P containing the likelihood of the model averaged across inter-individual draws. Drops all components except "model".
- "gradient": Returns P containing the gradient of the likelihood averaged across inter-individual draws. Drops all components except "model".
- "hessian": Returns P containing the Hessian of the likelihood averaged across inter-individual draws. Drops all components except "model".
- "output": Returns P containing the likelihood of all model components averaged across inter-individual draws.
- "prediction": Returns P containing the probabilities/likelihoods of all alternatives for all model components averaged across inter-individual draws.
- "preprocess": Returns P without changes.
- "raw": Returns P without changes.
- "report": Returns P without changes.
- "hessian": Returns P containing the likelihood, gradient and Hessian of the likelihood averaged across inter-individual draws. Drops all components except "model".
- "shares_LL": Return P with any matrix likelihood components averaged over inter-individual draws. If three-dimensional array components are present, the function stops with an error because intra-individual draws have not yet been averaged.
- "utilities": Returns P without changes.
- "validate": Returns P containing the likelihood of the model averaged across inter-individual draws. Drops all components except "model".
- "zero_LL": Return P with any matrix likelihood components averaged over inter-individual draws. If three-dimensional array components are present, the function stops with an error because intra-individual draws have not yet been averaged.

apollo_avgIntraDraws *Averages across intra-individual draws.*

Description

Averages observation-specific likelihood across intra-individual draws.

Usage

```
apollo_avgIntraDraws(P, apollo_inputs, functionality)
```

Arguments

- | | |
|---------------|--|
| P | List of vectors, matrices or 3-dim arrays. Likelihood of the model components. |
| apollo_inputs | List grouping most common inputs. Created by function apollo_validateInputs . |
| functionality | <p>Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call <code>apollo_probabilities</code>, though the user can also call <code>apollo_probabilities</code> manually with a given functionality for testing/debugging. Possible values are:</p> <ul style="list-style-type: none"> • "components": For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations. • "conditionals": For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws. • "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws. • "gradient": For model estimation, produces analytical gradients of the likelihood, where possible. • "output": Prepares output for post-estimation reporting. • "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws. • "preprocess": Prepares likelihood functions for use in estimation. • "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws. • "report": Prepares output summarising model and choiceset structure. • "shares_LL": Produces overall model likelihood with constants only. • "utilities": Returns utilities at provided parameter values. • "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws. • "zero_LL": Produces overall model likelihood with all parameters at zero. |

Value

Argument P with (for most functionalities) the original contents averaged over intra-individual draws. Shape depends on argument functionality.

- "components": Returns P without changes.
- "conditionals": Returns P containing the likelihood of the model averaged across intra-individual draws. Drops all components except for "model".
- "estimate": Returns P containing the likelihood of the model averaged across intra-individual draws. Drops all components except "model".
- "gradient": Returns P containing the gradient of the likelihood averaged across intra-individual draws. Drops all components except "model".
- "output": Returns P containing the likelihood of all model components averaged across intra-individual draws.
- "prediction": Returns P containing the probabilities of all alternatives for all model components averaged across intra-individual draws.
- "preprocess": Returns P without changes.
- "raw": Returns P without changes.
- "report": Returns P without changes.
- "shares_LL": Returns P with any three-dimensional likelihood components averaged over intra-individual draws.
- "utilities": Returns P without changes.
- "validate": Returns P containing the likelihood of the model averaged across intra-individual draws. Drops all components but "model".
- "zero_LL": Returns P with any three-dimensional likelihood components averaged over intra-individual draws.

apollo_basTest	<i>Ben-Akiva & Swait test</i>
----------------	-----------------------------------

Description

Carries out the Ben-Akiva & Swait test for non-nested models and reports the corresponding p-value.

Usage

```
apollo_basTest(model1, model2)
```

Arguments

model1	Either a character variable with the name (and possibly path) of a previously estimated model, or an estimated model in memory, as returned by apollo_estimate .
model2	Either a character variable with the name (and possibly path) of a previously estimated model, or an estimated model in memory, as returned by apollo_estimate .

Details

The two models need to both be discrete choice, and need to have been estimated on the same data.

Value

Ben-Akiva & Swait test p-value (invisibly)

apollo_bootstrap	<i>Bootstrap a model</i>
------------------	--------------------------

Description

Samples individuals with replacement from the database, and estimates the model for each sample.

Usage

```
apollo_bootstrap(
  apollo_beta,
  apollo_fixed,
  apollo_probabilities,
  apollo_inputs,
  estimate_settings = list(estimationRoutine = "bgw", maxIterations = 200, writeIter =
    FALSE, hessianRoutine = "none", printLevel = 2L, silent = FALSE, maxLik_settings =
    list()),
  bootstrap_settings = list(nRep = 30, samples = NA, calledByEstimate = FALSE, recycle =
    TRUE)
)
```

Arguments

- | | |
|----------------------|---|
| apollo_beta | Named numeric vector. Names and values for parameters. |
| apollo_fixed | Character vector. Names (as defined in apollo_beta) of parameters whose value should not change during estimation. |
| apollo_probabilities | Function. Returns probabilities of the model to be estimated. Must receive three arguments: <ul style="list-style-type: none"> • apollo_beta: Named numeric vector. Names and values of model parameters. • apollo_inputs: List containing options of the model. See apollo_validateInputs. • functionality: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL". |
| apollo_inputs | List grouping most common inputs. Created by function apollo_validateInputs . |
| estimate_settings | List. Options controlling the estimation process. See apollo_estimate . hessianRoutine="none" by default. |

`bootstrap_settings`

List containing settings for the sampling procedure. User input is required for all settings except those with a default or marked as optional.

- **calledByEstimate**: Logical. TRUE if `apollo_bootstrap` is called by `apollo_estimate`. FALSE by default.
- **nRep**: Numeric scalar. Number of times the model must be estimated with different samples. Default is 30.
- **recycle**: Logical. If TRUE, the function will look for old output files and append new repetitions to them. If FALSE, output files will be overwritten. TRUE by default.
- **samples**: Numeric matrix or data.frame. Optional argument. Must have as many rows as observations in the database, and as many columns as number of repetitions wanted. Each column represents a re-sample, and each element the number of times that observation must be included in the sample. If this argument is provided, then `nRep` is ignored. Note that this allows sampling at the observation rather than the individual level, which is not recommended for panel data.

Details

This function implements a basic block bootstrap. It estimates the model parameters on `nRep` different samples. Each new sample is constructed by sampling **with replacement** from the original full sample. Each new sample has as many individuals as the original sample, though some of them may be repeated. Sampling is done at the **individual** level, therefore if different individuals have different number of observations, each re-sample does not necessarily have the same number of observations.

By default, sampling is done at the individual level. If user-defined sampling rates are required, then the optional `bootstrap_settings$samples` argument can be provided. This also allows sampling at the observation level, which is not recommended for panel data.

For each sample, only the parameters and log-likelihood are estimated. Standard errors are not calculated (they may be added in future versions). The composition of the re-samples is stored in a file, but is stable with the same seed.

This function writes three different files to the working or output directory:

- `modelName_bootstrap_params.csv`: estimated parameters, final log-likelihood, and number of observations for each re-sample
- `modelName_bootstrap_samples.csv`: composition of each re-sample.
- `modelName_bootstrap_vcov.csv`: variance-covariance matrix of the estimated parameters across re-samples.

The first two files are updated throughout the run of this function, while the last one is only written once the function finishes.

When run, this function will look for the first two files above in the working/output directory. If they are found, the function will attempt to pick up re-sampling from where those files left off. This is useful in cases where the original bootstrapping was interrupted, or when additional re-sampling runs are to be performed.

Value

List with three elements.

- **estimates**: Matrix containing the parameter estimates for each repetition. As many rows as repetitions and as many columns as parameters.
- **LL**: Vector of final log-likelihoods of each repetition.
- **varcov**: Covariance matrix of the estimated parameters across the repetitions.

This function also writes three output files to the working/output directory, with the following names ('x' represents the model name):

- **x_bootstrap_params.csv**: Table containing the parameter estimates, log-likelihood, and number of observations for each repetition.
- **x_bootstrap_samples.csv**: Table containing the description of the sample used in each repetition. Same format than `bootstrap_settings$samples`.
- **x_bootstrap_vcov.csv**: Table containing the covariance matrix of estimated parameters across the repetitions.

apollo_checkArguments *Checks definitions of Apollo functions*

Description

Checks that the user-defined functions used by Apollo are correctly defined by the user.

Usage

```
apollo_checkArguments(
  apollo_probabilities = NA,
  apollo_randCoeff = NA,
  apollo_lcPars = NA
)
```

Arguments

apollo_probabilities	Function. Likelihood function as defined by the user.
apollo_randCoeff	Function. Used with mixing models. Constructs the random parameters of a mixing model. Receives two arguments: • apollo_beta: Named numeric vector. Names and values of model parameters. • apollo_inputs: The output of this function (<code>apollo_validateInputs</code>).
apollo_lcPars	Function. Used with latent class models. Constructs a list of parameters for each latent class. Receives two arguments: • apollo_beta: Named numeric vector. Names and values of model parameters. • apollo_inputs: The output of this function (<code>apollo_validateInputs</code>).

Details

It only checks that the functions have the correct definition of inputs. It does not run the functions.

Value

Returns (invisibly) TRUE if definitions are correct, and FALSE otherwise.

apollo_choiceAnalysis *Reports market share for subsamples*

Description

Compares market shares across subsamples in dataset, and conducts statistical tests.

Usage

```
apollo_choiceAnalysis(choiceAnalysis_settings, apollo_control, database)
```

Arguments

choiceAnalysis_settings

List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional.

- alternatives: Named numeric vector. Names of alternatives and their corresponding value in choiceVar. Note that these need not necessarily be the alternatives as defined in the model, but could e.g. relate to cheapest/most expensive.
- avail: Named list of numeric vectors or scalars. Availabilities of alternatives, one element per alternative. Names of elements must match those in alternatives. Values can be 0 or 1. A user can also specify avail=1 to indicate universal availability, or omit the setting completely.
- choiceVar: Numeric vector. Contains choices for all observations. It will usually be a column from the database. Values are defined in alternatives.
- explanators: data.frame. Variables determining subsamples of the database. Values in each column must describe a group or groups of individuals (e.g. socio-demographics). Most usually a subset of columns from the database.
- printToScreen: Logical. TRUE for returning output to screen as well as file. TRUE by default.
- rows: Boolean vector. Consideration of which rows to include. Length equal to the number of observations (nObs), with entries equal to TRUE for rows to include, and FALSE for rows to exclude. Default is "all", equivalent to rep(TRUE, nObs).

apollo_control List. Options controlling the running of the code. See [apollo_validateInputs](#).

database data.frame. Data used by model.

Details

Saves the output to a csv file in the working/output directory.

Value

Silently returns a matrix with alternatives as columns and, for each explanator, rows containing the mean when each alternative is chosen, the mean when it is not chosen, and the t-test comparing those means (H0: equivalence). The table is also written to a file called modelName_choiceAnalysis.csv and printed to screen.

apollo_classAlloc	<i>Calculates class allocation probabilities for a Latent Class model</i>
-------------------	---

Description

Calculates class allocation probabilities for a Latent Class model using a Multinomial Logit model and can also perform other operations based on the value of the functionality argument.

Usage

```
apollo_classAlloc(classAlloc_settings)
```

Arguments

classAlloc_settings

List of inputs of the MNL model. It should contain the following.

- **avail:** Named list of numeric vectors or scalars. Availabilities of classes, one element per class. Names of elements must match those in `classes`. Values can be 0 or 1. These can be scalars or vectors (of length equal to rows in the database). A user can also specify `avail=1` to indicate universal availability, or omit the setting completely.
- **classes:** Named vector. Names and values for the latent classes. Names must match the names used in `utilities` and `avail`, if provided.
- **componentName:** Character. Name given to model component. If not provided by the user, Apollo will set the name automatically according to the element in `P` to which the function output is directed.
- **rows:** Boolean vector. Consideration of which rows to include. Length equal to the number of observations (`nObs`), with entries equal to `TRUE` for rows to include, and `FALSE` for rows to exclude. Default is "all", equivalent to `rep(TRUE, nObs)`.
- **utilities:** Named list of deterministic utilities. Utilities of the classes in class allocation model. Names of elements must match those in `avail`, if provided.

Value

The returned object depends on the value of argument `functionality`, which it fetches from the calling stack (see [apollo_validateInputs](#)).

- "components": Same as "estimate".
- "conditionals": Same as "estimate".
- "estimate": List of vector/matrices/arrays with the allocation probabilities for each class.
- "gradient": List containing the class allocation probabilities and their analytical gradients.
- "hessian": List containing the likelihood, gradient and Hessian of the class allocation probabilities.
- "output": Same as "estimate".
- "prediction": Same as "estimate".
- "preprocess": Returns a list with pre-processed inputs, based on `classAlloc_settings`.
- "raw": Same as "estimate".
- "report": Same as "estimate".
- "shares_LL": List with probabilities for each class in an equal shares setting.
- "utilities": List of vectors/matrices/arrays. Returns a list with the utilities for all classes in class allocation model.
- "validate": Same as "estimate", but it also runs a set of tests to validate the function inputs.
- "zero_LL": List with probabilities for each class in an equal shares setting.

 apollo_cnl

Calculates Cross-Nested Logit probabilities

Description

Calculates the probabilities of a Cross-nested Logit model and can also perform other operations based on the value of the `functionality` argument.

Usage

```
apollo_cnl(cnl_settings, functionality)
```

Arguments

- | | |
|---------------------------|---|
| <code>cnl_settings</code> | <p>List of inputs of the CNL model. User input is required for all settings except those with a default or marked as optional.</p> <ul style="list-style-type: none"> • <code>alternatives</code>: Named numeric vector. Names of alternatives and their corresponding value in <code>choiceVar</code>. • <code>avail</code>: Named list of numeric vectors or scalars. Availabilities of alternatives, one element per alternative. Names of elements must match those in <code>alternatives</code>. Values can be 0 or 1. These can be scalars or vectors (of length equal to rows in the database). A user can also specify <code>avail=1</code> to indicate universal availability, or omit the setting completely. |
|---------------------------|---|

- **choiceVar**: Numeric vector. Contains choices for all observations. It will usually be a column from the database. Values are defined in alternatives.
- **cnlNests**: List of numeric scalars or vectors. Lambda parameters for each nest. Elements must be named according to nests. The lambda at the root is fixed to 1, and therefore does not need to be defined.
- **cnlStructure**: Numeric matrix. One row per nest and one column per alternative. Each element of the matrix is the alpha parameter of that (nest, alternative) pair.
- **componentName**: Character. Name given to model component. If not provided by the user, Apollo will set the name automatically according to the element in P to which the function output is directed.
- **utilities**: Named list of deterministic utilities. Utilities of the alternatives. Names of elements must match those in alternatives.
- **rows**: Boolean vector. Consideration of which rows to include. Length equal to the number of observations (nObs), with entries equal to TRUE for rows to include, and FALSE for rows to exclude. Default is "all", equivalent to rep(TRUE, nObs).

functionality Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call `apollo_probabilities`, though the user can also call `apollo_probabilities` manually with a given functionality for testing/debugging. Possible values are:

- **"components"**: For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations.
- **"conditionals"**: For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws.
- **"estimate"**: For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- **"gradient"**: Not implemented for CNL.
- **"output"**: Prepares output for post-estimation reporting.
- **"prediction"**: For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws.
- **"preprocess"**: Prepares likelihood functions for use in estimation.
- **"raw"**: For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
- **"report"**: Prepares output summarising model and choiceset structure.
- **"shares_LL"**: Produces overall model likelihood with constants only.
- **"utilities"**: Returns utilities at provided parameter values.
- **"validate"**: Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- **"zero_LL"**: Produces overall model likelihood with all parameters at zero.

Details

For the model to be consistent with utility maximisation, the estimated value of the lambda parameter of all nests should be between 0 and 1. Lambda parameters are inversely proportional to the correlation between the error terms of alternatives in a nest. If lambda=1, there is no relevant correlation between the unobserved utility of alternatives in that nest. Alpha parameters inside `cnlStructure` should be between 0 and 1. Using a transformation to ensure this constraint is satisfied is recommended for complex structures (e.g. logistic transformation).

Value

The returned object depends on the value of argument `functionality` as follows.

- `"components"`: Same as `"estimate"`
- `"conditionals"`: Same as `"estimate"`
- `"estimate"`: vector/matrix/array. Returns the probabilities for the chosen alternative for each observation.
- `"gradient"`: Not implemented.
- `"output"`: Same as `"estimate"` but also writes summary of input data to internal Apollo log.
- `"prediction"`: List of vectors/matrices/arrays. Returns a list with the probabilities for all alternatives, with an extra element for the chosen alternative probability.
- `"preprocess"`: Returns a list with pre-processed inputs, based on `cnl_settings`.
- `"raw"`: Same as `"prediction"`.
- `"report"`: List with tree structure and choice overview.
- `"shares_LL"`: vector/matrix/array. Returns the probability of the chosen alternative when only constants are estimated.
- `"utilities"`: Data frame containing individual IDs, observation numbers and utilities for each alternative, with unavailable alternatives set to NA.
- `"validate"`: Same as `"estimate"`.
- `"zero_LL"`: vector/matrix/array. Returns the probability of the chosen alternative when all parameters are zero.

apollo_combineModels	<i>Combines separate model components.</i>
----------------------	--

Description

Combines model components to create likelihood for overall model.

Usage

```
apollo_combineModels(
  P,
  apollo_inputs,
  functionality,
  components = NULL,
  asList = TRUE
)
```

Arguments

- | | |
|---------------|---|
| P | List of vectors, matrices or 3-dim arrays. Likelihood of the model components. |
| apollo_inputs | List grouping most common inputs. Created by function apollo_validateInputs . |
| functionality | <p>Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call <code>apollo_probabilities</code>, though the user can also call <code>apollo_probabilities</code> manually with a given functionality for testing/debugging. Possible values are:</p> <ul style="list-style-type: none"> • "components": For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations. • "conditionals": For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws. • "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws. • "gradient": For model estimation, produces analytical gradients of the likelihood, where possible. • "hessian": For model estimation, produces analytical gradients and Hessians of the likelihood, where possible. • "output": Prepares output for post-estimation reporting. • "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws. • "preprocess": Prepares likelihood functions for use in estimation. • "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws. • "report": Prepares output summarising model and choicest structure. • "shares_LL": Produces overall model likelihood with constants only. • "utilities": Returns utilities at provided parameter values. • "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws. • "zero_LL": Produces overall model likelihood with all parameters at zero. |

components	Character vector. Optional argument. Names of elements in P that should be multiplied to construct the whole model likelihood. If a single element is provided, it is interpreted as a regular expression. Default is to include all components in P.
asList	Logical. Only used if functionality is "conditionals", "estimate", "validate", "zero_LL", "shares_LL" or "output". If TRUE, it will return a list as described in the 'Value' section. If FALSE, it will only return a vector/matrix/3-dim array of the product of likelihoods inside P. Default is TRUE.

Details

This function should be called inside `apollo_probabilities` after all model components have been produced.

It should be called before `apollo_avgInterDraws`, `apollo_avgIntraDraws`, `apollo_panelProd` and `apollo_prepareProb`, whichever apply, except where these functions are called inside any latent class components of the overall model.

Value

Argument P with (for most functionalities) an extra element called "model", which is the product of all the other elements. Shape depends on argument functionality.

- "components": Returns P without changes.
- "conditionals": Returns P with an extra component called "model", which is the product of all other elements of P.
- "estimate": Returns P with an extra component called "model", which is the product of all other elements of P.
- "gradient": Returns a list containing only "model", with the combined likelihood and gradient after applying the product rule across model components.
- "hessian": Returns a list containing the combined likelihood, gradient and Hessian after applying the product rule across model components.
- "output": Returns P with an extra component called "model", which is the product of all other elements of P.
- "prediction": Returns P without changes.
- "preprocess": Returns P without changes.
- "raw": Returns P without changes.
- "report": Returns P without changes.
- "shares_LL": Returns P with an extra component called "model", which is the product of all other elements of P.
- "utilities": Returns P without changes.
- "validate": Returns P with an extra component called "model", which is the product of all other elements of P.
- "zero_LL": Returns P with an extra component called "model", which is the product of all other elements of P.

apollo_combineResults *Write model results to file*

Description

Writes results from various models to a single csv file.

Usage

```
apollo_combineResults(combineResults_settings = NULL)
```

Arguments

combineResults_settings

List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional.

- estimateDigits: Numeric scalar. Number of decimal places to print for estimates. Default is 4.
- modelNames: Character vector. Optional names of models to combine. Omit or use an empty vector to combine results from all models in the working/output directory.
- pDigits: Numeric scalar. Number of decimal places to print for p-values. Default is 2.
- printClassical: Boolean. TRUE for printing classical standard errors. FALSE by default.
- printPVal: Boolean. TRUE for printing p-values. FALSE by default.
- printT1: Boolean. If TRUE, t-test for $H_0: \text{apollo_beta}=1$ are printed. FALSE by default.
- sortByDate: Boolean. If TRUE, models are ordered by date. Default is TRUE.
- tDigits: Numeric scalar. Number of decimal places to print for t-ratios values. Default is 2.

Value

Invisibly returns TRUE, and writes a file called `model_comparison_[date].csv` in the working/output directory.

apollo_compareInputs	<i>Compares the content of apollo_inputs to its counterparts in the global environment</i>
----------------------	--

Description

Compares the content of apollo_inputs to its counterparts in the global environment

Usage

```
apollo_compareInputs(apollo_inputs)
```

Arguments

apollo_inputs List grouping most common inputs. Created by function [apollo_validateInputs](#).

Value

Logical. Invisibly returns TRUE if the content of apollo_inputs is the same as the corresponding objects in the global environment, and FALSE otherwise.

apollo_conditionals	<i>Calculates conditionals</i>
---------------------	--------------------------------

Description

Calculates posterior expected values (conditionals) of random coefficient models (continuous or discrete mixtures/latent class)

Usage

```
apollo_conditionals(model, apollo_probabilities, apollo_inputs)
```

Arguments

model Model object. Estimated model object as returned by function [apollo_estimate](#).

apollo_probabilities

Function. Returns probabilities of the model to be estimated. Must receive three arguments:

- apollo_beta: Named numeric vector. Names and values of model parameters.
- apollo_inputs: List containing options of the model. See [apollo_validateInputs](#).
- functionality: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "hessian", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL".

apollo_inputs List grouping most common inputs. Created by function [apollo_validateInputs](#).

Details

This functions is only meant for use with models using either continuous distributions or latent classes, not both at the same time.

Value

Depends on whether the model uses continuous mixtures or latent class.

- If the model contains a continuous mixture, the function returns a list of matrices. Each matrix has dimensions nIndiv x 3. One matrix per random component. Each row of each matrix contains the indivID of an individual, and the posterior mean and s.d. of this random component for this individual.
- If the model contains latent classes, the function returns a matrix with the posterior class allocation probabilities for each individual.
- If the model contains both continuous mixtures and latent classes, the function fails.

apollo_deltaMethod	<i>Delta method for Apollo models</i>
--------------------	---------------------------------------

Description

Applies the Delta method to calculate the standard errors of transformations of parameters.

Usage

```
apollo_deltaMethod(model, deltaMethod_settings)
```

Arguments

- | | |
|----------------------|--|
| model | Model object. Estimated model object as returned by function apollo_estimate . |
| deltaMethod_settings | <p>List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional.</p> <ul style="list-style-type: none"> • expression: Character vector. A character vector with a single or multiple arbitrary functions of the estimated parameters, as text. For example: <code>c(VTT="b1/b2*60")</code>. Each expression can only contain model parameters (estimated or fixed), numeric values, and operands. At least one of the parameters used needs to not have been fixed in estimation. Variables in the database cannot be included. If the user does not provide a name for an expression, then the expression itself is used in the output. If this setting is provided, then operation, parName1, parName2, multPar1 and multPar2 are ignored. • allPairs: Logical. If set to TRUE, Delta method calculations are carried out for the ratio and difference for all pairs of parameters and returned as two separate matrices with values and t-ratios. FALSE by default. |

- **varcov**: Character. Type of variance-covariance matrix to use in calculations. It can take values "classical", "robust" and "bootstrap". Default is "robust".
- **printPVal**: Logical or Scalar. TRUE or 1 for printing p-values for one-sided test, 2 for printing p-values for two-sided test, FALSE for not printing p-values. FALSE by default.
- **operation**: Character. Function to calculate the delta method for. See details. Not used if expression is provided.
- **parName1**: Character. Name of the first parameter if operation is used. See details. Not used if expression is provided.
- **parName2**: Character. Name of the second parameter if operation is used. See details. Not used if expression is provided.. Optional depending on operation.
- **multPar1**: Numeric scalar. An optional value to scale parName1. Not used if expression is provided. Default is 1.
- **multPar2**: Numeric scalar. An optional value to scale parName2. Not used if expression is provided. Default is 1.

Details

apollo_deltaMethod can be used in two ways. The first and recommended way is to provide an element called expression inside its argument deltaMethod_settings. expression should contain the expression or expressions for which the standard error is/are to be calculated, as text. For example, to calculate the ratio between parameters b1 and b2, expression=c(vtt="b1/b2") should be used.

The second method is to provide the name of a specific operation inside deltaMethod_settings. The following seven operations are supported.

- **diff**: Calculates the s.e. of parName1 - parName2 and parName2 - parName1
- **exp**: Calculates the s.e. of exp(parName1)
- **logistic**: If only parName1 is provided, it calculates the s.e. of $\exp(\text{parName1}) / (1 + \exp(\text{parName1}))$ and $1 / (1 + \exp(\text{parName1}))$. If parName1 and parName2 are provided, it calculates $\exp(\text{par}_i) / (1 + \exp(\text{parName1}) + \exp(\text{parName2}))$ for $i=1, 2$, and 3 ($\text{par}_3 = 1$).
- **lognormal**: Calculates the mean and s.d. of a lognormal distribution based on the mean (parName1) and s.d. (parName2) of the underlying normal.
- **prod**: Calculates the s.e. of parName1*parName2
- **ratio**: Calculates the s.e. of parName1/parName2 and parName2/parName1
- **sum**: Calculates the s.e. of parName1 + parName2

By default, apollo_deltaMethod uses the robust covariance matrix. However, the user can change this through the varcov setting.

Value

Invisibly returns a matrix containing the value, standard error and t-ratio resulting from the requested expression or operation. If printPVal is not FALSE, p-values are also included. If allPairs=TRUE,

invisibly returns a list containing the requested expression/operation output, if any, as well as matrices of values, standard errors and t-ratios for all pairwise ratios and differences. Results are also printed to screen, and pairwise results are written to CSV files when allPairs=TRUE.

apollo_detach	<i>Detaches parameters and the database.</i>
---------------	--

Description

Detaches variables attached by [apollo_attach](#).

Usage

```
apollo_detach(apollo_beta = NA, apollo_inputs = NA)
```

Arguments

apollo_beta Named numeric vector. Names and values for parameters.
apollo_inputs List grouping most common inputs. Created by function [apollo_validateInputs](#).

Details

This function detaches the variables attached by [apollo_attach](#). It should be called at the end of `apollo_probabilities`, only if [apollo_attach](#) was called at the beginning. This can also be achieved by adding the line `on.exit(apollo_detach(apollo_beta, apollo_inputs))` right after calling [apollo_attach](#). This function can also be called without any arguments, i.e. `apollo_detach()`.

Value

Invisibly returns NULL.

apollo_dft	<i>Calculate DFT probabilities</i>
------------	------------------------------------

Description

Calculate probabilities of a Decision Field Theory (DFT) model and can also perform other operations based on the value of the `functionality` argument.

Usage

```
apollo_dft(dft_settings, functionality)
```

Arguments

- | | |
|---------------|--|
| dft_settings | <p>List of settings for the DFT model. It should contain the following elements.</p> <ul style="list-style-type: none"> • alternatives: Named numeric vector. Names of alternatives and their corresponding value in choiceVar. • avail: Named list of numeric vectors or scalars. Availabilities of alternatives, one element per alternative. Names of elements must match those in alternatives. Values can be 0 or 1. These can be scalars or vectors (of length equal to rows in the database). A user can also specify <code>avail=1</code> to indicate universal availability, or omit the setting completely. • altStart: A named list with as many elements as alternatives. Each element can be a scalar or vector containing the starting preference value for the alternative. If omitted, starting values are set to zero for all alternatives. • attrScalings: A named list with as many elements as attributes, or fewer. Each element is a factor that scale the attribute, and can be a scalar, a vector or a matrix/array. They do not need to add up to one for each observation. <code>attrWeights</code> and <code>attrScalings</code> are incompatible, and they should not be both defined for an attribute. Default is 1 for all attributes. • attrValues: A named list with as many elements as alternatives. Each element is itself a named list of vectors of the alternative attributes for each observation (usually a column from the database). All alternatives must have the same attributes (can be set to zero if not relevant). • attrWeights: A named list with as many elements as attributes, or fewer. Each element is the weight of the attribute, and can be a scalar, a vector with as many elements as observations, or a matrix/array if random. They should add up to one for each observation and draw, if present, and will be re-scaled if they do not. <code>attrWeights</code> and <code>attrScalings</code> are incompatible, and they should not both be defined for an attribute. If omitted, equal weights across attributes are used. • choiceVar: Numeric vector. Contains choices for all observations. It will usually be a column from the database. Values are defined in <code>alternatives</code>. • componentName: Character. Name given to model component. If not provided by the user, Apollo will set the name automatically according to the element in P to which the function output is directed. • procPars: A list containing the four DFT 'process parameters' <ul style="list-style-type: none"> – error_sd: Numeric scalar or vector. The standard deviation of the error term in each timestep. – timesteps: Numeric scalar or vector. Number of timesteps to consider. Should be an integer bigger than 0. – phi1: Numeric scalar or vector. Sensitivity. – phi2: Numeric scalar or vector. Process parameter. • rows: Boolean vector. Consideration of which rows to include. Length equal to the number of observations (<code>nObs</code>), with entries equal to <code>TRUE</code> for rows to include, and <code>FALSE</code> for rows to exclude. Default is "all", equivalent to <code>rep(TRUE, nObs)</code>. |
| functionality | <p>Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call <code>apollo_probabilities</code>,</p> |

though the user can also call `apollo_probabilities` manually with a given functionality for testing/debugging. Possible values are:

- "components": For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations.
- "conditionals": For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws.
- "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "gradient": Not implemented for DFT.
- "output": Prepares output for post-estimation reporting.
- "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws.
- "preprocess": Prepares likelihood functions for use in estimation.
- "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
- "report": Prepares output summarising model and choiceset structure.
- "shares_LL": Produces overall model likelihood with constants only.
- "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "zero_LL": Produces overall model likelihood with all parameters at zero.

Value

The returned object depends on the value of argument `functionality` as follows.

- "components": Same as "estimate"
- "conditionals": Same as "estimate"
- "estimate": vector/matrix/array. Returns the probabilities for the chosen alternative for each observation.
- "gradient": Not implemented.
- "output": Same as "estimate".
- "prediction": List of vectors/matrices/arrays. Returns a list with the probabilities for all alternatives, with an extra element for the chosen alternative probability.
- "preprocess": Returns a list with pre-processed inputs, based on `dft_settings`.
- "raw": Same as "prediction"
- "report": Choice overview.
- "shares_LL": Not implemented. Returns a vector of NA with as many elements as observations.
- "validate": Same as "estimate"
- "zero_LL": vector/matrix/array. Returns the probability of the chosen alternative when all parameters are zero.

References

Hancock, T.; Hess, S. and Choudhury, C. (2018) Decision field theory: Improvements to current methodology and comparisons with standard choice modelling techniques. *Transportation Research* 107B, 18 - 40. Hancock, T.; Hess, S.; Marley A.A.J. and Choudhury, C. (2021), An accumulation of preference: two alternative dynamic models for understanding transport choices, *Transportation Research Part B*, Volume 149, July 2021, Pages 250-282. Roe, R.; Busemeyer, J. and Townsend, J. (2001) Multialternative decision field theory: A dynamic connectionist model of decision making. *Psychological Review* 108, 370

apollo_diagnostics	<i>Print diagnostics for model inputs Prints diagnostic summaries for a model component, including choice summaries, availability summaries, and selected parameter or structure diagnostics depending on the model type.</i>
--------------------	---

Description

Print diagnostics for model inputs Prints diagnostic summaries for a model component, including choice summaries, availability summaries, and selected parameter or structure diagnostics depending on the model type.

Usage

```
apollo_diagnostics(inputs, modelType, apollo_inputs, data = TRUE, param = TRUE)
```

Arguments

inputs	List of settings
modelType	Character. Type of model. Supported values include "mnl", "nl", "cnl", "dft", "el", "fmnl", "normd", "ol", "op", "mdcev", "mdcnev" and "lc".
apollo_inputs	List of main inputs to the model estimation process. See apollo_validateInputs .
data	Boolean. TRUE for printing report related to dependent and independent variables. FALSE for not printing it. Default is TRUE.
param	Boolean. TRUE for printing report related to estimated parameters (e.g. model structure). FALSE for not printing it. Default is TRUE.

Value

Invisibly returns TRUE if no error happened during execution.

apollo_drugChoiceData *Simulated dataset of medication choice.*

Description

A simulated dataset containing 10,000 stated medication choices among four alternatives.

Usage

```
apollo_drugChoiceData
```

Format

A data.frame with 10,000 rows and 33 variables:

ID Numeric. Identification number of the individual.

task Numeric. Index of choice situations for each individual, going from 1 to 10.

best Numeric. Index of alternative selected as best option.

second_pref Numeric. Index of alternative selected as second-best option.

third_pref Numeric. Index of alternative selected as third-best option.

worst Numeric. Index of alternative selected as worst option.

brand_1 Character. Brand for alternative 1.

country_1 Character. Country of origin for alternative 1.

char_1 Character. Characteristics of alternative 1 (standard, fast acting, or double strength).

side_effects_1 Numeric. Chance of suffering negative side effects with alternative 1 (out of 100,000).

price_1 Numeric. Cost of alternative 1 in Pounds sterling (GBP).

brand_2 Character. Brand for alternative 2.

country_2 Character. Country of origin for alternative 2.

char_2 Character. Characteristics of alternative 2 (standard, fast acting, or double strength).

side_effects_2 Numeric. Chance of suffering negative side effects with alternative 2 (out of 100,000).

price_2 Numeric. Cost of alternative 2 in Pounds sterling (GBP).

brand_3 Character. Brand for alternative 3.

country_3 Character. Country of origin for alternative 3.

char_3 Character. Characteristics of alternative 3 (standard, fast acting, or double strength).

side_effects_3 Numeric. Chance of suffering negative side effects with alternative 3 (out of 100,000).

price_3 Numeric. Cost of alternative 3 in Pounds sterling (GBP).

brand_4 Character. Brand for alternative 4.

country_4 Character. Country of origin for alternative 4.

char_4 Character. Characteristics of alternative 4 (standard, fast acting, or double strength).

side_effects_4 Numeric. Chance of suffering negative side effects with alternative 4 (out of 100,000).

- price_4** Numeric. Cost of alternative 4 in Pounds sterling (GBP).
- regular_user** Numeric. 1 if the respondent is a regular user of headache medicine, 0 otherwise.
- university_educated** Numeric. 1 if the respondent holds a university degree, 0 otherwise.
- over_50** Numeric. 1 if the respondent is 50 years old or older, 0 otherwise.
- attitude_quality** Numeric. Level of agreement from 1 (strongly disagree) to 5 (strongly agree) with the phrase 'I am concerned about the quality of drugs developed by unknown companies'.
- attitude_ingredients** Numeric. Level of agreement from 1 (strongly disagree) to 5 (strongly agree) with the phrase 'I believe that ingredients are the same no matter what brand'.
- attitude_patent** Numeric. Level of agreement from 1 (strongly disagree) to 5 (strongly agree) with the phrase 'The original patent holders have valuable experience with their medicines'.
- attitude_dominance** Numeric. Level of agreement from 1 (strongly disagree) to 5 (strongly agree) with the phrase 'I believe the dominance of big pharmaceutical companies is unhelpful'.

Details

This dataset is to be used for discrete choice modelling. Data comes from 1,000 individuals, each with ten stated choice (SC) scenarios involving choices among headache medication. There are 10,000 choices in total. Data is simulated. Each observation contains attributes of the alternatives, characteristics of the respondent, and their answers to four attitudinal questions. All four alternatives are always available for all individuals. Alternatives 1 and 2 are branded, while alternatives 3 and 4 are generic. Respondents provide a full ranking of alternatives for each choice task (i.e. observation).

Source

<https://www.ApolloChoiceModelling.com/>

apollo_dVdB	<i>Calculates gradients of utility functions</i>
-------------	--

Description

Calculates gradients (derivatives) of utility functions.

Usage

```
apollo_dVdB(apollo_beta, apollo_inputs, V)
```

Arguments

- apollo_beta** Named numeric vector of parameters.
- apollo_inputs** List grouping most common inputs. Created by function [apollo_validateInputs](#).
- V** Named list of functions. Each function defines the deterministic utility for one alternative.

Value

Named list. Each element is itself a list of functions: the partial derivatives of the elements of V.

apollo_dVdB0ld	<i>Calculates gradients of utility functions</i>
----------------	--

Description

Calculates gradients (derivatives) of utility functions.

Usage

apollo_dVdB0ld(apollo_beta, apollo_inputs, V)

Arguments

- apollo_beta Named numeric vector of parameters.
- apollo_inputs List grouping most common inputs. Created by function [apollo_validateInputs](#).
- V List of functions

Value

Named list. Each element is a function that returns a list, where each element is the partial derivatives of the elements of V.

apollo_el	<i>Calculates Exploded Logit probabilities</i>
-----------	--

Description

Calculates the probabilities of an Exploded Logit model and can also perform other operations based on the value of the functionality argument.

Usage

apollo_el(el_settings, functionality)

Arguments

- | | |
|---------------|--|
| el_settings | <p>List of inputs of the Exploded Logit model. It should contain the following.</p> <ul style="list-style-type: none"> • alternatives: Named numeric vector. Names of alternatives and their corresponding value in choiceVar. • avail: Named list of numeric vectors or scalars. Availabilities of alternatives, one element per alternative. Names of elements must match those in alternatives. Values can be 0 or 1. These can be scalars or vectors (of length equal to rows in the database). A user can also specify avail=1 to indicate universal availability, or omit the setting completely. • choiceVars: List of numeric vectors. Contain choices for each position of the ranking. The list must be ordered with the best choice first, second best second, etc. It will usually be a list of columns from the database. Use value -1 if a stage does not apply for a given observations (e.g. when some individuals have shorter rankings). • componentName: Character. Name given to model component. If not provided by the user, Apollo will set the name automatically according to the element in P to which the function output is directed. • utilities: Named list of deterministic utilities. Utilities of the alternatives. Names of elements must match those in alternatives. • rows: Boolean vector. Consideration of which rows to include. Length equal to the number of observations (nObs), with entries equal to TRUE for rows to include, and FALSE for rows to exclude. Default is "all", equivalent to rep(TRUE, nObs). • scales: List of vectors. Scale factors of each Logit model. At least one element should be normalized to 1. If omitted, scale=1 for all positions is assumed. |
| functionality | <p>Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call <code>apollo_probabilities</code>, though the user can also call <code>apollo_probabilities</code> manually with a given functionality for testing/debugging. Possible values are:</p> <ul style="list-style-type: none"> • "components": For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations. • "conditionals": For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws. • "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws. • "gradient": Not implemented for exploded logit models. • "output": Prepares output for post-estimation reporting. • "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws. • "preprocess": Prepares likelihood functions for use in estimation. • "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws. |

- "report": Prepares output summarising model and choiceset structure.
- "shares_LL": Produces overall model likelihood with constants only.
- "utilities": Returns utilities at provided parameter values.
- "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "zero_LL": Produces overall model likelihood with all parameters at zero.

Details

The function calculates the probability of a ranking as a product of Multinomial Logit models with gradually reducing availability, where scale differences can be allowed for.

Value

The returned object depends on the value of argument `functionality` as follows.

- "components": Same as "estimate"
- "conditionals": Same as "estimate"
- "estimate": vector/matrix/array. Returns the probabilities for the chosen alternative for each observation.
- "gradient": Not implemented. Returns NA.
- "output": Same as "estimate".
- "prediction": Not applicable (NA).
- "preprocess": Returns a list with pre-processed inputs, based on `el_settings`.
- "raw": Same as "estimate"
- "report": Choice overview across stages.
- "shares_LL": Not implemented. Returns a vector of NA with as many elements as observations.
- "utilities": Data frame containing individual IDs, observation numbers and utilities for each alternative, with unavailable alternatives set to 0 and excluded rows set to NA.
- "validate": Same as "estimate"
- "zero_LL": vector/matrix/array. Returns the probability of the chosen alternative when all parameters are zero.

apollo_emdc

MDC model with exogenous budget

Description

Calculates the likelihood function of the MDC model with exogenous budget. Can also predict and validate inputs.

Usage

```
apollo_emdc(emdc_settings, functionality = "estimate")
```

Arguments

- emdc_settings** List of settings for the model. It includes the following.
- **avail**: Named list of numeric vectors. Availability of each product. Can also be called "A".
 - **budget**: Optional numeric vector. Budget. Must be bigger than the expenditure on all inside goods. Can also be called "B".
 - **cost**: Named list of numeric vectors. Price of each product.
 - **delta**: Lower triangular numeric matrix, or list of lists. Complementarity/substitution parameter.
 - **continuousChoice**: Named list of numeric vectors. Amount consumed of each inside good. Outside good must not be included. Can also be called "X".
 - **gamma**: Named list of numeric vectors. Satiation parameter of each product.
 - **nRep**: Scalar positive integer. Number of repetitions used when prediction
 - **sigma**: Numeric vector or scalar. Standard deviation of the error term. Default is one.
 - **timeLimit**: Positive scalar. Maximum amount of seconds the optimiser can spend calculating a prediction before setting it to NA.
 - **tol**: Positive scalar. Tolerance of the prediction algorithm.
 - **utilities**: Named list of numeric vectors (or matrices or arrays). Base utility of each product. Can also be called "V".
 - **utilityOutside**: Numeric vector (or matrix or array). Shadow price of the budget. Must be normalised to 0 for at least one individual. Default is 0 for every observation. Can also be called "V0".
- functionality** Character. Either "validate", "zero_LL", "estimate", "conditionals", "raw", "output" or "prediction"

Details

This model extends the traditional multiple discrete-continuous (MDC) framework by (i) making the marginal utility of the outside good deterministic, and (ii) including complementarity and substitution in the model formulation. See the following paper for more details:

Palma, D. & Hess, S. (2022) Extending the Multiple Discrete Continuous (MDC) modelling framework to consider complementarity, substitution, and an unobserved budget. *Transportation Research 161B*, 13 - 35. <https://doi.org/10.1016/j.trb.2022.04.005>

Value

The returned object depends on the value of argument `functionality` as follows.

- **"estimate"**: vector/matrix/array. Returns the probabilities for the chosen alternative for each observation.

- "prediction": List of vectors/matrices/arrays. Returns a list with the probabilities for all alternatives, with an extra element for the probability of the chosen alternative.
- "validate": Same as "estimate", but it also runs a set of tests to validate the function inputs.
- "zero_LL": vector/matrix/array. Returns the probability of the chosen alternative when all parameters are zero.
- "conditionals": Same as "estimate"
- "output": Same as "estimate" but also writes summary of input data to internal Apollo log.
- "raw": Same as "prediction"

apollo_emdc1

MDC model with exogenous budget

Description

Calculates the likelihood function of the MDC model with exogenous budget. Can also predict and validate inputs.

Usage

```
apollo_emdc1(emdc_settings, functionality = "estimate")
```

Arguments

- emdc_settings List of settings for the model. It includes the following.
- avail: Named list of numeric vectors. Availability of each product. Can also be called "A".
 - budget: Numeric vector. Budget. Must be bigger than the expenditure on all inside goods. Can also be called "B".
 - continuousChoice: Named list of numeric vectors. Amount consumed of each inside good. Outside good must not be included. Can also be called "X".
 - cost: Named list of numeric vectors. Price of each product.
 - delta: Lower triangular numeric matrix, or list of lists. Complementarity/substitution parameter.
 - gamma: Named list of numeric vectors. Satiation parameter of each product.
 - nRep: Scalar positive integer. Number of repetitions used when prediction
 - sigma: Numeric vector or scalar. Standard deviation of the error term. Default is one.
 - timeLimit: Positive scalar. Maximum amount of seconds the optimiser can spend calculating a prediction before setting it to NA.
 - tol: Positive scalar. Tolerance of the prediction algorithm.
 - utilities: Named list of numeric vectors (or matrices or arrays). Base utility of each product. Can also be called "V".

- **utilityOutside**: Numeric vector (or matrix or array). Shadow price of the budget. Must be normalised to 0 for at least one individual. Default is 0 for every observation. Can also be called "V0".
- functionality** Character. Either "validate", "zero_LL", "estimate", "conditionals", "raw", "output" or "prediction"

Details

This model extends the traditional multiple discrete-continuous (MDC) framework by (i) making the marginal utility of the outside good deterministic, and (ii) including complementarity and substitution in the model formulation. See the following paper for more details:

Palma, D. & Hess, S. (2022) Extending the Multiple Discrete Continuous (MDC) modelling framework to consider complementarity, substitution, and an unobserved budget. *Transportation Research 161B*, 13 - 35. <https://doi.org/10.1016/j.trb.2022.04.005>

Value

The returned object depends on the value of argument `functionality` as follows.

- **"estimate"**: vector/matrix/array. Returns the probabilities for the chosen alternative for each observation.
- **"prediction"**: List of vectors/matrices/arrays. Returns a list with the probabilities for all alternatives, with an extra element for the probability of the chosen alternative.
- **"validate"**: Same as "estimate", but it also runs a set of tests to validate the function inputs.
- **"zero_LL"**: vector/matrix/array. Returns the probability of the chosen alternative when all parameters are zero.
- **"conditionals"**: Same as "estimate"
- **"output"**: Same as "estimate" but also writes summary of input data to internal Apollo log.
- **"raw"**: Same as "prediction"

apollo_emdc2

Extended MDC

Description

Calculates the likelihood function of the extended MDC model. Can also predict and validate inputs.

Usage

```
apollo_emdc2(emdc_settings, functionality = "estimate")
```

Arguments

- emdc_settings** List of settings for the model. It includes the following.
- **avail**: Named list of numeric vectors. Availability of each product. Can also be called "A".
 - **continuousChoice**: Named list of numeric vectors. Amount consumed of each inside good. Outside good must not be included. Can also be called "X".
 - **cost**: Named list of numeric vectors. Price of each product.
 - **delta**: Lower triangular numeric matrix, or list of lists. Complementarity/substitution parameter.
 - **gamma**: Named list of numeric vectors. Satiation parameter of each product.
 - **sigma**: Numeric scalar. Scale parameter.
 - **nIter**: Vector of two positive integers. Number of maximum iterations used during prediction, for the upper and lower iterative levels.
 - **nRep**: Scalar positive integer. Number of repetitions used when predictiong
 - **rawPrediction**: Scalar logical. When functionality is equal to "prediction", it returns the full set of simulations. Defaults is FALSE.
 - **tolerance**: Positive scalar Tolerance of the prediction algorithm.
 - **utilities**: Named list of numeric vectors (or matrices or arrays). Base utility of each product. Can also be called "V".
 - **utilityOutside**: Numeric vector (or matrix or array). Shadow price of the budget. Must be normalised to 0 for at least one individual. Default is 0 for every observation. Can also be called "V0".
- functionality** Character. Either "validate", "zero_LL", "estimate", "conditionals", "raw", "output" or "prediction"

Details

This model extends the traditional multiple discrete-continuous (MDC) framework by (i) dropping the need to define a budget, (ii) making the marginal utility of the outside good deterministic, and (iii) including complementarity and substitution in the model formulation. See the following paper for more details:

Palma, D. & Hess, S. (2022) Extending the Multiple Discrete Continuous (MDC) modelling framework to consider complementarity, substitution, and an unobserved budget. *Transportation Research 161B*, 13 - 35. <https://doi.org/10.1016/j.trb.2022.04.005>

Value

The returned object depends on the value of argument `functionality` as follows.

- **"estimate"**: vector/matrix/array. Returns the probabilities for the chosen alternative for each observation.
- **"prediction"**: List of vectors/matrices/arrays. Returns a list with the probabilities for all alternatives, with an extra element for the probability of the chosen alternative.
- **"validate"**: Same as "estimate", but it also runs a set of tests to validate the function inputs.

- "zero_LL": vector/matrix/array. Returns the probability of the chosen alternative when all parameters are zero.
- "conditionals": Same as "estimate"
- "output": Same as "estimate" but also writes summary of input data to internal Apollo log.
- "raw": Same as "prediction"

apollo_estimate	<i>Estimates model</i>
-----------------	------------------------

Description

Estimates a model using the likelihood function defined by `apollo_probabilities`.

Usage

```
apollo_estimate(
  apollo_beta,
  apollo_fixed,
  apollo_probabilities,
  apollo_inputs,
  estimate_settings = NA
)
```

Arguments

- | | |
|-----------------------------------|---|
| <code>apollo_beta</code> | Named numeric vector. Names and values for parameters. |
| <code>apollo_fixed</code> | Character vector. Names (as defined in <code>apollo_beta</code>) of parameters whose value should not change during estimation. |
| <code>apollo_probabilities</code> | Function. Returns probabilities of the model to be estimated. Must receive three arguments: <ul style="list-style-type: none"> • <code>apollo_beta</code>: Named numeric vector. Names and values of model parameters. • <code>apollo_inputs</code>: List containing options of the model. See apollo_validateInputs. • <code>functionality</code>: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "hessian", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL". |
| <code>apollo_inputs</code> | List grouping most common inputs. Created by function apollo_validateInputs . |
| <code>estimate_settings</code> | List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional. <ul style="list-style-type: none"> • <code>bgw_settings</code>: List. Additional arguments to the BGW optimisation method. See bgw_mle for more details. Default is an empty list, with missing BGW entries filled internally. |

- **bootstrapSE**: Numeric. Number of bootstrap samples to calculate standard errors. Default is 0, meaning no bootstrap s.e. will be calculated. Number must zero or a positive integer. Only used if `apollo_control$HB` is FALSE.
- **bootstrapSeed**: Numeric scalar (integer). Random number generator seed to generate the bootstrap samples. Only used if `bootstrapSE>0`. Default is 24.
- **constraints**: Character vector. Linear constraints on parameters to estimate. For example `c('b1>0', 'b1 + 2*b2>1')`. Only `>`, `<` and `=` can be used. Inequalities cannot be mixed with equality constraints, e.g. `c(b1-b2=0, b2>0)` will fail. All parameter names must be on the left side. Fixed parameters cannot go into constraints. Alternatively, constraints can be defined as in [maxLik](#). Constraints can only be used with maximum likelihood estimation and the BFGS routine in particular.
- **convergenceCheck**: Logical. Checks gradient-based convergence for BGW estimation. Default is FALSE.
- **estimationRoutine**: Character. Estimation method. Can take values "bfgs", "bgw", "bhhh", or "nr". Used only if `apollo_control$HB` is FALSE. Default is "bgw".
- **forceCovarianceMatrix**: Logical. Forces the computation of the covariance matrix even if a model has not converged. Default is FALSE.
- **hessianRoutine**: Character. Name of routine used to calculate the Hessian of the log-likelihood function after estimation. Valid values are "analytic" (default), "numDeriv" (to use the numeric routine in package `numDeriv`), "maxLik" (to use the numeric routine in package `maxLik`), and "none" to avoid calculating the Hessian and the covariance matrix. Only used if `apollo_control$HB=FALSE`.
- **load**: Environment. Optional environment containing previously saved pre-processing objects to reuse. NULL by default.
- **maxIterations**: Numeric. Maximum number of iterations of the estimation routine before stopping. Used only if `apollo_control$HB` is FALSE. Default is 200.
- **maxLik_settings**: List. Additional settings for `maxLik`. See argument control in [maxBFGS](#), [maxBHHH](#) and [maxNM](#) for more details. Only used for maximum likelihood estimation. If omitted, `printLevel` and `iterlim` are set from `estimate_settings$printLevel` and `estimate_settings$maxIterations`.
- **numDeriv_method**: Character. Method used for numerical differentiation when calculating the covariance matrix. Can be "Richardson" or "simple". Default is "Richardson". See argument method in [grad](#) for more details.
- **numDeriv_settings**: List. Additional arguments to the method used by `numDeriv` to calculate the Hessian. See argument method.args in [grad](#) for more details. Default is an empty list.
- **printLevel**: Higher values render more verbose output. Can take values 0, 1, 2 or 3. Ignored if `apollo_control$HB` is TRUE. Default is 3, but if `estimationRoutine="bgw"` and `printLevel` is not set manually, it is changed to 2.
- **save**: Logical. If TRUE, saves pre-processing objects in the returned model object for later reuse. Only available for single-core, non-HB estimation.

FALSE by default.

- `scaleAfterConvergence`: Logical. Used to increase numerical precision of convergence. If TRUE, parameters are scaled to 1 after convergence, and the estimation is repeated from these new starting values. Results are reported scaled back, so it is a transparent process for the user. Default is FALSE.
- `scaleHessian`: Logical. If TRUE, parameters are scaled to 1 for Hessian estimation. Default is FALSE.
- `scaling`: Named vector. Names of elements should match those in `apollo_beta`. Optional scaling for parameters. If provided, for each parameter `i`, $(\text{apollo_beta}[i]/\text{scaling}[i])$ is optimised, but $\text{scaling}[i] * (\text{apollo_beta}[i]/\text{scaling}[i])$ is used during estimation. For example, if parameter `b3=10`, while `b1` and `b2` are close to 1, then setting `scaling = c(b3=10)` can help estimation, specially the calculation of the Hessian. Reports will still be based on the non-scaled parameters.
- `silent`: Logical. If TRUE, no information is printed to the console during estimation. Default is FALSE.
- `validateGrad`: Logical. If TRUE, the analytical gradient (if used) is compared to the numerical one. Default is FALSE.
- `writeIter`: Logical. Writes value of the parameters in each iteration to a csv file. Works only if `estimationRoutine` is "bfgs" or "bgw". Default is TRUE.

Details

This is the main function of the Apollo package. The estimation process begins by running a number of checks on the `apollo_probabilities` function provided by the user. If all checks are passed, estimation begins. There is no limit to estimation time other than reaching the maximum number of iterations. If Bayesian estimation is used, estimation will finish once the predefined number of iterations are completed. By default, this function writes the estimated parameter values in each iteration to a file in the working/output directory. Writing can be turned off by setting `estimate_settings$writeIter` to FALSE. By default, **final results are not written into a file nor printed to the console**, so users must make sure to call function `apollo_modelOutput` and/or `apollo_saveOutput` afterwards. Users are strongly encouraged to visit <https://www.ApolloChoiceModelling.com/> to download examples on how to use the Apollo package. The webpage also provides a detailed manual for the package, as well as a user-group to get further help.

Value

model object

apollo_estimateHB

Estimates model using Bayesian estimation

Description

Estimates a model using Bayesian estimation on the likelihood function defined by `apollo_probabilities`.

Usage

```
apollo_estimateHB(
  apollo_beta,
  apollo_fixed,
  apollo_probabilities,
  apollo_inputs,
  estimate_settings = NA
)
```

Arguments

- apollo_beta** Named numeric vector. Names and values for parameters.
- apollo_fixed** Character vector. Names (as defined in `apollo_beta`) of parameters whose value should not change during estimation.
- apollo_probabilities** Function. Returns probabilities of the model to be estimated. Must receive three arguments:
- **apollo_beta**: Named numeric vector. Names and values of model parameters.
 - **apollo_inputs**: List containing options of the model. See [apollo_validateInputs](#).
 - **functionality**: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL".
- apollo_inputs** List grouping most common inputs. Created by function [apollo_validateInputs](#).
- estimate_settings** List. Options controlling the estimation process, as used for in [apollo_estimate](#).

Details

This is a sub function of [apollo_estimate](#) which is called when using Bayesian estimation.

Value

model object

<code>apollo_expandLoop</code>	<i>Expands loops in a function or expression</i>
--------------------------------	--

Description

Expands loops replacing the index by its value. It also evaluates `paste` and `paste0`, and removes `get`.

Usage

```
apollo_expandLoop(f, apollo_inputs, validate = TRUE)
```

Arguments

f	function (usually <code>apollo_probabilities</code>) inside which the name of the components are inserted.
apollo_inputs	List grouping most common inputs. Created by function apollo_validateInputs .
validate	Logical. If TRUE, the expanded function is evaluated and compared against the original function before being returned. TRUE by default.

Details

For example, the expression `for(j in 1:3) V[[paste0('alt', j)]] = b1*get(paste0('x', j)) + b2*X[, j]`

would be expanded into:

`V[["alt1"]] = b1*x1 + b2*X[, 1] V[["alt2"]] = b1*x2 + b2*X[, 2] V[["alt3"]] = b1*x3 + b2*X[, 3]`

Value

A function or expression of the same type as input f, with eligible loops expanded.

apollo_firstRow	<i>Keeps only the first row for each individual</i>
-----------------	---

Description

Given a multi-row input, keeps only the first row for each individual.

Usage

```
apollo_firstRow(P, apollo_inputs)
```

Arguments

P	List of vectors, matrices or 3-dim arrays. Likelihood of the model components (or other object).
apollo_inputs	List grouping most common inputs. Created by function apollo_validateInputs .

Details

This is a function to keep only the first row of an object per individual. It can handle multiple types of components, including scalars, vectors and three-dimensional arrays (cubes). The argument database **MUST** contain a column called 'apollo_sequence', which is created by [apollo_validateData](#).

Value

If P is a list, then it returns a list where each element has only the first row of each individual. If P is a single element, then it returns a single element with only the first row of each individual. The size of the element is changed only in the first dimension. If input is a scalar, then it returns a vector with the element repeated as many times as individuals in database. If the element is a vector, its length will be changed to the number of individuals. If the element is a matrix, then its first dimension will be changed to the number of individuals, while keeping the size of the second dimension. If the element is a cube, then only the first dimension's length is changed, preserving the others. If functionality in the parent frame is "preprocess" or "report", P is returned without changes.

apollo_fitsTest	<i>Compares log-likelihood of model across categories</i>
-----------------	---

Description

Given the estimates of a model, it compares the log-likelihood at the observation level across categories of observations.

Usage

```
apollo_fitsTest(model, apollo_probabilities, apollo_inputs, fitsTest_settings)
```

Arguments

- | | |
|----------------------|---|
| model | Model object. Estimated model object as returned by function apollo_estimate . |
| apollo_probabilities | Function. Returns probabilities of the model to be estimated. Must receive three arguments: <ul style="list-style-type: none"> • <code>apollo_beta</code>: Named numeric vector. Names and values of model parameters. • <code>apollo_inputs</code>: List containing options of the model. See apollo_validateInputs. • <code>functionality</code>: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "hessian", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL". |
| apollo_inputs | List grouping most common inputs. Created by function apollo_validateInputs . |
| fitsTest_settings | List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional. <ul style="list-style-type: none"> • subsamples: Optional named list of boolean vectors. Each element of the list defines whether a given observation belongs to a given subsample (e.g. by sociodemographics). |

Details

Prints a table comparing the average log-likelihood at the observation level for each category.

Value

Invisibly returns a matrix with average log-likelihood at observation level per category (invisibly).

apollo_fmnl

Calculates Fractional Multinomial Logit probabilities

Description

Calculates the probabilities of a Fractional Multinomial Logit model and can also perform other operations based on the value of the functionality argument.

Usage

```
apollo_fmnl(fmnl_settings, functionality)
```

Arguments

- | | |
|---------------|---|
| fmnl_settings | <p>List of inputs of the FMNL model. It should contain the following.</p> <ul style="list-style-type: none"> • alternatives: Character vector. Names of alternatives, elements must match the names in list 'utilities'. • avail: Named list of numeric vectors or scalars. Availabilities of alternatives, one element per alternative. Names of elements must match those in alternatives. Values can be 0 or 1. These can be scalars or vectors (of length equal to rows in the database). A user can also specify avail=1 to indicate universal availability, or omit the setting completely. • choiceShares: Named list of numeric vectors. Share allocated to each alternative. One element per alternative, as long as the number of observations or a scalar. Names must match those in alternatives. If all choiceShares are NA, then they will be set to 1/nAlt for all alternatives. If some choiceShares are NA, then they will be set to 1/nAlt for those alternatives. • componentName: Character. Name given to model component. If not provided by the user, Apollo will set the name automatically according to the element in P to which the function output is directed. • rows: Boolean vector. Consideration of which rows to include. Length equal to the number of observations (nObs), with entries equal to TRUE for rows to include, and FALSE for rows to exclude. Default is "all", equivalent to rep(TRUE, nObs). • utilities: Named list of deterministic utilities. Utilities of the alternatives. Names of elements must match those in alternatives. |
| functionality | <p>Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call apollo_probabilities, though the user can also call apollo_probabilities manually with a given functionality for testing/debugging. Possible values are:</p> <ul style="list-style-type: none"> • "components": For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations. |

- "conditionals": For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws.
- "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "gradient": For model estimation, produces analytical gradients of the likelihood, where possible.
- "output": Prepares output for post-estimation reporting.
- "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws.
- "preprocess": Prepares likelihood functions for use in estimation.
- "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
- "report": Prepares output summarising model and choiceset structure.
- "shares_LL": Produces overall model likelihood with constants only.
- "utilities": Returns utilities at provided parameter values.
- "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "zero_LL": Produces overall model likelihood with all parameters at zero.

Value

The returned object depends on the value of argument `functionality` as follows.

- "components": Same as "estimate"
- "conditionals": Same as "estimate"
- "estimate": vector/matrix/array. Returns the probabilities for the chosen alternative for each observation.
- "gradient": List containing the likelihood and gradient of the model component.
- "output": Same as "estimate".
- "prediction": List of vectors/matrices/arrays. Returns a list with the probabilities for all alternatives, with an extra element for the probability of the chosen alternative.
- "preprocess": Returns a list with pre-processed inputs, based on `fmnl_settings`.
- "raw": Same as "prediction"
- "report": Overview of dependent variable
- "shares_LL": Currently not implemented. Returns NA.
- "utilities": Data frame containing individual IDs, observation numbers and utilities for each alternative, with unavailable alternatives set to NA.
- "validate": Same as "estimate", but it also runs a set of tests to validate the function inputs.
- "zero_LL": vector/matrix/array. Returns the likelihood when all parameters are zero.

apollo_fnl

Calculates Fractional Nested Logit probabilities

Description

Calculates the probabilities of a Fractional Nested Logit (FNL) model and can also perform other operations based on the value of the functionality argument.

Usage

```
apollo_fnl(fnl_settings, functionality)
```

Arguments

- | | |
|---------------|--|
| fnl_settings | <p>List of inputs of the FNL model. It should contain the following.</p> <ul style="list-style-type: none"> • alternatives: Character vector. Names of alternatives, elements must match the names in list 'utilities'. • avail: Named list of numeric vectors or scalars. Availabilities of alternatives, one element per alternative. Names of elements must match those in alternatives. Values can be 0 or 1. These can be scalars or vectors (of length equal to rows in the database). A user can also specify avail=1 to indicate universal availability, or omit the setting completely. • choiceShares: Named list of numeric vectors. Share allocated to each alternative. One element per alternative, as long as the number of observations or a scalar. Names must match those in alternatives. • componentName: Character. Name given to model component. If not provided by the user, Apollo will set the name automatically according to the element in P to which the function output is directed. • nlNests: List of numeric scalars or vectors. Lambda parameters for each nest. Elements must be named with the nest name. The lambda at the root is automatically fixed to 1 if not provided by the user. • nlStructure: Named list of character vectors. As many elements as nests, it must include the "root". Each element contains the names of the nests or alternatives that belong to it. Element names must match those in nlNests. • utilities: Named list of deterministic utilities. Utilities of the alternatives. Names of elements must match those in alternatives. • rows: Boolean vector. Consideration of which rows to include. Length equal to the number of observations (nObs), with entries equal to TRUE for rows to include, and FALSE for rows to exclude. Default is "all", equivalent to rep(TRUE, nObs). |
| functionality | <p>Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call apollo_probabilities, though the user can also call apollo_probabilities manually with a given functionality for testing/debugging. Possible values are:</p> |

- "components": For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations.
- "conditionals": For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws.
- "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "gradient": Not implemented.
- "hessian": Not implemented.
- "output": Same as "estimate".
- "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws.
- "preprocess": Prepares likelihood functions for use in estimation.
- "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
- "report": Prepares output summarising model and choiceset structure.
- "shares_LL": Produces overall model likelihood with constants only.
- "utilities": Returns utilities at provided parameter values.
- "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "zero_LL": Produces overall model likelihood with all parameters at zero.

Details

In this implementation of the Fractional Nested Logit model, each nest must have a lambda parameter associated to it. For the model to be consistent with utility maximisation, the estimated value of the Lambda parameter of all nests should be between 0 and 1. Lambda parameters are inversely proportional to the correlation between the error terms of alternatives in a nest. If lambda=1, then there is no relevant correlation between the unobserved utility of alternatives in that nest. The tree must contain an upper nest called "root". The lambda parameter of the root is automatically set to 1 if not specified in nlNests, but can be changed by the user if desired (though not advised).

Value

The returned object depends on the value of argument functionality as follows.

- "components": Same as "estimate"
- "conditionals": Same as "estimate"
- "estimate": vector/matrix/array. Returns the probabilities for the chosen alternative for each observation.
- "gradient": Not implemented.
- "output": Same as "estimate".

- "prediction": List of vectors/matrices/arrays with the probabilities for all alternatives. If choiceShares are provided, the list also contains an element "chosen" with the fractional nested logit likelihood.
- "preprocess": Returns a list with pre-processed inputs, based on fnl_settings.
- "raw": Same as "prediction".
- "report": List with tree structure and choice overview.
- "shares_LL": Not implemented. Returns NA.
- "utilities": Data frame containing individual IDs, observation numbers and utilities for each alternative, with unavailable alternatives set to NA.
- "validate": Same as "estimate", but it also runs a set of tests to validate the function inputs.
- "zero_LL": vector/matrix/array. Returns the zero-utility fractional nested logit likelihood for each observation.

apollo_initialise	<i>Prepares environment</i>
-------------------	-----------------------------

Description

Prepares environment (the global environment if called by the user) for model definition and estimation.

Usage

```
apollo_initialise()
```

Details

This function detaches variables and makes sure that output is directed to console. It does not delete variables from the working environment.

Value

Nothing.

 apollo_insertComponentName

Adds componentName2 to model calls

Description

Adds componentName2 to model calls

Usage

```
apollo_insertComponentName(e)
```

Arguments

e An expression or a function. It will usually be apollo_probabilities.

Value

The original argument e, modified to add a setting called componentName2 to recognised calls to apollo_<model> functions, such as apollo_mnl, apollo_nl, etc.

 apollo_insertFunc

Modifies function to make it compatible with analytic gradients

Description

Takes a likelihood function and inserts function () before key elements to allow for analytic gradient calculation

Usage

```
apollo_insertFunc(f, like = TRUE, randCoeff = FALSE, lcPars = FALSE)
```

Arguments

f Function. Expressions inside it will be turned into functions. Usually apollo_probabilities or apollo_randCoeff.

like Logical. Must be TRUE if f is apollo_probabilities. TRUE by default.

randCoeff Logical. Must be TRUE if f is apollo_randCoeff. FALSE by default.

lcPars Logical. Must be TRUE if f is apollo_lcPars. FALSE by default.

Details

It modifies the definition of supported models. It can only track a maximum of 3 levels of depth in definitions. For example: `V <- list() V[["A"]] <- b1*x1A + b2*x2A V[["B"]] <- b1*x1B + b2*x2B mnl_settings1 <- list(alternatives=c("A", "B"), V = V, choiceVar = Y, avail = 1, componentName="MNL1") P[["MNL1"]] <- apollo_mnl(mnl_settings1, functionality)` But it may not be able to deal with the following: `VA <- b1*x1A + b2*x2A V <- list() V[["A"]] <- VA V[["B"]] <- b1*x1B + b2*x2B mnl_settings1 <- list(alternatives=c("A", "B"), V = V, choiceVar = Y, avail = 1, componentName="MNL1") P[["MNL1"]] <- apollo_mnl(mnl_settings1, functionality)` But that might be enough given how `apollo_dVdB` works.

Value

Function `f` but with relevant expressions turned into function definitions.

<code>apollo_insertOLLlist</code>	<i>Replaces <code>tau=c(...)</code> by <code>tau=list(...)</code> in calls to <code>apollo_ol</code></i>
-----------------------------------	--

Description

Takes a function, looks for calls to `apollo_ol`, identifies the corresponding `ol_settings`, then goes inside the definition of `ol_settings` and replaces `tau=c(...)` with `tau=list(...)`.

Usage

```
apollo_insertOLLlist(f)
```

Arguments

`f` Function. Usually `apollo_probabilities`, `apollo_randCoeff`, or `apollo_lcPars`.

Details

This only goes one level deep in definitions. For example, it will work correctly in the following cases: `ol_settings = list(outcomeOrdered = y1, V = b1*x1, tau = c(tau11, tau12)) P[["OL1"]] = apollo_ol(ol_settings, functionality) P[["OL2"]] = apollo_ol(list(outcomeOrdered=y2, V=b2*x2, tau=c(tau21, tau22)), functionality)` But it will not work on the following cases: `Tau = c(tau1, tau2, tau3) ol_settings = list(outcomeOrdered = y2, V = b2*x2, tau = Tau) P[["OL1"]] = apollo_ol(ol_settings, functionality) P[["OL2"]] = apollo_ol(list(outcomeOrdered=y1, V=b1*x1, tau=Tau), functionality)`

This function is called by `apollo_modifyUserDefFunc` to allow for analytical gradients when using `apollo_ol`.

Value

Function `f` with `tau=c(...)` replaced by `tau=list(...)`.

apollo_insertRows	<i>Inserts rows</i>
-------------------	---------------------

Description

Given a numeric object (scalar, vector, matrix or 3-dim array) inserts rows in the specified places.

Usage

```
apollo_insertRows(v, r, val)
```

Arguments

v	Numeric scalar, vector, matrix or 3-dim array.
r	Boolean vector. TRUE for inserting a row from v, FALSE to insert a new row with value val.
val	Numeric scalar. Value that will fill new rows.

Details

In general, r should be longer than the number of rows in utilities, and $\text{sum}(r) = \text{nrow}(v)$. If not, then a new object with as many rows as r will be returned. Old rows will be taken from utilities from the top down.

Value

The same argument v but with rows added where $r == \text{FALSE}$.

apollo_insertRRMQuotes	<i>Introduces quotes into rrm_settings</i>
------------------------	--

Description

Takes a function, looks for the definition of relevant parts of rrm_settings, and introduces quotes on them. This is to facilitate their processing by apollo_rrm under functionality="preprocess".

Usage

```
apollo_insertRRMQuotes(f)
```

Arguments

f	Function. Usually apollo_probabilities.
---	---

Value

Function f with relevant expressions turned into character.

apollo_insertScaling *Scales variables inside a function*

Description

It changes the syntax of the function by replacing variable names for their scaled form, e.g. $x \rightarrow x * \text{apollo_inputs}\$ \text{apollo_scale}["x"]$. In assignments, it only scales the right side of the assignment.

Usage

```
apollo_insertScaling(e, sca)
```

Arguments

e	Function, expression, call or symbol to alter.
sca	Named numeric vector with the scales. The names in these vectors determine which variables should be scaled.

Value

A function, expression, call or symbol with the corresponding variables scaled.

apollo_keepRows *Keeps only some rows*

Description

Given a numeric object (scalar, vector, matrix or 3-dim array) keeps only the specified rows.

Usage

```
apollo_keepRows(v, r)
```

Arguments

v	Numeric scalar, vector, matrix or 3-dim array.
r	Boolean vector. As many elements as rows in utilities. TRUE for keeping the row. FALSE to drop it.

Value

The same argument utilities but with the rows where $r == \text{FALSE}$ removed.

apollo_lc

Calculates the likelihood of a latent class model

Description

Given within class probabilities, and class allocation probabilities, calculates the probabilities of an Exploded Logit model and can also perform other operations based on the value of the `functionality` argument.

Usage

```
apollo_lc(lc_settings, apollo_inputs, functionality)
```

Arguments

- | | |
|---------------|--|
| lc_settings | <p>List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional.</p> <ul style="list-style-type: none"> • classProb: List of probabilities. Allocation probability for each class. One element per class, in the same order as <code>inClassProb</code>. • componentName: Character. Name given to model component (optional). • inClassProb: List of probabilities. Conditional likelihood for each class. One element per class, in the same order as <code>classProb</code>. |
| apollo_inputs | <p>List grouping most common inputs. Created by function apollo_validateInputs.</p> |
| functionality | <p>Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call <code>apollo_probabilities</code>, though the user can also call <code>apollo_probabilities</code> manually with a given <code>functionality</code> for testing/debugging. Possible values are:</p> <ul style="list-style-type: none"> • "components": For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations. • "conditionals": For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws. • "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws. • "gradient": For model estimation, produces analytical gradients of the likelihood, where possible. • "hessian": For model estimation, produces analytical gradients and Hessians of the likelihood, where possible. • "output": Prepares output for post-estimation reporting. • "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws. • "preprocess": Prepares likelihood functions for use in estimation. |

- "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
- "report": Prepares output summarising model and choiceset structure.
- "shares_LL": Produces overall model likelihood with constants only.
- "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "utilities": Returns utilities at provided parameter values.
- "zero_LL": Produces overall model likelihood with all parameters at zero.

Value

The returned object depends on the value of argument functionality as follows.

- "components": Returns nothing.
- "conditionals": Same as "estimate"
- "estimate": vector/matrix/array. Returns the probabilities for the chosen alternative for each observation.
- "gradient": List containing the likelihood and gradient of the model component.
- "hessian": List containing the likelihood, gradient and Hessian of the latent class model component.
- "output": Same as "estimate".
- "prediction": List of vectors/matrices/arrays. Returns class-probability-weighted probabilities for each output element.
- "preprocess": Returns a list with pre-processed inputs, based on lc_settings.
- "raw": Same as "prediction".
- "report": Class allocation overview.
- "shares_LL": Same as "estimate"
- "utilities": List of vectors/matrices/arrays. Returns class-probability-weighted outputs from the class-specific utility calculations.
- "validate": Same as "estimate", but also runs a set of tests on the given arguments.
- "zero_LL": Same as "estimate"

apollo_lcConditionals *Calculates conditionals for latent class models.*

Description

Calculates posterior expected values (conditionals) of class allocation probabilities for each individual.

Usage

```
apollo_lcConditionals(model, apollo_probabilities, apollo_inputs)
```

Arguments

model Model object. Estimated model object as returned by function [apollo_estimate](#).

apollo_probabilities Function. Returns probabilities of the model to be estimated. Must receive three arguments:

- **apollo_beta**: Named numeric vector. Names and values of model parameters.
- **apollo_inputs**: List containing options of the model. See [apollo_validateInputs](#).
- **functionality**: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "hessian", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL".

apollo_inputs List grouping most common inputs. Created by function [apollo_validateInputs](#).

Details

This function can only be used with latent class models without continuous heterogeneity.

Value

A data frame with one row per individual, containing the individual ID and posterior class allocation probabilities.

apollo_lcEM	<i>Uses EM for latent class model</i>
-------------	---------------------------------------

Description

Uses the EM algorithm for estimating a latent class model.

Usage

```
apollo_lcEM(
  apollo_beta,
  apollo_fixed,
  apollo_probabilities,
  apollo_inputs,
  lcEM_settings = NA,
  estimate_settings = NA
)
```

Arguments

apollo_beta	Named numeric vector. Names and values for parameters.
apollo_fixed	Character vector. Names (as defined in apollo_beta) of parameters whose value should not change during estimation.
apollo_probabilities	Function. Returns probabilities of the model to be estimated. Must receive three arguments: • apollo_beta: Named numeric vector. Names and values of model parameters. • apollo_inputs: List containing options of the model. See apollo_validateInputs. • functionality: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "hessian", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL".
apollo_inputs	List grouping most common inputs. Created by function apollo_validateInputs .
lcEM_settings	List. Options controlling the EM process. • EMmaxIterations: Numeric. Maximum number of iterations of the EM algorithm before stopping. Default is 100. • postEM: Numeric scalar. Determines the tasks performed by this function after the EM algorithm has converged. Can take values 0, 1 or 2 only. If value is 0, only the EM algorithm will be performed, and the results will be a model object without a covariance matrix (i.e. estimates only). If value is 1, after the EM algorithm, the covariance matrix of the model will be calculated as well, and the result will be a model object with a covariance matrix. If value is 2, after the EM algorithm, the estimated parameter values will be used as starting value for a maximum likelihood estimation process, which will render a model object with a covariance matrix. Performing maximum likelihood estimation after the EM algorithm is useful, as there may be room for further improvement. Default is 2. • silent: Boolean. If TRUE, no information is printed to the console during estimation. Default is FALSE. • EMstoppingCriterion: Numeric. Convergence criterion. The EM process will stop when improvements in the log-likelihood fall below this value. Default is 10^{-5}.
estimate_settings	List. Options controlling the estimation process within each EM iteration. See apollo_estimate for details. The defaults used inside apollo_lcEM differ from apollo_estimate: estimationRoutine="bfgs", writeIter=FALSE, and hessianRoutine="numDeriv".

Details

This function uses the EM algorithm for estimating a Latent Class model. It is only suitable for models without continuous mixing. All parameters need to vary across classes and need to be included in the apollo_lcPars function which is used by apollo_lcEM.

Value

model object

apollo_lcEM_new	<i>Uses EM for latent class model</i>
-----------------	---------------------------------------

Description

Uses the EM algorithm for estimating a latent class model.

Usage

```
apollo_lcEM_new(
  apollo_beta,
  apollo_fixed,
  apollo_probabilities,
  apollo_inputs,
  lcEM_settings = NA,
  estimate_settings = NA
)
```

Arguments

- | | |
|----------------------|--|
| apollo_beta | Named numeric vector. Names and values for parameters. |
| apollo_fixed | Character vector. Names (as defined in apollo_beta) of parameters whose value should not change during estimation. |
| apollo_probabilities | Function. Returns probabilities of the model to be estimated. Must receive three arguments: <ul style="list-style-type: none"> • apollo_beta: Named numeric vector. Names and values of model parameters. • apollo_inputs: List containing options of the model. See apollo_validateInputs. • functionality: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL". |
| apollo_inputs | List grouping most common inputs. Created by function apollo_validateInputs . |
| lcEM_settings | List. Options controlling the EM process. <ul style="list-style-type: none"> • EMmaxIterations: Numeric. Maximum number of iterations of the EM algorithm before stopping. Default is 100. • postEM: Numeric scalar. Determines the tasks performed by this function after the EM algorithm has converged. Can take values 0, 1 or 2 only. If value is 0, only the EM algorithm will be performed, and the results will be a model object without a covariance matrix (i.e. estimates only). If value is 1, after the EM algorithm, the covariance matrix of the model will be calculated as well, and the result will be a model object with a covariance matrix. If value is 2, after the EM algorithm, the estimated parameter values will be used as starting value for a maximum likelihood estimation process, which will render a model object with a covariance matrix. Performing |

maximum likelihood estimation after the EM algorithm is useful, as there may be room for further improvement. Default is 2.

- **silent**: Boolean. If TRUE, no information is printed to the console during estimation. Default is FALSE.
- **stoppingCriterion**: Numeric. Convergence criterion. The EM process will stop when improvements in the log-likelihood fall below this value. Default is 10^{-5} .

estimate_settings

List. Options controlling the estimation process within each EM iteration. See [apollo_estimate](#) for details.

Details

This function uses the EM algorithm for estimating a Latent Class model. It is only suitable for models without continuous mixing. All parameters need to vary across classes and need to be included in the `apollo_lcPars` function which is used by `apollo_lcEM`.

Value

model object

apollo_lcUnconditionals

Returns unconditionals for a latent class model

Description

Returns values for random parameters and class allocation probabilities in a latent class model.

Usage

```
apollo_lcUnconditionals(model, apollo_probabilities, apollo_inputs)
```

Arguments

model Model object. Estimated model object as returned by function [apollo_estimate](#).

apollo_probabilities

Function. Returns probabilities of the model to be estimated. Must receive three arguments:

- **apollo_beta**: Named numeric vector. Names and values of model parameters.
- **apollo_inputs**: List containing options of the model. See [apollo_validateInputs](#).
- **functionality**: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "hessian", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL".

apollo_inputs List grouping most common inputs. Created by function [apollo_validateInputs](#).

Value

A list of scalar log-likelihood values. The first element corresponds to the whole model, followed by the model components where available. Returns NA if component-level output is not available.

apollo_llCalc	<i>Calculates log-likelihood of all model components</i>
---------------	--

Description

Calculates the log-likelihood of each model component as well as the whole model.

Usage

```
apollo_llCalc(apollo_beta, apollo_probabilities, apollo_inputs, silent = FALSE)
```

Arguments

apollo_beta	Named numeric vector. Names and values for parameters.
apollo_probabilities	Function. Returns probabilities of the model to be estimated. Must receive three arguments: • apollo_beta: Named numeric vector. Names and values of model parameters. • apollo_inputs: List containing options of the model. See apollo_validateInputs. • functionality: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL".
apollo_inputs	List grouping most common inputs. Created by function apollo_validateInputs .
silent	Boolean. If TRUE, no information is printed to the console by the function. Default is FALSE.

Details

This function calls `apollo_probabilities` with `functionality="output"`. It then reorders the list of likelihoods so that "model" goes first.

Value

A list of vectors. Each vector corresponds to the log-likelihood of the whole model (first element) or a model component.

apollo_loadModel	<i>Loads model from file</i>
------------------	------------------------------

Description

Loads a previously estimated model object from a file.

Usage

```
apollo_loadModel(modelName)
```

Arguments

modelName	Character. Name of the model to load.
-----------	---------------------------------------

Details

This function looks for a file named modelName_model.rds in the output directory, if available, and otherwise in the working directory. It loads the object contained in the file and returns it.

Value

A model object.

apollo_longToWide	<i>Converts data from long to wide format.</i>
-------------------	--

Description

Converts choice data from long to wide format, with one row per observation as opposed to one row per alternative/observation.

Usage

```
apollo_longToWide(longData, longToWide_settings)
```

Arguments

longData	data.frame. Data in long format.
longToWide_settings	List. Contains settings for this function. User input is required for all settings. - altColumn: Character. Name of column in long data that contains the names of the alternatives (either numeric or character). - altSpecAtts: Character vector. Names of columns in long data with attributes that vary across alternatives within an observation.

- `choiceColumn`: Character. Name of column in long data that contains the choice indicator, coded 1 for the chosen alternative and 0 otherwise.
- `idColumn`: Character. Name of column in long data that contains the ID of individuals.
- `obsColumn`: Character. Name of column in long data that contains the observation index.

Value

Returns a `data.frame` with the wide-format version of the data. An overview of the conversion and choice data is printed to screen. The returned choice column, `choice_new`, codes alternatives by their position in the order shown in the printed overview. #' @importFrom tibble is_tibble

apollo_lrTest

Likelihood ratio test

Description

Calculates the likelihood ratio test value between two models and reports the corresponding p-value.

Usage

```
apollo_lrTest(model1, model2)
```

Arguments

- | | |
|---------------------|--|
| <code>model1</code> | Either a character variable with the name of a previously estimated model, or an estimated model in memory, as returned by apollo_estimate . |
| <code>model2</code> | Either a character variable with the name of a previously estimated model, or an estimated model in memory, as returned by apollo_estimate . |

Details

The two models need to have been estimated on the same data, and one model needs to be nested within the other model.

Value

LR-test p-value (invisibly)

apollo_makeCluster	<i>Creates cluster for estimation.</i>
--------------------	--

Description

Splits data, creates cluster and loads different pieces of the database on each worker.

Usage

```
apollo_makeCluster(
  apollo_probabilities,
  apollo_inputs,
  silent = FALSE,
  cleanMemory = FALSE
)
```

Arguments

apollo_probabilities	Function. Returns probabilities of the model to be estimated. Must receive three arguments: • apollo_beta: Named numeric vector. Names and values of model parameters. • apollo_inputs: List containing options of the model. See apollo_validateInputs. • functionality: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL".
apollo_inputs	List grouping most common inputs. Created by function apollo_validateInputs .
silent	Boolean. If TRUE, no messages are printed to the terminal. FALSE by default. It overrides apollo_inputs\$silent.
cleanMemory	Boolean. If TRUE, it saves apollo_inputs to disc, and removes database and draws from the apollo_inputs in .GlobalEnv and the parent environment.

Details

Internal use only. Called by apollo_estimate before estimation. Using multiple cores greatly increases memory consumption.

Value

Cluster (i.e. an object of class cluster from package parallel)

apollo_makeDraws	<i>Creates draws for models with mixing</i>
------------------	---

Description

Creates a list containing all draws necessary to estimate a model with mixing.

Usage

```
apollo_makeDraws(apollo_inputs, silent = FALSE)
```

Arguments

apollo_inputs	List grouping most common inputs. Created by function apollo_validateInputs .
silent	Boolean. If true, then no information is printed to console or default output. FALSE by default.

Details

Internal use only. Called by `apollo_validateInputs`. This function creates a list whose elements are the sets of draws requested by the user for use in a model with mixing. If the model does not include mixing, then it is not necessary to run this function. The number of draws has a massive impact on memory usage and estimation time. Memory usage and number of computations scale geometrically as $N \times \text{interNDraws} \times \text{intraNDraws}$ (where N is the number of observations). Special care should be taken when using both inter and intra-individual draws, as memory usage can easily reach the GB order of magnitude. Also, keep in mind that using several threads (i.e. multicore) at least doubles the memory usage. This function returns a list, with each element representing a random component of the mixing model. The dimensions of the array depend on the type of draws used.

1. If only inter-individual draws are used, then draws are stored as 2-dimensional arrays (i.e. matrices).
2. If intra-individual draws are used, then draws are stored as 3-dimensional arrays.
3. The first dimension of the arrays (rows) correspond with the observations in the database.
4. The second dimension of the arrays (columns) correspond to the number of inter-individual draws.
5. The third dimension of the arrays correspond to the number of intra-individual draws.

Value

List. Each element is an array of draws representing a random component of the mixing model.

apollo_makeGrad	<i>Creates gradient function.</i>
-----------------	-----------------------------------

Description

Creates gradient function from the likelihood function `apollo_probabilities` provided by the user. Returns NULL if the creation of gradient function fails.

Usage

```
apollo_makeGrad(
  apollo_beta,
  apollo_fixed,
  apollo_logLike,
  validateGrad = FALSE
)
```

Arguments

<code>apollo_beta</code>	Named numeric vector. Names and values for parameters.
<code>apollo_fixed</code>	Character vector. Names (as defined in <code>apollo_beta</code>) of parameters whose value should not change during estimation.
<code>apollo_logLike</code>	Function to calculate the log-likelihood of the model, as created by apollo_makeLogLike . If provided, the value of the analytical gradient will be compared to the value of the numerical gradient as calculated using <code>apollo_logLike</code> and the <code>numDeriv</code> package. If the difference between the two is bigger than 1 that the analytical gradient is wrong and NULL will be returned.
<code>validateGrad</code>	Logical. If TRUE, it compares the value of the analytical gradient evaluated at <code>apollo_beta</code> against the numeric gradient (using <code>numDeriv</code>) at the same value. If the difference is bigger than 1 return NULL.

Details

Internal use only. Called by `apollo_estimate` before estimation. The returned function can be single-threaded or multi-threaded based on the model options.

Value

`apollo_gradient` function. It receives the following arguments

- `b` Numeric vector of `_variable_` parameters (i.e. must not include fixed parameters).
- `countIter` Not used. Included only to mirror inputs of `apollo_logLike`.
- `getNIter` Not used. Included only to mirror inputs of `apollo_logLike`.
- `sumLL` Not used. Included only to mirror inputs of `apollo_logLike`.
- `writeIter` Not used. Included only to mirror inputs of `apollo_logLike`.

If the creation of the gradient function fails, then it returns NULL.

apollo_makeHessian	<i>Creates hessian function.</i>
--------------------	----------------------------------

Description

Creates hessian function from the likelihood function `apollo_probabilities` provided by the user. Returns NULL if the creation of gradient function fails.

Usage

```
apollo_makeHessian(apollo_beta, apollo_fixed, apollo_logLike)
```

Arguments

<code>apollo_beta</code>	Named numeric vector. Names and values for (all) parameters.
<code>apollo_fixed</code>	Character vector. Names (as defined in <code>apollo_beta</code>) of parameters whose value should not change during estimation.
<code>apollo_logLike</code>	Function to calculate the log-likelihood of the model, as created by apollo_makeLogLike . If provided, the value of the analytical gradient will be compared to the value of the numerical gradient as calculated using <code>apollo_logLike</code> and the <code>numDeriv</code> package. If the difference between the two is bigger than 1 that the analytical gradient is wrong and NULL will be returned.

Details

Internal use only. Called by `apollo_estimate` before estimation. The returned function can be single-threaded or multi-threaded based on the model options.

Value

`apollo_hessian` function. It receives a single argument called `b`, which are the `_variable_` parameters (i.e. must not include fixed parameters).

apollo_makeLogLike	<i>Creates log-likelihood function.</i>
--------------------	---

Description

Creates log-likelihood function from the likelihood function `apollo_probabilities` provided by the user.

Usage

```
apollo_makeLogLike(
  apollo_beta,
  apollo_fixed,
  apollo_probabilities,
  apollo_inputs,
  apollo_estSet = list(estimationRoutine = "bgw"),
  cleanMemory = FALSE
)
```

Arguments

- | | |
|----------------------|---|
| apollo_beta | Named numeric vector. Names and values for parameters. |
| apollo_fixed | Character vector. Names (as defined in apollo_beta) of parameters whose value should not change during estimation. |
| apollo_probabilities | Function. Returns probabilities of the model to be estimated. Must receive three arguments: <ul style="list-style-type: none"> • apollo_beta: Named numeric vector. Names and values of model parameters. • apollo_inputs: List containing options of the model. See apollo_validateInputs. • functionality: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL". |
| apollo_inputs | List grouping most common inputs. Created by function apollo_validateInputs . |
| apollo_estSet | List of estimation options. It must contain at least one element called estimationRoutine defining the estimation algorithm. See apollo_estimate . |
| cleanMemory | Logical. If TRUE, then apollo_inputs\$draws and apollo_inputs\$database are erased throughout the calling stack. Used to reduce memory usage in case of multithreading and a large database or number o draws. |

Details

Internal use only. Called by apollo_estimate before estimation. The returned function can be single-threaded or multi-threaded based on the model options.

Value

apollo_logLike function.

apollo_mdcev

Calculates MDCEV likelihoods

Description

Calculates the likelihoods of a Multiple Discrete Continuous Extreme Value (MDCEV) model and can also perform other operations based on the value of the functionality argument.

Usage

```
apollo_mdcev(mdcev_settings, functionality)
```

Arguments

- mdcev_settings List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional.
- alpha: Named list. Alpha parameters for each alternative, including for any outside good. As many elements as alternatives.
 - alternatives: Character vector. Names of alternatives, elements must match the names in list utilities.
 - avail: Named list of numeric vectors or scalars. Availabilities of alternatives, one element per alternative. Names of elements must match those in alternatives. Values can be 0 or 1. These can be scalars or vectors (of length equal to rows in the database). A user can also specify avail=1 to indicate universal availability.
 - budget: Numeric vector. Budget for each observation.
 - componentName: Character. Name given to model component. If not provided by the user, Apollo will set the name automatically according to the element in P to which the function output is directed.
 - continuousChoice: Named list of numeric vectors. Amount of consumption of each alternative. One element per alternative, as long as the number of observations or a scalar. Names must match those in alternatives.
 - cost: Named list of numeric vectors. Price of each alternative. One element per alternative, each one as long as the number of observations or a scalar. Names must match those in alternatives.
 - gamma: Named list. Gamma parameters for each alternative, excluding any outside good. As many elements as inside good alternatives.
 - nRep: Numeric scalar. Number of simulations of the whole dataset used for forecasting. The forecast is the average of these simulations. Default is 100.
 - outside: Character. Optional name of the outside good.
 - rawPrediction: Logical scalar. TRUE for prediction to be returned at the draw level (a 3-dim array). FALSE for prediction to be returned averaged across draws. Default is FALSE.

- **rows**: Boolean vector. Consideration of which rows to include. Length equal to the number of observations (nObs), with entries equal to TRUE for rows to include, and FALSE for rows to exclude. Default is "all", equivalent to rep(TRUE, nObs).
- **sigma**: Numeric scalar. Scale parameter of the model extreme value type I error.
- **utilities**: Named list. Utilities of the alternatives. Names of elements must match those in argument alternatives.

functionality Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call `apollo_probabilities`, though the user can also call `apollo_probabilities` manually with a given functionality for testing/debugging. Possible values are:

- **"components"**: For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations.
- **"conditionals"**: For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws.
- **"estimate"**: For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- **"gradient"**: For model estimation, produces analytical gradients of the likelihood. Not implemented yet.
- **"output"**: Prepares output for post-estimation reporting.
- **"prediction"**: For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws.
- **"preprocess"**: Prepares likelihood functions for use in estimation.
- **"raw"**: For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
- **"report"**: Prepares output summarising model and choiceset structure.
- **"shares_LL"**: Produces overall model likelihood with constants only.
- **"validate"**: Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- **"zero_LL"**: Produces overall model likelihood with all parameters at zero.

Value

The returned object depends on the value of argument `functionality` as follows.

- **"components"**: Same as "estimate"
- **"conditionals"**: Same as "estimate"
- **"estimate"**: vector/matrix/array. Returns the probabilities for the observed consumption for each observation.
- **"gradient"**: Not implemented

- "output": Same as "estimate".
- "prediction": If rawPrediction=FALSE, returns a matrix with one row per observation and columns giving means and standard deviations of continuous consumption, discrete participation and expenditure. If rawPrediction=TRUE, returns a three-dimensional array of simulated continuous consumption by observation, alternative and repetition.
- "preprocess": Returns a list with pre-processed inputs, based on mdcev_settings.
- "raw": Same as "prediction"
- "report": Dependent variable overview.
- "shares_LL": Not implemented. Returns a vector of NA with as many elements as observations.
- "validate": Same as "estimate", but it also runs a set of tests to validate the function inputs.
- "zero_LL": Not implemented. Returns a vector of NA with as many elements as observations.

apollo_mdcev2

Calculates MDCEV likelihoods

Description

Calculates the likelihoods of a Multiple Discrete Continuous Extreme Value (MDCEV) model and can also perform other operations based on the value of the functionality argument.

Usage

```
apollo_mdcev2(mdcev_settings, functionality)
```

Arguments

- mdcev_settings List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional.
- alpha: Named list. Alpha parameters for each alternative, including for any outside good. As many elements as alternatives.
 - alternatives: Character vector. Names of alternatives, elements must match the names in list 'utilities'.
 - avail: Named list of numeric vectors or scalars. Availabilities of alternatives, one element per alternative. Names of elements must match those in alternatives. Values can be 0 or 1. These can be scalars or vectors (of length equal to rows in the database). A user can also specify avail=1 to indicate universal availability, or omit the setting completely.
 - budget: Numeric vector. Budget for each observation.
 - componentName: Character. Name given to model component. If not provided by the user, Apollo will set the name automatically according to the element in P to which the function output is directed.
 - continuousChoice: Named list of numeric vectors. Amount of consumption of each alternative. One element per alternative, as long as the number of observations or a scalar. Names must match those in alternatives.

- **cost**: Named list of numeric vectors. Price of each alternative. One element per alternative, each one as long as the number of observations or a scalar. Names must match those in **alternatives**.
- **fastPred**: Boolean scalar. TRUE to mix parameter draws with repetition draws. This is formally incorrect, but a good approximation to the true prediction, and much faster. FALSE by default.
- **gamma**: Named list. Gamma parameters for each alternative, excluding any outside good. As many elements as inside good alternatives.
- **nRep**: Numeric scalar. Number of simulations of the whole dataset used for forecasting. The forecast is the average of these simulations. Default is 100.
- **outside**: Character. Optional name of the outside good.
- **rawPrediction**: Logical scalar. TRUE for prediction to be returned at the draw level (a 3-dim array). FALSE for prediction to be returned averaged across draws. Default is FALSE.
- **rows**: Boolean vector. Consideration of which rows to include. Length equal to the number of observations (**nObs**), with entries equal to TRUE for rows to include, and FALSE for rows to exclude. Default is "all", equivalent to `rep(TRUE, nObs)`.
- **sigma**: Numeric scalar. Scale parameter of the model extreme value type I error.
- **utilities**: Named list. Utilities of the alternatives. Names of elements must match those in argument 'alternatives'.

functionality Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call `apollo_probabilities`, though the user can also call `apollo_probabilities` manually with a given **functionality** for testing/debugging. Possible values are:

- **"components"**: For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations.
- **"conditionals"**: For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws.
- **"estimate"**: For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- **"gradient"**: For model estimation, produces analytical gradients of the likelihood, where possible.
- **"output"**: Prepares output for post-estimation reporting.
- **"prediction"**: For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws.
- **"preprocess"**: Prepares likelihood functions for use in estimation.
- **"raw"**: For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
- **"report"**: Prepares output summarising model and choicest structure.

- "shares_LL": Produces overall model likelihood with constants only.
- "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "zero_LL": Produces overall model likelihood with all parameters at zero.

Value

The returned object depends on the value of argument `functionality` as follows.

- "components": Same as "estimate"
- "conditionals": Same as "estimate"
- "estimate": vector/matrix/array. Returns the probabilities for the observed consumption for each observation.
- "gradient": Not implemented
- "output": Same as "estimate" but also writes summary of input data to internal Apollo log.
- "prediction": A matrix with one row per observation, and columns indicating means and s.d. of continuous and discrete predicted consumptions.
- "preprocess": Returns a list with pre-processed inputs, based on `mdcnev_settings`.
- "raw": Same as "estimate"
- "report": Dependent variable overview.
- "shares_LL": Not implemented. Returns a vector of NA with as many elements as observations.
- "validate": Same as "estimate", but it also runs a set of tests to validate the function inputs.
- "zero_LL": Not implemented. Returns a vector of NA with as many elements as observations.

apollo_mdcnev

Calculates MDCNEV likelihoods

Description

Calculates the likelihoods of a Multiple Discrete Continuous Nested Extreme Value (MDCNEV) model with an outside good and can also perform other operations based on the value of the `functionality` argument.

Usage

```
apollo_mdcnev(mdcnev_settings, functionality)
```

Arguments**mdcnev_settings**

List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional.

- **alpha:** Named list. Alpha parameters for each alternative, including for the outside good. As many elements as alternatives.
- **alternatives:** Character vector. Names of alternatives, elements must match the names in list 'utilities'.
- **avail:** Named list of numeric vectors or scalars. Availabilities of alternatives, one element per alternative. Names of elements must match those in alternatives. Values can be 0 or 1. These can be scalars or vectors (of length equal to rows in the database). A user can also specify `avail=1` to indicate universal availability, or omit the setting completely.
- **budget:** Numeric vector. Budget for each observation.
- **componentName:** Character. Name given to model component. If not provided by the user, Apollo will set the name automatically according to the element in P to which the function output is directed.
- **continuousChoice:** Named list of numeric vectors. Amount of consumption of each alternative. One element per alternative, as long as the number of observations or a scalar. Names must match those in alternatives.
- **cost:** Named list of numeric vectors. Price of each alternative. One element per alternative, each one as long as the number of observations or a scalar. Names must match those in alternatives.
- **gamma:** Named list. Gamma parameters for each alternative, including for the outside good. As many elements as alternatives.
- **mdcnevNests:** Named list. Lambda parameters for each nest. Elements must be named with the nest name. The lambda at the root is fixed to 1, and therefore must not be defined. The value of the estimated mdcnevNests parameters should be between 0 and 1 to ensure consistency with random utility maximization.
- **mdcnevStructure:** Numeric matrix. One row per nest and one column per alternative. Each element of the matrix is 1 if an alternative belongs to the corresponding nest.
- **outside:** Character. Alternative name for the outside good. Default is "outside".
- **rows:** Boolean vector. Consideration of which rows to include. Length equal to the number of observations (nObs), with entries equal to TRUE for rows to include, and FALSE for rows to exclude. Default is "all", equivalent to `rep(TRUE, nObs)`.
- **utilities:** Named list. Utilities of the alternatives. Names of elements must match those in argument 'alternatives'.

functionality

Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call `apollo_probabilities`, though the user can also call `apollo_probabilities` manually with a given functionality for testing/debugging. Possible values are:

- "components": For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations.
- "conditionals": For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws.
- "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "gradient": Not implemented for MDCNEV.
- "output": Prepares output for post-estimation reporting.
- "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws.
- "preprocess": Prepares likelihood functions for use in estimation.
- "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
- "report": Prepares output summarising model and choiceset structure.
- "shares_LL": Produces overall model likelihood with constants only.
- "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "zero_LL": Produces overall model likelihood with all parameters at zero.

Value

The returned object depends on the value of argument `functionality` as follows.

- "components": Same as "estimate"
- "conditionals": Same as "estimate"
- "estimate": vector/matrix/array. Returns the probabilities for the observed consumption for each observation.
- "gradient": Not implemented
- "output": Same as "estimate".
- "prediction": A matrix with one row per observation and columns giving means and standard deviations of predicted continuous consumption, discrete participation and expenditure.
- "preprocess": Returns a list with pre-processed inputs, based on `mdcnev_settings`.
- "raw": Same as "estimate"
- "report": List containing captured diagnostic output for the dependent variable overview and nest structure.
- "shares_LL": Not implemented. Returns a vector of NA with as many elements as observations.
- "validate": Same as "estimate", but it also runs a set of tests to validate the function inputs.
- "zero_LL": Not implemented. Returns a vector of NA with as many elements as observations.

 apollo_mixConditionals

Calculates conditionals for continuous mixture models

Description

Calculates posterior expected values (conditionals) of continuously distributed random coefficients, as well as their standard deviations.

Usage

```
apollo_mixConditionals(model, apollo_probabilities, apollo_inputs)
```

Arguments

- | | |
|----------------------|--|
| model | Model object. Estimated model object as returned by function apollo_estimate . |
| apollo_probabilities | Function. Returns probabilities of the model to be estimated. Must receive three arguments: <ul style="list-style-type: none"> • apollo_beta: Named numeric vector. Names and values of model parameters. • apollo_inputs: List containing options of the model. See apollo_validateInputs. • functionality: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "hessian", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL". |
| apollo_inputs | List grouping most common inputs. Created by function apollo_validateInputs . |

Details

This functions is only meant for use with continuous distributions.

Value

A list of data frames, one per random component. Each data frame has one row per individual and columns for the individual ID, posterior mean and posterior standard deviation. If there is only one random component, the corresponding data frame is returned directly.

apollo_mixEM

Uses EM for models with continuous random coefficients

Description

Uses the EM algorithm for estimating a model with continuous random coefficients.

Usage

```
apollo_mixEM(
  apollo_beta,
  apollo_fixed,
  apollo_probabilities,
  apollo_inputs,
  mixEM_settings = NA,
  estimate_settings = NA
)
```

Arguments

- | | |
|----------------------|--|
| apollo_beta | Named numeric vector. Names and values for parameters. These need to be provided in the following order. With K random parameters, K means for the underlying Normals, followed by the elements of the lower triangle of the Cholesky matrix, by row. |
| apollo_fixed | Character vector. Names (as defined in apollo_beta) of parameters whose value should not change during estimation. |
| apollo_probabilities | Function. Returns probabilities of the model to be estimated. Must receive three arguments: <ul style="list-style-type: none"> • apollo_beta: Named numeric vector. Names and values of model parameters. • apollo_inputs: List containing options of the model. See apollo_validateInputs. • functionality: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "hessian", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL". |
| apollo_inputs | List grouping most common inputs. Created by function apollo_validateInputs . |
| mixEM_settings | List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional. <ul style="list-style-type: none"> • EMmaxIterations: Numeric. Maximum number of iterations of the EM algorithm before stopping. Default is 100. • postEM: Numeric scalar. Determines the tasks performed by this function after the EM algorithm has converged. Can take values 0, 1 or 2 only. If value is 0, only the EM algorithm will be performed, and the results will be a model object without a covariance matrix (i.e. estimates only). If value is 1, after the EM algorithm, the covariance matrix of the model will be |

calculated as well, and the result will be a model object with a covariance matrix. If value is 2, after the EM algorithm, the estimated parameter values will be used as starting value for a maximum likelihood estimation process, which will render a model object with a covariance matrix. Performing maximum likelihood estimation after the EM algorithm is useful, as there may be room for further improvement. Default is 2.

- **silent:** Boolean. If TRUE, no information is printed to the console during estimation. Default is FALSE.
- **EMstoppingCriterion:** Numeric. Convergence criterion. The EM process will stop when improvements in the log-likelihood fall below this value. Default is 10^{-5} .
- **transforms:** List. Optional argument, with one entry per random parameter, showing the inverse transform to return from the transformed random coefficient to the underlying Normal. If omitted, all random coefficients are assumed to use untransformed Normal distributions.

estimate_settings

List. Options controlling the estimation process within each EM iteration. See [apollo_estimate](#) for details.

Details

This function uses the EM algorithm for estimating a model with continuous random coefficients. It is only suitable for models where all parameters are random, with a full covariance matrix. All random parameters need to be based on underlying Normals with a full covariance matrix, but any transform thereof can be used.

Value

Model object containing EM estimates, and, depending on `mixEM_settings$postEM`, possibly a covariance matrix or estimates refined by a subsequent maximum likelihood estimation.

apollo_mixUnconditionals

Returns draws for continuously distributed random parameters in mixture model

Description

Returns draws (unconditionals) for random parameters in model, including interactions with deterministic covariates.

Usage

```
apollo_mixUnconditionals(
  model,
  apollo_probabilities,
  apollo_inputs,
  obsLevel = NULL
)
```

Arguments

model	Model object. Estimated model object as returned by function apollo_estimate .
apollo_probabilities	Function. Returns probabilities of the model to be estimated. Must receive three arguments: • apollo_beta: Named numeric vector. Names and values of model parameters. • apollo_inputs: List containing options of the model. See apollo_validateInputs. • functionality: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL".
apollo_inputs	List grouping most common inputs. Created by function apollo_validateInputs .
obsLevel	Logical. If TRUE, unconditionals are returned at the observation level rather than person level. This setting only applies to continuous mixture models and is set to TRUE by default only in the presence of intra-individual draws. Otherwise, the default is FALSE.

Details

This functions is only meant for use with continuous distributions

Value

List of object, one per random coefficient. With inter-individual draws only, this will be a matrix, with one row per individual, and one column per draw. With intra-individual draws, this will be a three-dimensional array, with one row per observation, inter-individual draws in the second dimension, and intra-individual draws in the third dimension.

apollo_mlhs	<i>Generate random draws using MLHS algorithm</i>
-------------	---

Description

Generate random draws using the Modified Latin Hypercube Sampling algorithm.

Usage

```
apollo_mlhs(N, d, i)
```

Arguments

N	Numeric. The number of draws to generate in each dimension
d	Numeric. The number of dimensions to generate draws in
i	Numeric. The number of individuals to generate draws for

Details

Internal use only. Algorithm described in Hess, S., Train, K., and Polak, J. (2006) Transportation Research Part B, 40, 147 - 163.

Value

A (N*i) x d matrix with random draws

apollo_mnl	<i>Calculates Multinomial Logit probabilities</i>
------------	---

Description

Calculates the probabilities of a Multinomial Logit model and can also perform other operations based on the value of the functionality argument.

Calculates the probabilities of a Multinomial Logit model and can also perform other operations based on the value of the functionality argument.

Usage

```
apollo_mnl(mnl_settings, functionality)
```

```
apollo_mnl(mnl_settings, functionality)
```

Arguments

- | | |
|--------------|--|
| mnl_settings | <p>List of inputs of the MNL model. It should contain the following.</p> <ul style="list-style-type: none"> • alternatives: Named numeric vector. Names of alternatives and their corresponding value in choiceVar. • avail: Named list of numeric vectors or scalars. Availabilities of alternatives, one element per alternative. Names of elements must match those in alternatives. Values can be 0 or 1. These can be scalars or vectors (of length equal to rows in the database). A user can also specify avail=1 to indicate universal availability, or omit the setting completely. • choiceVar: Numeric vector. Contains choices for all observations. It will usually be a column from the database. Values are defined in alternatives. • componentName: Character. Name given to model component. If not provided by the user, Apollo will set the name automatically according to the element in P to which the function output is directed. • rows: Boolean vector. Consideration of which rows to include. Length equal to the number of observations (nObs), with entries equal to TRUE for rows to include, and FALSE for rows to exclude. Default is "all", equivalent to rep(TRUE, nObs). Set to "all" by default if omitted. • utilities: Named list of deterministic utilities. Utilities of the alternatives. Names of elements must match those in alternatives. |
|--------------|--|

- functionality Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call `apollo_probabilities`, though the user can also call `apollo_probabilities` manually with a given functionality for testing/debugging. Possible values are:
- "components": For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations.
 - "conditionals": For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws.
 - "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
 - "gradient": For model estimation, produces analytical gradients of the likelihood, where possible.
 - "hessian": For model estimation, produces analytical gradients and Hessians of the likelihood, where possible.
 - "output": Prepares output for post-estimation reporting.
 - "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws.
 - "preprocess": Prepares likelihood functions for use in estimation.
 - "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
 - "report": Prepares output summarising model and choiceset structure.
 - "shares_LL": Produces overall model likelihood with constants only.
 - "utilities": Returns utilities at provided parameter values.
 - "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
 - "zero_LL": Produces overall model likelihood with all parameters at zero.

Value

The returned object depends on the value of argument `functionality` as follows.

- "components": Same as "estimate"
- "conditionals": Same as "estimate"
- "estimate": vector/matrix/array. Returns the probabilities for the chosen alternative for each observation.
- "gradient": List containing the likelihood and gradient of the model component.
- "hessian": List containing the likelihood, gradient and Hessian of the model component.
- "output": Same as "estimate".
- "prediction": List of vectors/matrices/arrays. Returns a list with the probabilities for all alternatives, with an extra element for the probability of the chosen alternative.
- "preprocess": Returns a list with pre-processed inputs, based on `mnl_settings`.

- "raw": Same as "prediction"
- "report": Choice overview
- "shares_LL": vector/matrix/array. Returns the probability of the chosen alternative when only constants are estimated.
- "utilities": Data frame containing individual IDs, observation numbers and utilities for each alternative, with unavailable alternatives set to NA.
- "validate": Same as "estimate", but it also runs a set of tests to validate the function inputs.
- "zero_LL": vector/matrix/array. Returns the probability of the chosen alternative when all parameters are zero.

The returned object depends on the value of argument `functionality` as follows.

- "components": Same as "estimate"
- "conditionals": Same as "estimate"
- "estimate": vector/matrix/array. Returns the probabilities for the chosen alternative for each observation.
- "gradient": List containing the likelihood and gradient of the model component.
- "hessian": List containing the likelihood, gradient and Hessian of the model component.
- "output": Same as "estimate".
- "prediction": List of vectors/matrices/arrays. Returns a list with the probabilities for all alternatives, with an extra element for the probability of the chosen alternative.
- "preprocess": Returns a list with pre-processed inputs, based on `mnl_settings`.
- "raw": Same as "prediction"
- "report": Choice overview
- "shares_LL": vector/matrix/array. Returns the probability of the chosen alternative when only constants are estimated.
- "utilities": Data frame containing individual IDs, observation numbers and utilities for each alternative, with unavailable alternatives set to NA.
- "validate": Same as "estimate", but it also runs a set of tests to validate the function inputs.
- "zero_LL": vector/matrix/array. Returns the probability of the chosen alternative when all parameters are zero.

apollo_modeChoiceData *Simulated dataset of mode choice.*

Description

A simulated dataset containing 8,000 mode choices among four alternatives.

Usage

```
apollo_modeChoiceData
```

Format

A data.frame with 8,000 rows and 26 variables:

ID Numeric. Identification number of the individual.

RP Numeric. 1 if the row corresponds to a revealed preference (RP) observation. 0 otherwise.

RP_journey Numeric. Consecutive ID of RP observations. 0 if SP observation.

SP Numeric. 1 if the row corresponds to a stated preference (SP) observation. 0 otherwise.

SP_task Numeric. Consecutive ID of SP choice tasks. 0 if RP observation.

access_air Numeric. Access time (in minutes) of mode air.

access_bus Numeric. Access time (in minutes) of mode bus.

access_rail Numeric. Access time (in minutes) of mode rail.

av_air Numeric. 1 if the mode air (plane) is available. 0 otherwise.

av_bus Numeric. 1 if the mode bus is available. 0 otherwise.

av_car Numeric. 1 if the mode car is available. 0 otherwise.

av_rail Numeric. 1 if the mode rail (train) is available. 0 otherwise.

business Numeric. Purpose of the trip. 1 for business, 0 for other.

choice Numeric. Choice indicator, 1=car, 2=bus, 3=air, 4=rail.

cost_air Numeric. Cost (in GBP) of mode air.

cost_bus Numeric. Cost (in GBP) of mode bus.

cost_car Numeric. Cost (in GBP) of mode car.

cost_rail Numeric. Cost (in GBP) of mode rail.

female Numeric. Sex of individual. 1 for female, 0 for male.

income Numeric. Income (in GBP per annum) of the individual.

service_air Numeric. Additional services for the air alternative. 1 for no-frills, 2 for wifi, 3 for food. This is not used in the RP data, where it is set to 0.

service_rail Numeric. Additional services for the rail alternative. 1 for no-frills, 2 for wifi, 3 for food. This is not used in the RP data, where it is set to 0.

time_air Numeric. Travel time (in minutes) of mode air.

time_bus Numeric. Travel time (in minutes) of mode bus.

time_car Numeric. Travel time (in minutes) of mode car.

time_rail Numeric. Travel time (in minutes) of mode rail.

Details

This dataset is to be used for discrete choice modelling. Data comes from 500 individuals, each with two revealed preference (RP) observations and 14 stated preference (SP) observations. There are 8,000 choices in total. Data is simulated. Each observation contains attributes for the alternatives, availability of alternatives, and characteristics of the individuals.

Source

<https://www.ApolloChoiceModelling.com/>

apollo_modelOutput	<i>Prints estimation results to console</i>
--------------------	---

Description

Prints estimation results to console. Amount of information presented can be adjusted through arguments.

Usage

```
apollo_modelOutput(model, modelOutput_settings = NA)
```

Arguments

- | | |
|----------------------|--|
| model | Model object. Estimated model object as returned by function apollo_estimate . |
| modelOutput_settings | <p>List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional.</p> <ul style="list-style-type: none"> • printBHHH: Logical. TRUE for printing BHHH standard errors. FALSE by default. • printChange: Logical. TRUE for printing difference between starting values and estimates. FALSE by default. • printClassical: Logical. TRUE for printing classical standard errors. TRUE by default. • printCorr: Boolean. TRUE for printing parameters correlation matrix. If printClassical=TRUE, both classical and robust matrices are printed. For Bayesian estimation, this setting is used for the correlation of random parameters. FALSE by default. • printCovar: Boolean. TRUE for printing parameters covariance matrix. If printClassical=TRUE, both classical and robust matrices are printed. For Bayesian estimation, this setting is used for the covariance of random parameters. FALSE by default.#' • printDataReport: Logical. TRUE for printing summary of choices in database and other diagnostics. FALSE by default. • printFixed: Logical. TRUE for printing fixed parameters among estimated parameter. TRUE by default. • printFunctions: Logical. TRUE for printing apollo_control, apollo_randCoeff (when available), apollo_lcPars (when available) and apollo_probabilities. FALSE by default. • printHBconvergence: Boolean. TRUE for printing Geweke convergence tests. FALSE by default. • printHBiterations: Boolean. TRUE for printing an iterations report for HB estimation. FALSE by default. • printModelStructure: Logical. TRUE for printing model structure. TRUE by default. |

- `printOutliers`: Logical or Scalar. TRUE for printing 20 individuals with worst average fit across observations. FALSE by default. If Scalar is given, this replaces the default of 20.
- `printPVal`: Logical or Scalar. TRUE or 1 for printing p-values for one-sided test, 2 for printing p-values for two-sided test, FALSE for not printing p-values. FALSE by default.
- `printRobust`: Logical. TRUE for printing robust standard errors. TRUE by default.
- `printT1`: Logical. If TRUE, t-test for $H_0: \text{apollo_beta}=1$ are printed. FALSE by default.

Details

Prints to screen the output of a model previously estimated by `apollo_estimate()`

Value

Invisibly returns a matrix of coefficients, standard errors and t-tests for classical estimation. For HB models, invisibly returns a list of posterior summaries and random-parameter covariance/correlation outputs.

`apollo_modifyUserDefFunc`

Checks and modifies Apollo user-defined functions

Description

Checks and enhances user defined functions `apollo_probabilities`, `apollo_randCoeff` and `apollo_lcPars`.

Usage

```
apollo_modifyUserDefFunc(
  apollo_beta,
  apollo_fixed,
  apollo_probabilities,
  apollo_inputs,
  validate = TRUE,
  noModification = FALSE
)
```

Arguments

<code>apollo_beta</code>	Named numeric vector. Names and values for parameters.
<code>apollo_fixed</code>	Character vector. Names of parameters inside <code>apollo_beta</code> whose values should be kept constant throughout estimation.

apollo_probabilities

Function. Returns probabilities of the model to be estimated. Must receive three arguments:

- **apollo_beta**: Named numeric vector. Names and values of model parameters.
- **apollo_inputs**: List containing options of the model. See [apollo_validateInputs](#).
- **functionality**: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL".

apollo_inputs List grouping most common inputs. Created by function [apollo_validateInputs](#).

validate Logical. If TRUE, the original and modified `apollo_probabilities` functions are estimated. If their results do not match, then the original functions are returned, and success is set to FALSE inside the returned list.

noModification Logical. If TRUE, loop expansion etc are skipped.

Details

Internal use only. Called by `apollo_estimate` before estimation. Checks include: no re-definition of variables, no (direct) calls to database, calling of `apollo_weighting` if weights are defined.

Value

List with four elements: `apollo_probabilities`, `apollo_randCoeff`, `apollo_lcPars` and a dummy called `success` (TRUE if modification was successful, FALSE if not. FALSE will be only be returns if the modifications are validated).

<code>apollo_nl</code>	<i>Calculates Nested Logit probabilities</i>
------------------------	--

Description

Calculates the probabilities of a Nested Logit model and can also perform other operations based on the value of the `functionality` argument.

Usage

```
apollo_nl(nl_settings, functionality)
```

Arguments

nl_settings List of inputs of the NL model. It should contain the following.

- **alternatives**: Named numeric vector. Names of alternatives and their corresponding value in `choiceVar`.

- **avail**: Named list of numeric vectors or scalars. Availabilities of alternatives, one element per alternative. Names of elements must match those in alternatives. Values can be 0 or 1. These can be scalars or vectors (of length equal to rows in the database). A user can also specify `avail=1` to indicate universal availability, or omit the setting completely.
- **choiceVar**: Numeric vector. Contains choices for all observations. It will usually be a column from the database. Values are defined in alternatives.
- **componentName**: Character. Name given to model component. If not provided by the user, Apollo will set the name automatically according to the element in `P` to which the function output is directed.
- **nlNests**: List of numeric scalars or vectors. Lambda parameters for each nest. Elements must be named with the nest name. The lambda at the root is automatically fixed to 1 if not provided by the user.
- **nlStructure**: Named list of character vectors. As many elements as nests, it must include the "root". Each element contains the names of the nests or alternatives that belong to it. Element names must match those in `nlNests`.
- **utilities**: Named list of deterministic utilities. Utilities of the alternatives. Names of elements must match those in alternatives.
- **rows**: Boolean vector. Consideration of which rows to include. Length equal to the number of observations (`nObs`), with entries equal to `TRUE` for rows to include, and `FALSE` for rows to exclude. Default is "all", equivalent to `rep(TRUE, nObs)`.

functionality Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call `apollo_probabilities`, though the user can also call `apollo_probabilities` manually with a given functionality for testing/debugging. Possible values are:

- **"components"**: For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations.
- **"conditionals"**: For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws.
- **"estimate"**: For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- **"gradient"**: For model estimation, produces analytical gradients of the likelihood, where possible.
- **"output"**: Prepares output for post-estimation reporting.
- **"prediction"**: For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws.
- **"preprocess"**: Prepares likelihood functions for use in estimation.
- **"raw"**: For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
- **"report"**: Prepares output summarising model and choiceset structure.
- **"shares_LL"**: Produces overall model likelihood with constants only.
- **"utilities"**: Returns utilities at provided parameter values.

- "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "zero_LL": Produces overall model likelihood with all parameters at zero.

Details

In this implementation of the Nested Logit model, each nest must have a lambda parameter associated to it. For the model to be consistent with utility maximisation, the estimated value of the Lambda parameter of all nests should be between 0 and 1. Lambda parameters are inversely proportional to the correlation between the error terms of alternatives in a nest. If lambda=1, then there is no relevant correlation between the unobserved utility of alternatives in that nest. The tree must contain an upper nest called "root". The lambda parameter of the root is automatically set to 1 if not specified in nlNests, but can be changed by the user if desired (though not advised).

Value

The returned object depends on the value of argument `functionality` as follows.

- "components": Same as "estimate"
- "conditionals": Same as "estimate"
- "estimate": vector/matrix/array. Returns the probabilities for the chosen alternative for each observation.
- "gradient": List containing the likelihood and analytical gradients of the model component.
- "output": Same as "estimate".
- "prediction": List of vectors/matrices/arrays. Returns a list with the probabilities for all alternatives, with an extra element for the probability of the chosen alternative.
- "preprocess": Returns a list with pre-processed inputs, based on `nl_settings`.
- "raw": Same as "prediction"
- "report": List with tree structure and choice overview.
- "shares_LL": vector/matrix/array. Returns the probability of the chosen alternative when only constants are estimated.
- "utilities": Data frame containing individual IDs, observation numbers and utilities for each alternative, with unavailable alternatives set to NA.
- "validate": Same as "estimate", but it also runs a set of tests to validate the function inputs.
- "zero_LL": vector/matrix/array. Returns the probability of the chosen alternative when all parameters are zero.

apollo_normalDensity *Calculates density for a Normal distribution*

Description

Calculates density for a Normal distribution at a specific value with a specified mean and standard deviation and can also perform other operations based on the value of the functionality argument.

Usage

```
apollo_normalDensity(normalDensity_settings, functionality)
```

Arguments

normalDensity_settings

List of arguments to the functions. It must contain the following.

- componentName: Character. Name given to model component. If not provided by the user, Apollo will set the name automatically according to the element in P to which the function output is directed.
- mu: Numeric scalar. Intercept of the linear model.
- outcomeNormal: Numeric vector. Dependent variable.
- rows: Boolean vector. Consideration of which rows to include. Length equal to the number of observations (nObs), with entries equal to TRUE for rows to include, and FALSE for rows to exclude. Default is "all", equivalent to rep(TRUE, nObs).
- sigma: Numeric scalar. Standard deviation of the error component of the linear model.
- xNormal: Numeric vector. Single explanatory variable.

functionality Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call apollo_probabilities, though the user can also call apollo_probabilities manually with a given functionality for testing/debugging. Possible values are:

- "components": For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations.
- "conditionals": For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws.
- "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "gradient": For model estimation, produces analytical gradients of the likelihood, where possible.
- "hessian": For model estimation, produces analytical gradients and Hessians of the likelihood, where possible.
- "output": Prepares output for post-estimation reporting.

- "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws.
- "preprocess": Prepares likelihood functions for use in estimation.
- "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
- "report": Prepares output summarising model and choicest structure.
- "shares_LL": Produces overall model likelihood with constants only.
- "utilities": Returns utilities at provided parameter values.
- "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "zero_LL": Produces overall model likelihood with all parameters at zero.

Details

This function calculates the probability of the linear model outcome $\text{Normal} = \mu + x\text{Normal} + \epsilon$, where ϵ is a random error distributed $\text{Normal}(0, \sigma)$. If using this function in the context of an Integrated Choice and Latent Variable (ICLV) model with continuous indicators, then outcomeNormal would be the value of the indicator, $x\text{Normal}$ would be the value of the latent variable (possibly multiplied by a parameter to measure its correlation with the indicator, e.g. $x\text{Normal} = \lambda \cdot \text{LV}$), and μ would be an additional parameter to be estimated (the mean of the indicator, which should be fixed to zero if the indicator is centered around its mean beforehand).

Value

The returned object depends on the value of argument `functionality` as follows.

- "components": Same as "estimate"
- "conditionals": Same as "estimate"
- "estimate": vector/matrix/array. Returns the likelihood for each observation.
- "gradient": List containing the likelihood and gradient of the model component.
- "hessian": List containing the likelihood, gradient and Hessian of the model component.
- "output": Same as "estimate".
- "prediction": Predicted value at the observation level.
- "preprocess": Returns a list with pre-processed inputs, based on `normalDensity_settings`.
- "raw": Same as "estimate"
- "report": List containing captured diagnostic output for the dependent variable overview.
- "shares_LL": Not implemented. Returns a vector of NA with as many elements as observations.
- "utilities": Data frame containing individual IDs, observation numbers and the $x\text{Normal}$ values, with excluded rows set to NA.
- "validate": Same as "estimate", but it also runs a set of tests to validate the function inputs.
- "zero_LL": Not implemented. Returns a vector of NA with as many elements as observations.

apollo_ol

Calculates Ordered Logit probabilities

Description

Calculates the probabilities of an Ordered Logit model and can also perform other operations based on the value of the functionality argument.

Usage

```
apollo_ol(ol_settings, functionality)
```

Arguments

- | | |
|---------------|---|
| ol_settings | <p>List of settings for the OL model. It should include the following.</p> <ul style="list-style-type: none"> • coding: Numeric or character vector. Optional argument. Defines the order of the levels in outcomeOrdered. The first value is associated with the lowest level of outcomeOrdered, and the last one with the highest value. If not provided, is assumed to be 1:(length(tau) + 1). • componentName: Character. Name given to model component. If not provided by the user, Apollo will set the name automatically according to the element in P to which the function output is directed. • outcomeOrdered: Numeric vector. Dependent variable. The coding of this variable is assumed to be from 1 to the maximum number of different levels. For example, if the ordered response has three possible values: "never", "sometimes" and "always", then it is assumed that outcomeOrdered contains "1" for "never", "2" for "sometimes", and 3 for "always". If another coding is used, then it should be specified using the coding argument. • rows: Boolean vector. TRUE if a row must be considered in the calculations, FALSE if it must be excluded. It must have length equal to the length of argument outcomeOrdered. Default value is "all", meaning all rows are considered in the calculation. • tau: List of numeric vectors/matrices/3-dim arrays. Thresholds. As many as number of different levels in the dependent variable - 1. Extreme thresholds are fixed at -inf and +inf. Mixing is allowed in thresholds. Can also be a matrix with as many rows as observations and as many columns as thresholds. • utility: Numeric vector/matrix/3-dim array. A single explanatory variable (usually a latent variable). Must have the same number of rows as outcomeOrdered. |
| functionality | <p>Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call apollo_probabilities, though the user can also call apollo_probabilities manually with a given functionality for testing/debugging. Possible values are:</p> |

- "components": For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations.
- "conditionals": For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws.
- "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "gradient": For model estimation, produces analytical gradients of the likelihood, where possible.
- "output": Prepares output for post-estimation reporting.
- "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws.
- "preprocess": Prepares likelihood functions for use in estimation.
- "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
- "report": Prepares output summarising model and choiceset structure.
- "shares_LL": Produces overall model likelihood with constants only.
- "utilities": Returns utilities at provided parameter values.
- "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "zero_LL": Produces overall model likelihood with all parameters at zero.

Details

This function estimates an Ordered Logit model of the type: $y^* = V + \text{epsilon}$ outcomeOrdered = 1 if $-\text{Inf} < y^* < \text{tau}[1]$ 2 if $\text{tau}[1] < y^* < \text{tau}[2]$... maxLvl if $\text{tau}[\text{length}(\text{tau})] < y^* < +\text{Inf}$ Where epsilon is distributed standard logistic, and the values 1, 2, ..., maxLvl can be replaced by coding[1], coding[2], ..., coding[maxLvl]. The behaviour of the function changes depending on the value of the functionality argument.

Value

The returned object depends on the value of argument functionality as follows.

- "components": Same as "estimate"
- "conditionals": Same as "estimate"
- "estimate": vector/matrix/array. Returns the probabilities for the chosen alternative for each observation.
- "gradient": List containing the likelihood and gradient of the model component.
- "output": Same as "estimate".
- "prediction": List of vectors/matrices/arrays. Returns a list with the probabilities for all possible levels, with an extra element for the probability of the chosen alternative.
- "preprocess": Returns a list with pre-processed inputs, based on ol_settings.

- "raw": Same as "prediction"
- "report": List containing captured diagnostic output for the dependent variable overview.
- "shares_LL": vector/matrix/array. Returns the probability of the chosen alternative when only constants are estimated.
- "utilities": Data frame containing individual IDs, observation numbers and the ordered-logit utility, with excluded rows set to NA.
- "validate": Same as "estimate", but it also runs a set of tests to validate the function inputs.
- "zero_LL": Not implemented. Returns a vector of NA with as many elements as observations.

apollo_op

Calculates Ordered Probit probabilities

Description

Calculates the probabilities of an Ordered Probit model and can also perform other operations based on the value of the functionality argument.

Usage

```
apollo_op(op_settings, functionality)
```

Arguments

- | | |
|-------------|--|
| op_settings | <p>List of settings for the OP model. It should include the following.</p> <ul style="list-style-type: none"> • coding: Numeric or character vector. Optional argument. Defines the order of the levels in outcomeOrdered. The first value is associated with the lowest level of outcomeOrdered, and the last one with the highest value. If not provided, is assumed to be 1:(length(tau) + 1). • componentName: Character. Name given to model component. If not provided by the user, Apollo will set the name automatically according to the element in P to which the function output is directed. • outcomeOrdered: Numeric vector. Dependent variable. The coding of this variable is assumed to be from 1 to the maximum number of different levels. For example, if the ordered response has three possible values: "never", "sometimes" and "always", then it is assumed that outcomeOrdered contains "1" for "never", "2" for "sometimes", and 3 for "always". If another coding is used, then it should be specified using the coding argument. • rows: Boolean vector. TRUE if a row must be considered in the calculations, FALSE if it must be excluded. It must have length equal to the length of argument outcomeOrdered. Default value is "all", meaning all rows are considered in the calculation. • tau: List of numeric vectors/matrices/3-dim arrays. Thresholds. As many as number of different levels in the dependent variable - 1. Extreme thresholds are fixed at -inf and +inf. Mixing is allowed in thresholds. Can also be a matrix with as many rows as observations and as many columns as thresholds. |
|-------------|--|

- **utility**: Numeric vector/matrix/3-dim array. A single explanatory variable (usually a latent variable). Must have the same number of rows as outcomeOrdered.
- functionality** Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call `apollo_probabilities`, though the user can also call `apollo_probabilities` manually with a given functionality for testing/debugging. Possible values are:
- **"components"**: For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations.
 - **"conditionals"**: For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws.
 - **"estimate"**: For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
 - **"gradient"**: For model estimation, produces analytical gradients of the likelihood, where possible.
 - **"output"**: Prepares output for post-estimation reporting.
 - **"prediction"**: For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws.
 - **"preprocess"**: Prepares likelihood functions for use in estimation.
 - **"raw"**: For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
 - **"report"**: Prepares output summarising model and choiceset structure.
 - **"shares_LL"**: Produces overall model likelihood with constants only.
 - **"utilities"**: Returns utilities at provided parameter values.
 - **"validate"**: Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
 - **"zero_LL"**: Produces overall model likelihood with all parameters at zero.

Details

This function estimates an ordered probit model of the type:

$$y^* = V + \epsilon y = 1 \text{ if } -\infty < y^* < \tau_1, 2 \text{ if } \tau_1 < y^* < \tau_2, \dots, \max(y) \text{ if } \tau_{\max(y)-1} < y^* < \infty$$

Where ϵ is distributed standard normal, and the values $1, 2, \dots, \max(y)$ can be replaced by `coding[1]`, `coding[2]`, ..., `coding[maxLvl]`. The behaviour of the function changes depending on the value of the **functionality** argument.

Value

The returned object depends on the value of argument **functionality** as follows.

- **"components"**: Same as **"estimate"**

- "conditionals": Same as "estimate"
- "estimate": vector/matrix/array. Returns the probabilities for the chosen alternative for each observation.
- "gradient": List containing the likelihood and gradient of the model component.
- "output": Same as "estimate".
- "prediction": List of vectors/matrices/arrays. Returns a list with the probabilities for all possible levels, with an extra element for the probability of the chosen alternative.
- "preprocess": Returns a list with pre-processed inputs, based on op_settings.
- "raw": Same as "prediction"
- "report": List containing captured diagnostic output for the dependent variable overview.
- "shares_LL": vector/matrix/array. Returns the probability of the chosen alternative when only constants are estimated.
- "utilities": Data frame containing individual IDs, observation numbers and the ordered-probit utility, with excluded rows set to NA.
- "validate": Same as "estimate", but it also runs a set of tests to validate the function inputs.
- "zero_LL": Not implemented. Returns a vector of NA with as many elements as observations.

apollo_outOfSample	<i>Cross-validation of fit (LL)</i>
--------------------	-------------------------------------

Description

Randomly generates estimation and validation samples, estimates the model on the first and calculates the likelihood for the second, then repeats.

Usage

```
apollo_outOfSample(
  apollo_beta,
  apollo_fixed,
  apollo_probabilities,
  apollo_inputs,
  estimate_settings = list(estimationRoutine = "bgw", maxIterations = 200, writeIter =
    FALSE, hessianRoutine = "none", printLevel = 3L, silent = TRUE),
  outOfSample_settings = list(nRep = 10, validationSize = 0.1, samples = NA, rmse = NULL)
)
```

Arguments

apollo_beta	Named numeric vector. Names and values for parameters.
apollo_fixed	Character vector. Names (as defined in apollo_beta) of parameters whose value should not change during estimation.

apollo_probabilities

Function. Returns probabilities of the model to be estimated. Must receive three arguments:

- **apollo_beta**: Named numeric vector. Names and values of model parameters.
- **apollo_inputs**: List containing options of the model. See [apollo_validateInputs](#).
- **functionality**: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL".

apollo_inputs List grouping most common inputs. Created by function [apollo_validateInputs](#).

estimate_settings

List. Options controlling the estimation process. See [apollo_estimate](#). The defaults used inside `apollo_outOfSample` include `estimationRoutine="bgw"`, `maxIterations=200`, `writeIter=FALSE`, `hessianRoutine="none"`, `printLevel=3L` and `silent=TRUE`.

outOfSample_settings

List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional.

nRep Numeric scalar. Number of times a different pair of estimation and validation sets are to be extracted from the full database. Default is 10.

rmse Character matrix with two columns. Used to calculate Root Mean Squared Error (RMSE) of prediction. The first column must contain the names of observed outcomes in the database. The second column must contain the names of the predicted outcomes as returned by `apollo_prediction`. If omitted or NULL, no RMSE is calculated. This only works for models with a single component.

samples Numeric matrix or data.frame. Optional argument. Must have as many rows as observations in the database, and as many columns as number of repetitions wanted. Each column represents a re-sample, and each element must be a 0 if the observation should be assigned to the estimation sample, or 1 if the observation should be assigned to the prediction sample. If this argument is provided, then `nRep` and `validationSize` are ignored. Note that this allows sampling at the observation rather than the individual level.

validationSize Numeric scalar. Size of the validation sample. Can be a percentage of the sample (0-1) or the number of individuals in the validation sample (>1). Default is 0.1.

Details

A common way to test for overfitting of a model is to measure its fit on a sample not used during estimation that is, measuring its out-of-sample fit. A simple way to do this is splitting the complete available dataset in two parts: an estimation sample, and a validation sample. The model of interest is estimated using only the estimation sample, and then those estimated parameters are used to measure the fit of the model (e.g. the log-likelihood of the model) on the validation sample. Doing this with only one validation sample, however, may lead to biased results, as a particular validation sample need not be representative of the population. One way to minimise this issue is to randomly

draw several pairs of estimation and validation samples from the complete dataset, and apply the procedure to each pair.

The splitting of the database into estimation and validation samples is done at the individual level, not at the observation level. If sampling is required at the observation level, which is not recommended for panel data, then the optional `outOfSample_settings$samples` argument should be provided.

This function writes two different files to the `working/output` directory:

- `modelName_outOfSample_params.csv`: Records the estimated parameters, final log-likelihood, and number of observations on each repetition.
- `modelName_outOfSample_samples.csv`: Records the sample composition of each repetition.

Both files are updated after each successful repetition.

When run, this function will look for the two files above in the `working/output` directory. If they are found, the function will attempt to pick up re-sampling from where those files left off. This is useful in cases where the original cross-validation was interrupted, or when additional re-sampling wants to be performed.

Value

Invisibly returns a matrix with the average log-likelihood per observation in the estimation and validation samples, plus the percentage difference, for each repetition and their average. Files with repetition-level estimates, likelihoods, sample composition and optional RMSE values are written to the `working/output` directory.

<code>apollo_ownModel</code>	<i>Calculates own model probabilities</i>
------------------------------	---

Description

Receives functions or expressions for each functionality so that a user-defined model can interface with Apollo.

Usage

```
apollo_ownModel(ownModel_settings, functionality)
```

Arguments

`ownModel_settings`

List of arguments. Only likelihood is mandatory.

- `componentName`: Character. Optional name for the model component. If omitted, a default name is assigned.
- `gradient`: Function or expression used to calculate the gradient of the likelihood. If not provided, Apollo will attempt to calculate it automatically.
- `likelihood`: Function or expression used to calculate the likelihood of the model. Should evaluate to a vector, matrix, or 3-dimensional array.

- **prediction**: Function or expression used to calculate the prediction of the model. Should evaluate to a vector, matrix, or 3-dimensional array.
- **report**: List of functions or expressions used to produce a text report summarising the input and parameter estimates of the model. Should contain two elements: "data" (with a summary of the input data), and "param" (with a summary of the estimated parameters).
- **rows**: Boolean vector. Optional row filter. By default, all rows are used.
- **shares_LL**: Function or expression used to calculate the likelihood of the constants-only model.
- **zero_LL**: Function or expression used to calculate the likelihood of the base model (e.g. equiprobable model).

functionality Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call `apollo_probabilities`, though the user can also call `apollo_probabilities` manually with a given functionality for testing/debugging. Possible values are:

- **"components"**: For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations.
- **"conditionals"**: For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws.
- **"estimate"**: For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- **"gradient"**: For model estimation, produces analytical gradients of the likelihood, where possible.
- **"output"**: Prepares output for post-estimation reporting.
- **"prediction"**: For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws.
- **"preprocess"**: Prepares likelihood functions for use in estimation.
- **"raw"**: For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
- **"report"**: Prepares output summarising model and choiceset structure.
- **"shares_LL"**: Produces overall model likelihood with constants only.
- **"validate"**: Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- **"zero_LL"**: Produces overall model likelihood with all parameters at zero.

Value

The returned object depends on the value of argument `functionality` as follows.

- **"components"**: Same as **"estimate"**
- **"conditionals"**: Same as **"estimate"**

- "estimate": vector/matrix/array. Returns the probabilities for the chosen alternative for each observation.
- "gradient": List containing the likelihood and gradient of the model component.
- "output": Same as "estimate".
- "prediction": List of vectors/matrices/arrays. Returns a list with the probabilities for all alternatives, with an extra element for the probability of the chosen alternative.
- "preprocess": Returns a list with pre-processed inputs, based on ownModel_settings.
- "raw": Same as "prediction"
- "report": User-defined report output, or NULL if no report function was supplied.
- "shares_LL": vector/matrix/array. Returns the probability of the chosen alternative when only constants are estimated.
- "validate": Same as "estimate", but it also runs a set of tests to validate the function inputs.
- "zero_LL": vector/matrix/array. Returns the probability of the chosen alternative when all parameters are zero.

apollo_panelProd	<i>Calculates product across observations from same individual.</i>
------------------	---

Description

Multiplies likelihood of observations from the same individual, or adds the log of them.

Usage

```
apollo_panelProd(P, apollo_inputs, functionality)
```

Arguments

- | | |
|---------------|--|
| P | List of vectors, matrices or 3-dim arrays. Likelihood of the model components. |
| apollo_inputs | List grouping most common inputs. Created by function apollo_validateInputs . |
| functionality | Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call <code>apollo_probabilities</code> , though the user can also call <code>apollo_probabilities</code> manually with a given functionality for testing/debugging. Possible values are: <ul style="list-style-type: none"> • "components": For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations. • "conditionals": For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws. • "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws. • "gradient": For model estimation, produces analytical gradients of the likelihood, where possible. |

- "hessian": For model estimation, produces analytical gradients and Hessians of the likelihood after applying the product rule across observations for the same individual.
- "output": Prepares output for post-estimation reporting.
- "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws.
- "preprocess": Prepares likelihood functions for use in estimation.
- "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
- "report": Prepares output summarising model and choicest structure.
- "shares_LL": Produces overall model likelihood with constants only.
- "utilities": Returns utilities at provided parameter values.
- "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "zero_LL": Produces overall model likelihood with all parameters at zero.

Details

This function should be called inside `apollo_probabilities` only if the data has a panel structure. It should be called after `apollo_avgIntraDraws` if intra-individual draws are used.

Value

Argument `P` with (for most functionalities) the original contents after multiplying across observations at the individual level. Shape depends on argument functionality.

- "components": Returns `P` without changes.
- "conditionals": Returns `P` after multiplying observations at the individual level, without averaging across inter-individual draws. Drops all components except "model".
- "estimate": Returns `P` containing the likelihood of the model after multiplying observations at the individual level. Drops all components except "model".
- "gradient": Returns `P` containing the gradient of the likelihood after applying the product rule across observations for the same individual.
- "hessian": Returns a list containing the likelihood, gradient and Hessian of the model at the individual level after applying the product rule across observations for the same individual.
- "output": Returns `P` containing the likelihood of the model after multiplying observations at the individual level.
- "prediction": Returns `P` without changes.
- "preprocess": Returns `P` without changes.
- "raw": Returns `P` without changes.
- "report": Returns `P` without changes.

- "shares_LL": Returns P containing the likelihood of the model after multiplying observations at the individual level.
- "validate": Returns P containing the likelihood of the model after multiplying observations at the individual level. Drops all components except "model".
- "utilities": Returns P without changes.
- "zero_LL": Returns P containing the likelihood of the model after multiplying observations at the individual level.

apollo_prediction	<i>Predicts using an estimated model</i>
-------------------	--

Description

Calculates apollo_probabilities with functionality="prediction".

Usage

```
apollo_prediction(
  model,
  apollo_probabilities,
  apollo_inputs,
  prediction_settings = list(),
  modelComponent = NA
)
```

Arguments

- | | |
|----------------------|---|
| model | Model object. Estimated model object as returned by function apollo_estimate . A user can also simply provide a vector of parameter values instead of a whole model object, allowing for prediction to take place without having estimated a model. |
| apollo_probabilities | Function. Returns probabilities of the model to be estimated. Must receive three arguments: <ul style="list-style-type: none"> • apollo_beta: Named numeric vector. Names and values of model parameters. • apollo_inputs: List containing options of the model. See apollo_validateInputs. • functionality: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL". |
| apollo_inputs | List grouping most common inputs. Created by function apollo_validateInputs . |
| prediction_settings | List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional. |

- `includeChosen`: Boolean. If TRUE, the predicted choice for each observation is included in the output. Default is FALSE.
- `modelComponent`: Character. Name of component of `apollo_probabilities` output to calculate predictions for. Default is to predict for all components.
- `nRep`: Scalar integer. Only used for models that require simulation for prediction (e.g. MDCEV). Number of draws used to calculate prediction. Default is 100.
- `runs`: Numeric. Number of runs to use for computing confidence intervals of predictions. Default is 1, meaning no confidence intervals are calculated.
- `silent`: Boolean. If TRUE, this function will not print output to screen. Default is FALSE, unless `apollo_inputs$silent=TRUE`.
- `simChoice`: Boolean. If TRUE, simulated choices are added to the output. FALSE by default.
- `summary`: Boolean. If TRUE, a summary of the prediction is printed to screen. TRUE by default.

`modelComponent` **Deprecated.** Same as `modelComponent` inside `prediction_settings`.

Details

Structure of predictions are simplified before returning, e.g. list of vectors are turned into a matrix.

Value

Predictions from the model. If `runs=1`, the function returns a data frame for a single component, or a named list of data frames for multiple components. If `runs>1`, each component is returned as a list with `at_estimates`, containing predictions at the estimated parameter values, and `draws`, an array of predictions obtained using draws from the asymptotic distribution of the estimates. If no predictions are available, the function returns NULL.

<code>apollo_preEstimate</code>	<i>Conducts all the pre-estimation steps for a model</i>
---------------------------------	--

Description

Conducts all the pre-estimation steps for a model using the likelihood function defined by `apollo_probabilities`.

Usage

```
apollo_preEstimate(
  apollo_beta,
  apollo_fixed,
  apollo_probabilities,
  apollo_inputs,
  estimate_settings = NA
)
```

Arguments

- apollo_beta** Named numeric vector. Names and values for parameters.
- apollo_fixed** Character vector. Names (as defined in **apollo_beta**) of parameters whose value should not change during estimation.
- apollo_probabilities** Function. Returns probabilities of the model to be estimated. Must receive three arguments:
- **apollo_beta**: Named numeric vector. Names and values of model parameters.
 - **apollo_inputs**: List containing options of the model. See [apollo_validateInputs](#).
 - **functionality**: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL".
- apollo_inputs** List grouping most common inputs. Created by function [apollo_validateInputs](#).
- estimate_settings** List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional.
- **bgw_settings**: List. Additional arguments to the BGW optimisation method. See [bgw_mle](#) for more details.
 - **bootstrapSE**: Numeric. Number of bootstrap samples to calculate standard errors. Default is 0, meaning no bootstrap s.e. will be calculated. Number must zero or a positive integer. Only used if `apollo_control$estMethod!="HB"`.
 - **bootstrapSeed**: Numeric scalar (integer). Random number generator seed to generate the bootstrap samples. Only used if `bootstrapSE>0`. Default is 24.
 - **constraints**: Character vector. Linear constraints on parameters to estimate. For example `c('b1>0', 'b1 + 2*b2>1')`. Only `>`, `<` and `=` can be used. Inequalities cannot be mixed with equality constraints, e.g. `c(b1-b2=0, b2>0)` will fail. All parameter names must be on the left side. Fixed parameters cannot go into constraints. Alternatively, constraints can be defined as in [maxLik](#). Constraints can only be used with maximum likelihood estimation and the BFGS routine in particular.
 - **estimationRoutine**: Character. Estimation method. Can take values "bfgs", "bgw", "bhhh", or "nr". Used only if `apollo_control$HB` is FALSE. Default is "bgw".
 - **hessianRoutine**: Character. Name of routine used to calculate the Hessian of the log-likelihood function after estimation. Valid values are "analytic" (default), "numDeriv" (to use the numeric routine in package `numDeriv`), "maxLik" (to use the numeric routine in package `maxLik`), and "none" to avoid calculating the Hessian and the covariance matrix. Only used if `apollo_control$HB=FALSE`.
 - **maxIterations**: Numeric. Maximum number of iterations of the estimation routine before stopping. Used only if `apollo_control$HB` is FALSE. Default is 200.

- maxLik_settings: List. Additional settings for maxLik. See argument control in [maxBFGS](#), [maxBHHH](#) and [maxNM](#) for more details. Only used for maximum likelihood estimation.
- numDeriv_method: Character. Method used for numerical differentiation when calculating the covariance matrix. Can be "Richardson" or "simple", Only used if analytic gradients are available. See argument method in [grad](#) for more details.
- numDeriv_settings: List. Additional arguments to the method used by numDeriv to calculate the Hessian. See argument method.args in [grad](#) for more details.
- printLevel: Higher values render more verbous outputs. Can take values 0, 1, 2 or 3. Ignored if apollo_control\$HB is TRUE. Default is 3.
- scaleAfterConvergence: Logical. Used to increase numerical precision of convergence. If TRUE, parameters are scaled to 1 after convergence, and the estimation is repeated from this new starting values. Results are reported scaled back, so it is a transparent process for the user. Default is FALSE.
- scaleHessian: Logical. If TRUE, parameters are scaled to 1 for Hessian estimation. Default is TRUE.
- scaling: Named vector. Names of elements should match those in apollo_beta. Optional scaling for parameters. If provided, for each parameter i, (apollo_beta[i]/scaling[i]) is optimised, but scaling[i]*(apollo_beta[i]/scaling[i]) is used during estimation. For example, if parameter b3=10, while b1 and b2 are close to 1, then setting scaling = c(b3=10) can help estimation, specially the calculation of the Hessian. Reports will still be based on the non-scaled parameters.
- silent: Logical. If TRUE, no information is printed to the console during estimation. Default is FALSE.
- validateGrad: Logical. If TRUE, the analytical gradient (if used) is compared to the numerical one. Default is FALSE.
- writeIter: Logical. Writes value of the parameters in each iteration to a csv file. Works only if estimation_routine=="bfgs"|"bgw". Default is TRUE.

Value

model object

apollo_prepareProb	<i>Checks likelihood function</i>
--------------------	-----------------------------------

Description

Checks that the likelihood function for the model is in the appropriate format to be returned.

Usage

```
apollo_prepareProb(P, apollo_inputs, functionality)
```

Arguments

P	List of vectors, matrices or 3-dim arrays. Likelihood of the model components.
apollo_inputs	List grouping most common inputs. Created by function apollo_validateInputs .
functionality	Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call <code>apollo_probabilities</code>, though the user can also call <code>apollo_probabilities</code> manually with a given functionality for testing/debugging. Possible values are: • "components": For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations. • "conditionals": For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws. • "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws. • "gradient": For model estimation, produces analytical gradients of the likelihood, where possible. • "hessian": For model estimation, produces the analytical Hessian of the log-likelihood, where possible. • "output": Prepares output for post-estimation reporting. • "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws. • "preprocess": Prepares likelihood functions for use in estimation. • "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws. • "report": Prepares output summarising model and choiceset structure. • "shares_LL": Produces overall model likelihood with constants only. • "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws. • "utilities": Returns utilities at provided parameter values. • "zero_LL": Produces overall model likelihood with all parameters at zero.

Details

This function should be called inside `apollo_probabilities`, near the end of it, just before `return(P)`. This function only performs checks on the shape of P, but does not change its values.

Value

Argument P with (for most functionalities) the original contents. Output depends on argument functionality.

- "components": Returns P without changes.
- "conditionals": Returns only the "model" component of argument P.
- "estimate": Returns the "model" component of argument P, after checking that panel multiplication and draw averaging have already been applied where required.
- "gradient": Returns a matrix of log-likelihood gradients, with one row per likelihood contribution and one column per estimated parameter.
- "hessian": Returns the analytical Hessian matrix of the log-likelihood.
- "output": Returns argument P without any changes to its content, but gives names to unnamed elements.
- "prediction": Returns argument P without any changes.
- "preprocess": Returns argument P without any changes to its content, but gives names to elements corresponding to componentNames.
- "raw": Returns argument P without any changes.
- "report": Returns P without changes.
- "shares_LL": Returns argument P without any changes to its content, but gives names to unnamed elements.
- "validate": Returns argument P without any changes.
- "utilities": Returns P without changes.
- "zero_LL": Returns argument P without any changes to its content, but gives names to unnamed elements.

apollo_preprocess	<i>Pre-process input for multiple models return</i>
-------------------	---

Description

Pre-process input for multiple models return

Usage

```
apollo_preprocess(inputs, modelType, functionality, apollo_inputs)
```

Arguments

inputs	List of settings
modelType	Character. Type of model, e.g. "mnl", "nl", "cnl", etc.
functionality	Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call <code>apollo_probabilities</code>, though the user can also call <code>apollo_probabilities</code> manually with a given functionality for testing/debugging. Possible values are: • "components": For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations. • "conditionals": For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws. • "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws. • "gradient": For model estimation, produces analytical gradients of the likelihood, where possible. • "output": Prepares output for post-estimation reporting. • "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws. • "preprocess": Prepares likelihood functions for use in estimation. • "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws. • "report": Prepares output summarising model and choicest structure. • "shares_LL": Produces overall model likelihood with constants only. • "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws. • "zero_LL": Produces overall model likelihood with all parameters at zero.
apollo_inputs	List grouping most common inputs. Created by function apollo_validateInputs .

Value

The returned object is a pre-processed version of the model settings. This is independent of functionality, but the function is only called during preprocessing.

apollo_print	<i>Prints message to terminal</i>
--------------	-----------------------------------

Description

Prints message to terminal if `apollo_inputs$silent` is FALSE

Usage

```
apollo_print(txt, nSignifD = 4, widthLim = 11, pause = 0, type = "t")
```

Arguments

txt	Character, what to print.
nSignifD	Optional numeric integer. Minimum number of significant digits when printing numeric matrices. Default is 4.
widthLim	Optional numeric integer. Minimum width (in characters) of each column when printing numeric matrices. Default is 11
pause	Scalar integer. Number of seconds the execution will pause after printing the message. Default is 0.
type	Character. "t" for regular text (default), "w" for warning, "i" for information.

Value

Nothing

apollo_readBeta	<i>Reads parameters from file</i>
-----------------	-----------------------------------

Description

Reads in parameters from a previously estimated model and copies the values to the given apollo_beta vector, only for those parameters whose name matches.

Usage

```
apollo_readBeta(
  apollo_beta,
  apollo_fixed,
  inputModelName,
  overwriteFixed = FALSE
)
```

Arguments

apollo_beta	Named numeric vector. Names and values for parameters.
apollo_fixed	Character vector. Names (as defined in apollo_beta) of parameters whose value should not change during estimation.
inputModelName	Character. modelName for model from which results are used as starting values.
overwriteFixed	Boolean. TRUE if starting values for fixed parameters should also be updated from the input file. Default is FALSE.

Details

This function will update the values of the parameters in its argument `apollo_beta` with the matching values in the file `(inputModelName)_estimates.csv`. If there is no match for a given parameter in `apollo_beta`, its value will not be updated.

Value

Named numeric vector. Names and updated starting values for parameters.

apollo_rrm	<i>Calculates Random Regret Minimisation model probabilities</i>
------------	--

Description

Calculates the probabilities of a Random Regret Minimisation model and can also perform other operations based on the value of the functionality argument.

Usage

```
apollo_rrm(rrm_settings, functionality)
```

Arguments

- | | |
|--------------|--|
| rrm_settings | <p>List of inputs of the RRM model. It should contain the following.</p> <ul style="list-style-type: none">alternatives: Named numeric vector. Names of alternatives and their corresponding value in choiceVar.avail: Named list of numeric vectors or scalars. Availabilities of alternatives, one element per alternative. Names of elements must match those in alternatives. Values can be 0 or 1. These can be scalars or vectors (of length equal to rows in the database). A user can also specify <code>avail=1</code> to indicate universal availability, or omit the setting completely.choiceset_scaling: Numeric vector/scalar or character expression. Optional choiceset-scaling term. If omitted, a value of 1 is used.choiceVar: Numeric vector. Contains choices for all observations. It will usually be a column from the database. Values are defined in alternatives.componentName: Character. Name given to model component. If not provided by the user, Apollo will set the name automatically according to the element in P to which the function output is directed.regret_inputs: Named list of regret functions. This should contain one list per attribute, where these lists themselves contain two vectors, namely a vector of attributes (at the alternative level) and parameters (either generic or attribute specific). Zeros can be used for omitted attributes for some alternatives. The order for each attribute needs to be the same as the order in alternatives. |
|--------------|--|

- **regret_scale**: Named list or vector of regret scales. This should have the same length as `rrm_settings$regret_inputs` or be a single entry in the case of a generic scale parameter across regret attributes. If omitted, a value of 1 is used.
- **rum_inputs**: Named list of optional deterministic utilities. Utilities of the alternatives to be included in combined RUM-RRM models. Names of elements must match those in `alternatives`. If omitted, zero utilities are used for all alternatives.
- **rows**: Boolean vector. Consideration of which rows to include. Length equal to the number of observations (`nObs`), with entries equal to `TRUE` for rows to include, and `FALSE` for rows to exclude. Default is `"all"`, equivalent to `rep(TRUE, nObs)`.
- **rum_inputs**: Named list of (optional) deterministic utilities. Utilities of the alternatives to be included in combined RUM-RRM models. Names of elements must match those in `alternatives`.

functionality Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call `apollo_probabilities`, though the user can also call `apollo_probabilities` manually with a given `functionality` for testing/debugging. Possible values are:

- `"components"`: For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations.
- `"conditionals"`: For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws.
- `"estimate"`: For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- `"gradient"`: For model estimation, produces analytical gradients of the likelihood, where possible.
- `"output"`: Prepares output for post-estimation reporting.
- `"prediction"`: For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws.
- `"preprocess"`: Prepares likelihood functions for use in estimation.
- `"raw"`: For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
- `"report"`: Prepares output summarising model and choiceset structure.
- `"shares_LL"`: Produces overall model likelihood with constants only.
- `"validate"`: Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- `"zero_LL"`: Produces overall model likelihood with all parameters at zero.

Value

The returned object depends on the value of argument `functionality` as follows.

- "components": Same as "estimate"
- "conditionals": Same as "estimate"
- "estimate": vector/matrix/array. Returns the probabilities for the chosen alternative for each observation.
- "gradient": List containing the likelihood and gradient of the model component.
- "output": Same as "estimate".
- "prediction": List of vectors/matrices/arrays. Returns a list with the probabilities for all alternatives, with an extra element for the probability of the chosen alternative.
- "preprocess": Returns a list with pre-processed inputs, based on `rrm_settings`.
- "raw": Same as "prediction"
- "report": List containing captured diagnostic output for the choice overview.
- "shares_LL": vector/matrix/array. Returns the probability of the chosen alternative when only constants are estimated.
- "utilities": Data frame containing individual IDs, observation numbers and regret functions for each alternative, with unavailable alternatives set to NA.
- "validate": Same as "estimate", but it also runs a set of tests to validate the function inputs.
- "zero_LL": vector/matrix/array. Returns the probability of the chosen alternative when all parameters are zero.

apollo_saveOutput	<i>Saves estimation results to files.</i>
-------------------	---

Description

Writes files in the working/output directory with the estimation results.

Usage

```
apollo_saveOutput(model, saveOutput_settings = NA)
```

Arguments

<code>model</code>	Model object. Estimated model object as returned by function apollo_estimate .
<code>saveOutput_settings</code>	List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional. • <code>printBHHH</code>: Logical. TRUE for printing BHHH standard errors. FALSE by default. • <code>printChange</code>: Boolean. TRUE for printing difference between starting values and estimates. FALSE by default. • <code>printClassical</code>: Boolean. TRUE for printing classical standard errors. TRUE by default.

- `printCorr`: Boolean. TRUE for printing parameters correlation matrix. If `printClassical=TRUE`, both classical and robust matrices are printed. For Bayesian estimation, this setting is used for the correlation of random parameters. TRUE by default.
- `printCovar`: Boolean. TRUE for printing parameters covariance matrix. If `printClassical=TRUE`, both classical and robust matrices are printed. For Bayesian estimation, this setting is used for the covariance of random parameters. TRUE by default.
- `printDataReport`: Boolean. TRUE for printing summary of choices in database and other diagnostics. TRUE by default.
- `printFixed`: Logical. TRUE for printing fixed parameters among estimated parameter. TRUE by default.
- `printFunctions`: Boolean. TRUE for printing `apollo_control`, `apollo_randCoeff` (when available), `apollo_lcPars` (when available) and `apollo_probabilities`. TRUE by default.
- `printHBconvergence`: Boolean. TRUE for printing Geweke convergence tests. TRUE by default.
- `printHBiterations`: Boolean. TRUE for printing an iterations report for HB estimation. TRUE by default.
- `printModelStructure`: Boolean. TRUE for printing model structure. TRUE by default.
- `printOutliers`: Boolean or Scalar. TRUE for printing 20 individuals with worst average fit across observations. FALSE by default. If Scalar is given, this replaces the default of 20.
- `printPVal`: Boolean or Scalar. TRUE or 1 for printing p-values for one-sided test, 2 for printing p-values for two-sided test, FALSE for not printing p-values. FALSE by default.
- `printRobust`: Logical. TRUE for printing robust standard errors. TRUE by default.
- `printT1`: Boolean. If TRUE, t-test for $H_0: \text{apollo_beta}=1$ are printed. FALSE by default.
- `saveEst`: Boolean. TRUE for saving estimated parameters and standard errors to a CSV file. TRUE by default.
- `saveCorr`: Boolean. TRUE for saving estimated correlation matrix to a CSV file. FALSE by default.
- `saveCov`: Boolean. TRUE for saving estimated covariance matrix to a CSV file. FALSE by default.
- `saveHBiterations`: Boolean. TRUE for including HB iterations in the saved model object. FALSE by default.
- `saveModelObject`: Boolean. TRUE to save the R model object to a file (use [apollo_loadModel](#) to load it to memory). TRUE by default.
- `saveOld`: Boolean. If TRUE, existing files are kept with an added OLD suffix. If not, they are overwritten. TRUE by default.
- `writeF12`: Boolean. TRUE for writing results into an F12 file (ALOGIT format). FALSE by default.

Details

Estimation results are saved in different files in the working/output directory: In addition, depending on the settings and estimation method, the function may also write:

- `modelName_BHHHvarcov.csv`: BHHH covariance matrix, if BHHH standard errors are available and covariance matrices are saved.
- `modelName_BHHHcorr.csv`: BHHH correlation matrix, if BHHH standard errors are available and correlation matrices are saved.
- `modelName_bootcovar.csv`: Bootstrap covariance matrix, if bootstrap standard errors are available and covariance matrices are saved.
- `modelName_bootcorr.csv`: Bootstrap correlation matrix, if bootstrap standard errors are available and correlation matrices are saved.
- `(modelName)_corr.csv` CSV file with the estimated classical correlation matrix. Only when bayesian estimation was not used.
- `(modelName)_covar.csv` CSV file with the estimated classical covariance matrix. Only when bayesian estimation was not used.
- `(modelName)_estimates.csv` CSV file with the estimated parameter values, their standard errors, and t-ratios.
- `(modelName).F12 F12` file with model results. Compatible with ALOGIT.
- `modelName_model.rds`: Saved model object, if `saveModelObject=TRUE`.
- `(modelName)_output.txt` Text file with the output produced by function `apollo_modelOutput`.
- `(modelName)_robcorr.csv` CSV file with the estimated robust correlation matrix. Only when bayesian estimation was not used.
- `(modelName)_robcovar.csv` CSV file with the estimated robust covariance matrix. Only when bayesian estimation was not used.

For models estimated using HB, additional files containing posterior means, posterior standard deviations, random-parameter summaries, and optionally iteration-level HB output may also be written.

Value

Invisibly returns TRUE after writing output files.

<code>apollo_searchStart</code>	<i>Searches for better starting values.</i>
---------------------------------	---

Description

Given a set of starting values and a range for them, searches for points with a better likelihood and steeper gradients.

Usage

```
apollo_searchStart(
  apollo_beta,
  apollo_fixed,
  apollo_probabilities,
  apollo_inputs,
  searchStart_settings = NA
)
```

Arguments

- apollo_beta** Named numeric vector. Names and values for parameters.
- apollo_fixed** Character vector. Names (as defined in `apollo_beta`) of parameters whose value should not change during estimation.
- apollo_probabilities**
Function. Returns probabilities of the model to be estimated. Must receive three arguments:
- `apollo_beta`: Named numeric vector. Names and values of model parameters.
 - `apollo_inputs`: List containing options of the model. See [apollo_validateInputs](#).
 - `functionality`: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "hessian", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL".
- apollo_inputs** List grouping most common inputs. Created by function [apollo_validateInputs](#).
- searchStart_settings**
List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional.
- `apolloBetaMax`: Vector. Maximum possible value of parameters when generating candidates. Ignored if `smartStart` is TRUE. Default is `apollo_beta + 0.1`.
 - `apolloBetaMin`: Vector. Minimum possible value of parameters when generating candidates. Ignored if `smartStart` is TRUE. Default is `apollo_beta - 0.1`.
 - `bgwIter`: Numeric scalar. Number of BGW iterations to perform at each stage to each remaining candidate. Default is 20.
 - `dTest`: Numeric scalar. Tolerance for test 1. A candidate is discarded if its distance in parameter space to a better one is smaller than `dTest`. Default is 1.
 - `gTest`: Numeric scalar. Tolerance for test 2. A candidate is discarded if the norm of its gradient is smaller than `gTest` AND its LL is further than `llTest` from a better candidate. Default is 10^{-3} .
 - `llTest`: Numeric scalar. Tolerance for test 2. A candidate is discarded if the norm of its gradient is smaller than `gTest` AND its LL is further than `llTest` from a better candidate. Default is 3.

- **maxStages**: Numeric scalar. Maximum number of search stages. The algorithm will stop when there is only one candidate left, or if it reaches this number of stages. Default is 5.
- **nCandidates**: Numeric scalar. Number of candidate sets of parameters to be used at the start. Should be an integer bigger than 1. Default is 100.
- **smartStart**: Boolean. If TRUE, candidates are randomly generated with more chances in the directions the Hessian indicates improvement of the LL function. Default is FALSE.

Details

This function implements a simplified version of the algorithm proposed by Bierlaire, M., Themans, M. & Zufferey, N. (2010), A Heuristic for Nonlinear Global Optimization, INFORMS Journal on Computing, 22(1), pp.59-70. The main difference lies in it implementing only two out of three tests on the candidates described by the authors. The implemented algorithm has the following steps.

1. Randomly draw `nCandidates` candidates from an interval given by the user.
2. Label all candidates with a valid log-likelihood (LL) as active.
3. Apply `bgwIter` iterations of the BGW algorithm to each active candidate.
4. Apply the following tests to each active candidate:
 - (a) Has the BGW search converged to a worse solution?
 - (b) Is the candidate closer than `dTest` in parameter space to any other candidate with higher LL?
 - (c) Is the candidate's LL further than `llTest` from a candidate with better LL, while its gradient norm is smaller than `gTest`?
5. Mark any candidates for which at least one test results in yes as inactive.
6. Go back to step 3, unless only one candidate is active, or the maximum number of iterations (`maxStages`) has been reached.

This function will write a CSV file to the working/output directory summarising progress. This file is called `modelName_searchStart.csv`.

Value

Invisibly returns a named vector of model parameters. These are the best values found.

<code>apollo_setRows</code>	<i>Sets specified rows to a given value</i>
-----------------------------	---

Description

Given a numeric object (scalar, vector, matrix or 3-dim array) sets a subset of rows to a given value.

Usage

```
apollo_setRows(v, r, val)
```

Arguments

<code>v</code>	Numeric scalar, vector, matrix or 3-dim array. Rows of this object will be replaced by <code>val</code> and
<code>r</code>	Boolean vector. As many elements as rows in <code>utilities</code> . TRUE for replacing that row, FALSE for not changing it.
<code>val</code>	Numeric scalar. Value to which the specified rows must be set to.

Value

The same argument `utilities` but with the rows where `r==TRUE` set to `val`.

<code>apollo_setWorkDir</code>	<i>Automatically sets working directory to active file directory</i>
--------------------------------	--

Description

This function only works in RStudio. If called outside RStudio, it prints a message to screen saying that it could not set the working directory.

Usage

```
apollo_setWorkDir()
```

Value

Invisibly returns TRUE if the working directory was set, and FALSE otherwise.

<code>apollo_sharesTest</code>	<i>Compares predicted and observed shares</i>
--------------------------------	---

Description

Comparing the shares predicted by the model with the shares observed in the data, and conducts statistical tests.

Usage

```
apollo_sharesTest(
  model,
  apollo_probabilities,
  apollo_inputs,
  sharesTest_settings
)
```

Arguments

- model** Model object. Estimated model object as returned by function [apollo_estimate](#).
- apollo_probabilities** Function. Returns probabilities of the model to be estimated. Must receive three arguments:
- **apollo_beta**: Named numeric vector. Names and values of model parameters.
 - **apollo_inputs**: List containing options of the model. See [apollo_validateInputs](#).
 - **functionality**: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL".
- apollo_inputs** List grouping most common inputs. Created by function [apollo_validateInputs](#).
- sharesTest_settings** List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional.
- **alternatives**: Named numeric vector. Names of alternatives and their corresponding value in choiceVar.
 - **choiceVar**: Numeric vector. Contains choices for all observations. It will usually be a column from the database. Values are defined in alternatives.
 - **modelComponent**: Name of model component. Set to model by default.
 - **newAlts**: Optional list describing the new alternatives to be used by `apollo_sharesTest`. This should have as many elements as new alternatives, with each entry being a matrix of 0-1 entries, with one row per observation, and one column per alternative used in the model.
 - **newAltsOnly**: Boolean. If TRUE, results will only be printed for the 'new' alternatives defined in `newAlts`, not the original alternatives used in the model. Set to FALSE by default.
 - **subsamples**: Named list of boolean vectors. Each element of the list defines whether a given observation belongs to a given subsample (e.g. by sociodemographics). If omitted, the full sample is used.

Details

This is an auxiliary function to help guide the definition of utility functions in a choice model. By comparing the predicted and observed shares of alternatives for different categories of the data, it is possible to identify what additional explanatory variables could improve the fit of the model.

Value

Invisibly returns a list of share-test output matrices, one for each subsample and, where applicable, for each set of newly defined alternatives.

apollo_sink	<i>Starts or stops writing output to a text file.</i>
-------------	---

Description

Starts or stops writing the output shown in the console to a file named "modelName_additional_output.txt".

Usage

```
apollo_sink(apollo_inputs = NULL)
```

Arguments

apollo_inputs List grouping most common inputs. Created by function [apollo_validateInputs](#). If not provided, it will be looked for in the global environment.

Details

After the first time this function is called, all output shown in the console will also be written to a text file called "modelName_additional_output.txt", where "modelName" is the modelName set inside apollo_control. The second time this function is called, it stops writing the console output to the file. The user should always call this function an even number of times to close the output file and prevent data loss. If any output sink is already open, this function closes the most recent sink.

Value

Invisibly returns NULL.

apollo_speedTest	<i>Measures evaluation time of a model</i>
------------------	--

Description

Measures the evaluation time of a model for different number of cores and draws.

Usage

```
apollo_speedTest(
  apollo_beta,
  apollo_fixed,
  apollo_probabilities,
  apollo_inputs,
  speedTest_settings = NA
)
```

Arguments

- apollo_beta** Named numeric vector. Names and values for parameters.
- apollo_fixed** Character vector. Names (as defined in `apollo_beta`) of parameters whose value should not change during estimation.
- apollo_probabilities**
Function. Returns probabilities of the model to be estimated. Must receive three arguments:
- `apollo_beta`: Named numeric vector. Names and values of model parameters.
 - `apollo_inputs`: List containing options of the model. See [apollo_validateInputs](#).
 - `functionality`: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL".
- apollo_inputs** List grouping most common inputs. Created by function [apollo_validateInputs](#).
- speedTest_settings**
List. Contains settings for this function. User input is required for all settings except those with a default or marked as optional.
- `nCoresTry`: Numeric vector. Number of threads to try. Default is from 1 to the detected number of cores.
 - `nDrawsTry`: Numeric vector. Number of inter and intra-person draws to try. Default value is `c(50, 100, 200)`. Ignored for models without mixing.
 - `nRep`: Numeric scalar. Number of times the likelihood is evaluated for each combination of threads and draws. Default is 10.

Details

This function evaluates the function `apollo_probabilities` several times using different number of threads (a.k.a. processor cores), and draws (if the model uses mixing). It then plots the estimation time for each combination. Estimation time grows at least linearly with number of draws, while time savings decrease with the number of threads. This function can help decide what number of draws and cores to use for estimation, though a high number of draws is always recommended. If the computer will be used for additional activities during estimation, no more than (machine number of cores - 1) should be used. Using more threads than cores available in the machine will lead to reduced performance. The use of additional cores come at the expense of additional memory usage. If R uses more memory than the physical RAM available, then significant slow-downs in processing time can be expected. This function can help avoid such pitfalls.

Value

Invisibly returns a list of two matrices: `timeTaken`, with the average time per evaluation for each combination of cores and draws, and `RAM`, with the RAM used. A graph is also plotted.

apollo_swissRouteChoiceData
Swiss route choice dataset.

Description

A stated choice dataset containing 3,492 route choices between two alternatives.

Usage

apollo_swissRouteChoiceData

Format

A data frame with 3,492 rows and 16 variables:

ID Numeric. Identification number of the individual.
choice Numeric. Choice indicator, 1 for alternative 1, and 2 for alternative 2.
tt1 Numeric. Travel time (in minutes) for alternative 1.
tc1 Numeric. Travel cost (in CHF) for alternative 1.
hw1 Numeric. Headway time (in minutes) for alternative 1.
ch1 Numeric. Number of interchanges for alternative 1.
tt2 Numeric. Travel time (in minutes) for alternative 2.
tc2 Numeric. Travel cost (in CHF) for alternative 2.
hw2 Numeric. Headway time (in minutes) for alternative 2.
ch2 Numeric. Number of interchanges for alternative 2.
hh_inc_abs Numeric. Household income (in CHF per annum).
car_availability Numeric. 1 if respondent has a car available, 0 otherwise.
commute Numeric. 1 if the purpose of the trip is commuting, 0 otherwise.
shopping Numeric. 1 if the purpose of the trip is shopping, 0 otherwise.
business Numeric. 1 if the purpose of the trip is business, 0 otherwise.
leisure Numeric. 1 if the purpose of the trip is leisure, 0 otherwise.

Details

This dataset is to be used for discrete choice modelling. Data comes from 388 individuals who participated in a stated choice (SC) survey, providing a total of 3,492 observations. Each choice scenario includes two rail alternatives described in terms of travel time, cost, headway and interchanges. Additional information on respondents is available. This dataset comes from the following publication: Axhausen, K.W., Hess, S., König, A., Abay, G., Bates, J.J. & Bierlaire, M. (2008), Income and distance elasticities of values of travel time savings: New Swiss results, Transport Policy, 15(3), pp. 173-185. <https://doi.org/10.1016/j.tranpol.2008.02.001>

Source

<https://www.ApolloChoiceModelling.com/>

apollo_timeUseData *Time use dataset.*

Description

A revealed preference dataset containing 2,826 full-day observations.

Usage

apollo_timeUseData

Format

A data frame with 2,826 rows and 21 variables:

indivID Numeric. Identification number of the individual.
day Numeric. Index of the day for each observation (day 1 was excluded).
date Numeric. Date in format `yyyymmdd`.
budget Numeric. Total amount of time registered during the day (in minutes).
t_a01 Numeric. Time spent dropping off or picking up other people (in minutes).
t_a02 Numeric. Time spent working (in minutes).
t_a03 Numeric. Time spent on educational activities (in minutes).
t_a04 Numeric. Time spent shopping (in minutes).
t_a05 Numeric. Time spent on private business (in minutes).
t_a06 Numeric. Time spent getting petrol (in minutes).
t_a07 Numeric. Time spent on social or leisure activities (in minutes).
t_a08 Numeric. Time spent on vacation or long (inter-city) travel (in minutes).
t_a09 Numeric. Time spent doing exercise (in minutes).
t_a10 Numeric. Time spent at home (in minutes).
t_a11 Numeric. Time spent travelling (everyday travelling) (in minutes).
t_a12 Numeric. Non-allocated time (in minutes).
female Numeric. 1 if the respondent is female, 0 otherwise.
age Numeric. Age of respondent (in years, approximate).
occ_full_time Numeric. 1 if the respondent works full time, 0 otherwise.
weekend Numeric. 1 if the current date is a weekend, 0 otherwise.

Details

This dataset is to be used for Multiple Discrete Continuous (MDC) modelling. Data comes from 447 individuals who provided activity diaries for a total of 2,826 days. Each observation summarizes the amount of time spent in each of twelve different activities. The dataset also includes characteristics of the participants. This dataset comes from the following publication: Calastri, C., Crastes dit Sourd, R. and Hess, S. (2020) We want it all: experiences from a survey seeking to capture social network structures, lifetime events and short-term travel and activity planning. *Transportation*, 47(1), pp. 175-201.

Source

<https://www.ApolloChoiceModelling.com/>

apollo_tobit	<i>Calculates density for a Tobit model (censored Normal)</i>
--------------	---

Description

Calculates density for a censored Normal distribution at a specific value with a specified mean and standard deviation and user provided bounds, and can also perform other operations based on the value of the functionality argument.

Usage

```
apollo_tobit(tobit_settings, functionality)
```

Arguments

`tobit_settings` List of arguments to the functions. It must contain the following.

- `componentName`: Character. Name given to model component. If not provided by the user, Apollo will set the name automatically according to the element in P to which the function output is directed.
- `lowerLimit`: Numeric scalar. Lower bound beyond which the density is 0. If not provided by the user, this will be set to -Inf.
- `mu`: Numeric scalar. Intercept of the linear model.
- `outcomeTobit`: Numeric vector. Dependent variable.
- `rows`: Boolean vector. Consideration of which rows to include. Length equal to the number of observations (nObs), with entries equal to TRUE for rows to include, and FALSE for rows to exclude. Default is "all", equivalent to `rep(TRUE, nObs)`.
- `sigma`: Numeric scalar. Standard deviation of the error component of the linear model.
- `upperLimit`: Numeric scalar. Upper bound beyond which the density is 0. If not provided by the user, this will be set to +Inf.
- `xTobit`: Numeric vector. Single explanatory variable.

`functionality` Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call `apollo_probabilities`, though the user can also call `apollo_probabilities` manually with a given functionality for testing/debugging. Possible values are:

- `"components"`: For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations.
- `"conditionals"`: For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws.

- "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "gradient": For model estimation, produces analytical gradients of the likelihood, where possible.
- "output": Prepares output for post-estimation reporting.
- "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws.
- "preprocess": Prepares likelihood functions for use in estimation.
- "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
- "report": Prepares output summarising model and choicest structure.
- "shares_LL": Produces overall model likelihood with constants only.
- "utilities": Returns utilities at provided parameter values.
- "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "zero_LL": Produces overall model likelihood with all parameters at zero.

Details

This function calculates the likelihood contribution for the linear model $\text{outcomeTobit} = \mu + x\text{Tobit} + \epsilon$, where ϵ is distributed $\text{Normal}(0, \sigma)$. Observations at or below `lowerLimit` and at or above `upperLimit` are treated as censored observations.

Value

The returned object depends on the value of argument `functionality` as follows.

- "components": Same as "estimate"
- "conditionals": Same as "estimate"
- "estimate": vector/matrix/array. Returns the likelihood for each observation.
- "gradient": List containing the likelihood and gradient of the model component.
- "output": Same as "estimate".
- "prediction": Predicted value at the observation level.
- "preprocess": Returns a list with pre-processed inputs, based on `tobit_settings`.
- "raw": Same as "estimate"
- "report": List containing captured diagnostic output for the dependent variable overview.
- "shares_LL": Not implemented. Returns a vector of NA with as many elements as observations.
- "utilities": Data frame containing individual IDs, observation numbers and the `xTobit` values, with excluded rows set to NA.
- "validate": Same as "estimate", but it also runs a set of tests to validate the function inputs.
- "zero_LL": Not implemented. Returns a vector of NA with as many elements as observations.

apollo_unconditionals *Returns unconditionals for models with random heterogeneity*

Description

Returns unconditionals for random parameters in model, both for continuous mixtures and latent class.

Usage

```
apollo_unconditionals(
  model,
  apollo_probabilities,
  apollo_inputs,
  obsLevel = NULL
)
```

Arguments

- | | |
|----------------------|--|
| model | Model object. Estimated model object as returned by function apollo_estimate . |
| apollo_probabilities | Function. Returns probabilities of the model to be estimated. Must receive three arguments: <ul style="list-style-type: none"> • apollo_beta: Named numeric vector. Names and values of model parameters. • apollo_inputs: List containing options of the model. See apollo_validateInputs. • functionality: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "hessian", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL". |
| apollo_inputs | List grouping most common inputs. Created by function apollo_validateInputs . |
| obsLevel | Logical. If TRUE, unconditionals are returned at the observation level rather than person level. This setting only applies to continuous mixture models and is set to TRUE by default only in the presence of intra-individual draws. Otherwise, the default is FALSE. |

Details

This function is only meant for use with models using continuous distributions or latent classes, or both at the same time.

Value

Depends on whether the model uses continuous mixtures or latent class.

- If the model contains a continuous mixture, it returns a list with one object per random coefficient. When using inter-individual draws only, each element will usually be a matrix with one row per individual and one column per draw. When using intra-individual draws, each element can be returned at the observation level as a three-dimensional array, with observations in the first dimension, inter-individual draws in the second dimension, and intra-individual draws in the third dimension. If `obsLevel=FALSE`, outputs are reduced to the individual level where applicable.
- If the model contains latent classes, it returns a list with as many elements as random coefficients in the model, plus one additional element containing the class allocation probabilities.
- If the model contains both continuous mixing and latent classes, a list with the two elements described above will be returned.

apollo_validate

Pre-process input for common models return

Description

Pre-process input for common models return

Usage

```
apollo_validate(inputs, modelType, functionality, apollo_inputs)
```

Arguments

- | | |
|---------------|---|
| inputs | List of settings |
| modelType | Character. Type of model, e.g. "mnl", "nl", "cnl", etc. |
| functionality | <p>Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call <code>apollo_probabilities</code>, though the user can also call <code>apollo_probabilities</code> manually with a given functionality for testing/debugging. Possible values are:</p> <ul style="list-style-type: none"> • "components": For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations. • "conditionals": For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws. • "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws. • "gradient": For model estimation, produces analytical gradients of the likelihood, where possible. • "output": Prepares output for post-estimation reporting. • "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws. • "preprocess": Prepares likelihood functions for use in estimation. |

- "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws.
- "report": Prepares output summarising model and choiceset structure.
- "shares_LL": Produces overall model likelihood with constants only.
- "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws.
- "zero_LL": Produces overall model likelihood with all parameters at zero.

apollo_inputs List of main inputs to the model estimation process. See [apollo_validateInputs](#).

Value

The returned object depends on the value of argument operation

apollo_validateControl

Validates apollo_control

Description

Validates the options controlling the running of the code `apollo_control` and sets default values for the omitted ones.

Usage

```
apollo_validateControl(database, apollo_control, silent = FALSE)
```

Arguments

database data.frame. Data used by model.

apollo_control List. Options controlling the running of the code. User input is required for all settings except those with a default or marked as optional.

- analyticGrad: Boolean. TRUE to use analytical gradients where available. Default is TRUE for non-HB models and FALSE for HB models.
- analyticHessian: Boolean. TRUE to use analytical Hessians where available. Default is FALSE.
- calculateLLC: Boolean. TRUE if user wants to calculate LL at constants (if applicable). - TRUE by default.
- cpp: Boolean. TRUE to use C++ implementations where available. Default is FALSE.
- debug: Boolean. TRUE to print additional diagnostic messages during validation. Default is FALSE.
- dropLoopExpansion: Boolean. TRUE to skip loop-expansion checks during preprocessing. Default is FALSE.

- dropRedefCheck: Boolean. TRUE to skip checks for variable redefinitions during preprocessing. Default is FALSE.
- HB: Boolean. TRUE if using RSGHB for Bayesian estimation. Default is FALSE.
- indivID: Character. Name of column in the database with each decision maker's ID.
- matrixMult: Boolean. TRUE to use matrix multiplication mode in compatible non-mixing models. Default is FALSE.
- memorySaver: Boolean. TRUE to reduce memory usage when calculating analytical gradients and hessian - FALSE by default.
- mixing: Boolean. TRUE for models that include random parameters. Default is FALSE, unless implied by other inputs before validation.
- modelDescr: Character. Description of the model. Used in output files. If omitted, a default description is used.
- modelName: Character. Name of the model. Used when saving the output to files.
- nCores: Numeric scalar. Number of cores to use in likelihood calculations. Default is 1.
- noDiagnostics: Boolean. TRUE if user does not wish model diagnostics to be printed - FALSE by default.
- noModification: Boolean. TRUE to avoid automatic modification of model code during preprocessing. Default is FALSE.
- noValidation: Boolean. TRUE if user does not wish model input to be validated before estimation - FALSE by default.
- outputDirectory: Character. Optional directory for outputs if different from the working directory. If omitted or empty, the current working directory is used.
- overridePanel: Boolean. TRUE to override panel-data likelihood multiplication where supported. Default is FALSE.
- panelData: Boolean. TRUE if there are multiple observations (i.e. rows) for each decision maker - Automatically set based on indivID by default.
- preventOverridePanel: Boolean. TRUE to prevent automatic panel override where supported. Default is FALSE.
- seed: Numeric scalar. Seed for random number generation. Default is 13.
- subMaxV: Boolean. TRUE to subtract the maximum utility before exponentiation in supported models for numerical stability. Default is TRUE.
- weights: Character. Name of column in database containing weights for estimation.
- workInLogs: Boolean. TRUE for increased numeric precision in models with panel data - FALSE by default.

silent

Boolean. If TRUE, no messages are printed to screen.

Details

This function should be run before running `apollo_validateData`.

Value

Validated version of `apollo_control`, with additional element called `panelData` set to `TRUE` for repeated choice data.

<code>apollo_validateData</code>	<i>Validates data</i>
----------------------------------	-----------------------

Description

Checks consistency of the database with `apollo_control`, sorts it by `indivID`, and adds an internal ID variable (`apollo_sequence`)

Usage

```
apollo_validateData(database, apollo_control, silent = FALSE)
```

Arguments

<code>database</code>	data.frame. Data used by model.
<code>apollo_control</code>	List. Options controlling the running of the code. See apollo_validateInputs .
<code>silent</code>	Boolean. <code>TRUE</code> to prevent the function from printing to the console. Default is <code>FALSE</code> .

Details

This function should be called after calling [apollo_validateControl](#). Observations are not sorted by this function. For panel data, all rows for the same individual must already be contiguous.

Value

data.frame. Validated version of database.

<code>apollo_validateHBControl</code>	<i>Validates the apollo_HB list of parameters</i>
---------------------------------------	---

Description

Validates the `apollo_HB` list of parameters and sets default values for the omitted ones.

Usage

```
apollo_validateHBControl(
  apollo_HB,
  apollo_beta,
  apollo_fixed,
  apollo_control,
  silent = FALSE
)
```

Arguments

- | | |
|--------------|--|
| apollo_HB | <p>List. Contains options for Bayesian estimation. See ?RSGHB::doHB for details. Parameters modelname, gVarNamesFixed, gVarNamesNormal, gDIST, svN and FC are automatically set based on the other arguments of this function. Other settings to include are the following.</p> <ul style="list-style-type: none"> • constraintsNorm: Character vector. Constraints for <i>random</i> coefficients in bayesian estimation. Constraints can be written as "b1>b2", "b1<b2", "b1>0", or "b1<0". • fixedA: Named numeric vector. Contains the names and fixed mean values of random parameters. For example, c(b1=0) fixes the mean of b1 to zero. • fixedD: Named numeric vector. Contains the names and fixed variance of random parameters. For example, c(b1=1) fixes the variance of b1 to zero. • gFULLCV: Boolean. Whether the full variance-covariance structure should be used for random parameters (TRUE by default). • gNCREP: Numeric. Number of burn-in iterations to use prior to convergence (default=10⁵). • gNEREP: Numeric. Number of iterations to keep for averaging after convergence has been reached (default=10⁵). • gINFOSKIP: Numeric. Number of iterations between printing/plotting information about the iteration process (default=250). • hbDist: <i>Mandatory</i> setting. A named character vector determining the distribution of each parameter to be estimated. Possible values are as follows. <ul style="list-style-type: none"> – "CN+": Positive censored normal. – "CN-": Negative censored normal. – "JSB": Johnson SB. – "LN+": Positive log-normal. – "LN-": Negative log-normal. – "N": Normal. – "NR": Fixed (as in non-random) parameter. • nodiagnostics: Boolean. Turn off pre-estimation diagnostics for RSGHB. Set to TRUE by default. |
| apollo_beta | Named numeric vector. Names and values for parameters. |
| apollo_fixed | Character vector. Names (as defined in apollo_beta) of parameters whose value should not change during estimation. value is constant throughout estimation). |

apollo_control List. Options controlling the running of the code. See [apollo_validateInputs](#).
 silent Boolean. TRUE to keep the function from printing to the console. Default is FALSE.

Details

This function is only necessary when using bayesian estimation.

Value

Validated apollo_HB

apollo_validateInputs *Prepares input for apollo_estimate*

Description

Searches the user work space (.GlobalEnv) for all necessary input to run apollo_estimate, and packs it in a single list.

Usage

```
apollo_validateInputs(  
  apollo_beta = NA,  
  apollo_fixed = NA,  
  database = NA,  
  apollo_control = NA,  
  apollo_HB = NA,  
  apollo_draws = NA,  
  apollo_randCoeff = NA,  
  apollo_lcPars = NA,  
  recycle = TRUE,  
  silent = FALSE  
)
```

Arguments

apollo_beta Named numeric vector. Names and values for parameters.
 apollo_fixed Character vector. Names (as defined in apollo_beta) of parameters whose value should not change during estimation.
 database data.frame. Data used by model.
 apollo_control List. Options controlling the running of the code. User input is required for all settings except those with a default or marked as optional.

- analyticGrad: Boolean. TRUE to use analytical gradients during parameter estimation, if they are available. FALSE to use numerical gradients. - TRUE by default.

- calculateLLC: Boolean. TRUE if user wants to calculate LL at constants (if applicable). - TRUE by default.
- HB: Boolean. TRUE if using RSGHB for Bayesian estimation of model.
- indivID: Character. Name of column in the database with each decision maker's ID.
- mixing: Boolean. TRUE for models that include random parameters.
- modelDescr: Character. Description of the model. Used in output files.
- modelName: Character. Name of the model. Used when saving the output to files.
- nCores: Numeric>0. Number of cores to use in calculations of the model likelihood.
- noDiagnostics: Boolean. TRUE if user does not wish model diagnostics to be printed - FALSE by default.
- noValidation: Boolean. TRUE if user does not wish model input to be validated before estimation - FALSE by default.
- outputDirectory: Character. Optional directory for outputs if different from working director - empty by default
- panelData: Boolean. TRUE if there are multiple observations (i.e. rows) for each decision maker - Automatically set based on indivID by default.
- seed: Numeric. Seed for random number generation.
- weights: Character. Name of column in database containing weights for estimation.
- workInLogs: Boolean. TRUE for increased numeric precision in models with panel data - FALSE by default.

apollo_HB

List. Contains options for Bayesian estimation. See ?RSGHB::doHB for details. Parameters modelName, gVarNamesFixed, gVarNamesNormal, gDIST, svN and FC are automatically set based on the other arguments of this function. Other settings to include are the following.

- constraintNorm: Character vector. Constraints for *random* coefficients in bayesian estimation. Constraints can be written as "b1>b2", "b1<b2", "b1>0", or "b1<0".
- fixedA: Named numeric vector. Contains the names and fixed mean values of random parameters. For example, c(b1=0) fixes the mean of b1 to zero.
- fixedD: Named numeric vector. Contains the names and fixed variance of random parameters. For example, c(b1=1) fixes the variance of b1 to zero.
- gNCREP: Numeric. Number of burn-in iterations to use prior to convergence (default=10⁵).
- gNEREP: Numeric. Number of iterations to keep for averaging after convergence has been reached (default=10⁵).
- gINFOSKIP: Numeric. Number of iterations between printing/plotting information about the iteration process (default=250).
- hbDist: *Mandatory* setting. A named character vector determining the distribution of each parameter to be estimated. Possible values are as follows.
 - "CN+": Positive censored normal.
 - "CN-": Negative censored normal.

	– "DNE": Parameter kept at its starting value (not estimated). – "JSB": Johnson SB. – "LN+": Positive log-normal. – "LN-": Negative log-normal. – "N": Normal. – "NR": Fixed (as in non-random) parameter.
apollo_draws	List of arguments describing the inter and intra individual draws. Required only if <code>apollo_control\$mixing = TRUE</code>. Unused elements can be omitted. • <code>interDrawsType</code>: Character. Type of inter-individual draws ('halton', 'mlhs', 'pmc', 'sobol' or the name of an object loaded in memory, see manual in www.ApolloChoiceModelling.com for details). • <code>interNDraws</code>: Numeric scalar (≥ 0). Number of inter-individual draws per individual. Should be set to 0 if not using them. • <code>interNormDraws</code>: Character vector. Names of normally distributed inter-individual draws. • <code>interUnifDraws</code>: Character vector. Names of uniform-distributed inter-individual draws. • <code>intraDrawsType</code>: Character. Type of intra-individual draws ('halton', 'mlhs', 'pmc', 'sobol' or the name of an object loaded in memory). • <code>intraNDraws</code>: Numeric scalar (≥ 0). Number of intra-individual draws per individual. Should be set to 0 if not using them. • <code>intraUnifDraws</code>: Character vector. Names of uniform-distributed intra-individual draws. • <code>intraNormDraws</code>: Character vector. Names of normally distributed intra-individual draws.
apollo_randCoeff	Function. Used with mixing models. Constructs the random parameters of a mixing model. Receives two arguments: • <code>apollo_beta</code>: Named numeric vector. Names and values of model parameters. • <code>apollo_inputs</code>: The output of this function (<code>apollo_validateInputs</code>).
apollo_lcPars	Function. Used with latent class models. Constructs a list of parameters for each latent class. Receives two arguments: • <code>apollo_beta</code>: Named numeric vector. Names and values of model parameters. • <code>apollo_inputs</code>: The output of this function (<code>apollo_validateInputs</code>).
recycle	Logical. If TRUE, an older version of <code>apollo_inputs</code> is looked for in the calling environment (parent frame), and any element in that old version created by the user is copied into the new <code>apollo_inputs</code> returned by this function. For <code>recycle=TRUE</code> to work, the old version of <code>apollo_inputs</code> must be named "apollo_inputs". If FALSE, nothing is copied from any older version of <code>apollo_inputs</code>. TRUE is the default.
silent	Logical. TRUE to keep the function from printing to the console. Default is FALSE.

Details

All arguments to this function are optional. If the function is called without arguments, then it will look in the user workspace (i.e. the global environment) for variables with the same name as its omitted arguments. We strongly recommend users to visit <https://www.ApolloChoiceModelling.com/> for examples on how to use Apollo. In the website, users will also find a detailed manual and a user-group for help and further reference.

Value

List grouping several required input for model estimation.

apollo_varcov	<i>Calculates variance-covariance matrix of an Apollo model</i>
---------------	---

Description

Calculates the Hessian, variance-covariance matrix and standard errors of an Apollo model as defined by its likelihood function and apollo_inputs list of settings. Performs automatic scaling for increased numeric stability.

Usage

```
apollo_varcov(apollo_beta, apollo_fixed, varcov_settings)
```

Arguments

- | | |
|-----------------|--|
| apollo_beta | Named numeric vector. Names and values of parameters at which to calculate the covariance matrix. Values must not be scaled , and they must include any fixed parameter. |
| apollo_fixed | Character vector. Names of fixed parameters. |
| varcov_settings | <p>List of settings defining the behaviour of this function. It must contain at least one of the following: apollo_logLike, apollo_grad or apollo_inputs together with apollo_probabilities.</p> <ul style="list-style-type: none"> • apollo_grad: Function to calculate the gradient of the model, as returned by apollo_makeGrad. • apollo_hessian: Function to calculate the Hessian of the model, as returned by apollo_makeHessian. • apollo_inputs: List grouping most common inputs. Created by function apollo_validateInputs. • apollo_logLike: Function to calculate the log-likelihood of the model, as returned by apollo_makeLogLike. • apollo_probabilities: apollo_probabilities Function. Returns probabilities of the model to be estimated. Must receive three arguments: <ul style="list-style-type: none"> – apollo_beta: Named numeric vector. Names and values of model parameters. |

- `apollo_inputs`: List containing options of the model. See [apollo_validateInputs](#).
- `functionality`: Character. Can be either "components", "conditionals", "estimate" (default), "gradient", "hessian", "output", "prediction", "preprocess", "raw", "report", "shares_LL", "validate" or "zero_LL".
- `BHHHhessian`: Matrix. Optional input, providing the BHHH matrix so it does not get recalculated.
- `hessianRoutine`: Character. Name of routine used to calculate the Hessian. Valid values are "analytic", "numDeriv", "maxLik" or "none" to avoid estimating the Hessian and covariance matrix. Default is "analytic".
- `numDeriv_method`: Character. Method used for numerical differentiation. Can be "Richardson" or "simple". Only used if analytical gradients are available. Default is "Richardson". See argument `method` in [grad](#) for more details.
- `numDeriv_settings`: List. Additional arguments to the Richardson method used by `numDeriv` to calculate the Hessian. Default is an empty list. See argument `method.args` in [grad](#) for more details.
- `scaleBeta`: Logical. If TRUE (default), parameters are scaled by their own value before calculating the Hessian to increase numerical stability. However, the output is de-scaled, so they are in the same scale as the `apollo_beta` argument.

Details

It calculates the Hessian, variance-covariance, and standard errors at `apollo_beta` values of an estimated model. At least one of the following settings must be provided (ordered by speed of computation): `apollo_grad`, `apollo_logLik`, or (`apollo_probabilities` and `apollo_inputs`). If more than one is provided, then the priority is: `apollo_grad`, `apollo_logLik`, (`apollo_probabilities` and `apollo_inputs`).

Value

List with the following elements

- `apollo_beta`: Named numerical vector. Parameter estimates (`model$estimate`, not scaled).
- `corrmat`: Numerical matrix. Correlation between parameter estimates.
- `eigValue`: Numeric scalar. Largest Hessian eigenvalue, if available and real.
- `hessian`: Numerical matrix. Hessian of the model at parameter estimates (`model$estimate`).
- `hessianEigenValue`: Numeric vector. Eigenvalues of the Hessian, if the Hessian was calculated.
- `hessianMethodsAttempted`: Character vector. Names of methods attempted to calculate the Hessian.
- `hessianMethodUsed`: Character. Name of method used to calculate the Hessian.
- `hessianScaling`: Named numeric vector. Scales used on the parameters to calculate the Hessian (non-fixed only).
- `robcorrmat`: Numerical matrix. Robust correlation between parameter estimates.
- `robse`: Named numerical vector. Robust standard errors of parameter estimates.

- robvarcov: Numerical matrix. Robust variance-covariance matrix.
- se: Named numerical vector. Standard errors of parameter estimates.
- varcov: Numerical matrix. Variance-covariance matrix.

apollo_varList	<i>Lists variable names and definitions used inside a function</i>
----------------	--

Description

Returns a list containing the names and definitions of variables in f, apollo_randCoeff and apollo_lcPars

Usage

apollo_varList(f, apollo_inputs)

Arguments

- | | |
|---------------|--|
| f | Function. Usually apollo_probabilities. The function is parsed to identify variable definitions. |
| apollo_inputs | List grouping most common inputs. Created by function apollo_validateInputs . Returns a list containing the names and definitions of variables defined inside f, apollo_randCoeff and apollo_lcPars. |

Details

It looks for variable definitions inside f, apollo_randCoeff, and apollo_lcPars. It returns them in a list.

apollo_weighting	<i>Applies weights</i>
------------------	------------------------

Description

Applies weights to individual observations in likelihood function.

Usage

apollo_weighting(P, apollo_inputs, functionality)

Arguments

P	List of vectors, matrices or 3-dim arrays. Likelihood of the model components.
apollo_inputs	List grouping most common inputs. Created by function apollo_validateInputs .
functionality	Character. Setting instructing Apollo what processing to apply to the likelihood function. This is in general controlled by the functions that call <code>apollo_probabilities</code>, though the user can also call <code>apollo_probabilities</code> manually with a given functionality for testing/debugging. Possible values are: • "components": For further processing/debugging, produces likelihood for each model component (if multiple components are present), at the level of individual draws and observations. • "conditionals": For conditionals, produces likelihood of the full model, at the level of individual inter-individual draws. • "estimate": For model estimation, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws. • "gradient": For model estimation, produces analytical gradients of the likelihood, where possible. • "output": Prepares output for post-estimation reporting. • "prediction": For model prediction, produces probabilities for individual alternatives and individual model components (if multiple components are present) at the level of an observation, after averaging across draws. • "preprocess": Prepares likelihood functions for use in estimation. • "raw": For debugging, produces probabilities of all alternatives and individual model components at the level of an observation, at the level of individual draws. • "report": Prepares output summarising model and choiceset structure. • "shares_LL": Produces overall model likelihood with constants only. • "utilities": Returns utilities at provided parameter values. • "validate": Validates model specification, produces likelihood of the full model, at the level of individual decision-makers, after averaging across draws. • "zero_LL": Produces overall model likelihood with all parameters at zero.

Value

The model likelihood or prediction object after applying individual-specific weights. For likelihood-based functionality, weights are applied by raising likelihood contributions to the relevant weight, or by multiplying log-likelihoods when `workInLogs=TRUE`. For prediction functionality, probabilities are multiplied by the relevant weights.

apollo_writeF12	<i>Writes an F12 file</i>
-----------------	---------------------------

Description

Writes an F12 file (ALogit format) with the results of a model estimation.

Usage

```
apollo_writeF12(model, truncateCoeffNames = TRUE)
```

Arguments

model	Model object. Estimated model object as returned by function apollo_estimate .
truncateCoeffNames	Boolean. TRUE to truncate parameter names to 10 characters. TRUE by default.

Value

Invisibly returns TRUE after writing the F12 file.

apollo_writeTheta	<i>Writes the vector [beta,ll] to a file called modelname_iterations.csv</i>
-------------------	--

Description

Writes the vector [beta,ll] to a file called modelname_iterations.csv

Usage

```
apollo_writeTheta(
  beta,
  ll,
  modelName,
  scaling = NULL,
  outDir = NULL,
  apollo_beta = NULL
)
```

Arguments

beta	vector of parameters to be written (including fixed ones).
ll	scalar representing the log-likelihood of the whole model.
modelName	Character. Name of the model.
scaling	Numeric vector of scales applied to beta
outDir	Scalar character. Name of output directory
apollo_beta	Named numeric vector of starting values.

Value

Nothing.

aux_validateRows	<i>Validates and expands rows if necessary.</i>
------------------	---

Description

Validates and expands rows if necessary.

Usage

```
aux_validateRows(rows, componentName = NULL, apollo_inputs = NULL)
```

Arguments

rows	Boolean vector. Consideration of which rows to include. Length equal to the number of observations (nObs), with entries equal to TRUE for rows to include, and FALSE for rows to exclude. Default is "all", equivalent to rep(TRUE, nObs). Set to "all" by default if omitted.
componentName	Character. Name given to model component. If not provided by the user, Apollo will set the name automatically according to the element in P to which the function output is directed.
apollo_inputs	List grouping most common inputs. Created by function apollo_validateInputs .

print.apollo	<i>Prints brief summary of Apollo model</i>
--------------	---

Description

Receives an estimated model object and prints a brief summary using the generic print function.

Usage

```
## S3 method for class 'apollo'
print(x, ...)
```

Arguments

x	Model object. Estimated model object as returned by function apollo_estimate .
...	further arguments passed to or from other methods.

Value

nothing.

summary.apollo	<i>Prints summary of Apollo model</i>
----------------	---------------------------------------

Description

Receives an estimated model object and prints a summary using the generic summary function.

Usage

```
## S3 method for class 'apollo'
summary(object, ..., pTwoSided = FALSE)
```

Arguments

object	Model object. Estimated model object as returned by function apollo_estimate .
...	further arguments passed to or from other methods.
pTwoSided	Logical. Should two-sided p-values be printed instead of one-sided p-values. FALSE by default. #' @return nothing.

Index

* datasets

- apollo_drugChoiceData, 28
- apollo_modeChoiceData, 79
- apollo_swissRouteChoiceData, 117
- apollo_timeUseData, 118
- .onAttach, 4
- apollo_addCovariance, 5
- apollo_attach, 5, 24
- apollo_avgInterDraws, 6, 19
- apollo_avgIntraDraws, 8, 19
- apollo_basTest, 9
- apollo_bootstrap, 10
- apollo_checkArguments, 12
- apollo_choiceAnalysis, 13
- apollo_classAlloc, 14
- apollo_cnl, 15
- apollo_combineModels, 17
- apollo_combineResults, 20
- apollo_compareInputs, 21
- apollo_conditionals, 21
- apollo_deltaMethod, 22
- apollo_detach, 5, 24
- apollo_dft, 24
- apollo_diagnostics, 27
- apollo_drugChoiceData, 28
- apollo_dVdB, 29
- apollo_dVdBOld, 30
- apollo_el, 30
- apollo_emdc, 32
- apollo_emdc1, 34
- apollo_emdc2, 35
- apollo_estimate, 5, 9–11, 21, 22, 37, 40, 42, 54, 55, 57, 60, 65, 73, 75, 76, 81, 93, 98, 108, 114, 121, 134, 136
- apollo_estimateHB, 39
- apollo_expandLoop, 40
- apollo_firstRow, 41
- apollo_fitsTest, 42
- apollo_fmnl, 43

- apollo_fnl, 45
- apollo_initialise, 47
- apollo_insertComponentName, 48
- apollo_insertFunc, 48
- apollo_insertOLList, 49
- apollo_insertRows, 50
- apollo_insertRRMQuotes, 50
- apollo_insertScaling, 51
- apollo_keepRows, 51
- apollo_lc, 52
- apollo_lcConditionals, 53
- apollo_lcEM, 54
- apollo_lcEM_new, 56
- apollo_lcUnconditionals, 57
- apollo_llCalc, 58
- apollo_loadModel, 59, 109
- apollo_longToWide, 59
- apollo_lrTest, 60
- apollo_makeCluster, 61
- apollo_makeDraws, 62
- apollo_makeGrad, 63, 130
- apollo_makeHessian, 64, 130
- apollo_makeLogLike, 63, 64, 64, 130
- apollo_mdcev, 66
- apollo_mdcev2, 68
- apollo_mdcnev, 70
- apollo_mixConditionals, 73
- apollo_mixEM, 74
- apollo_mixUnconditionals, 75
- apollo_mlhs, 76
- apollo_mnl, 77
- apollo_modeChoiceData, 79
- apollo_modelOutput, 39, 81
- apollo_modifyUserDefFunc, 82
- apollo_n1, 83
- apollo_normalDensity, 86
- apollo_ol, 88
- apollo_op, 90
- apollo_outOfSample, 92

apollo_ownModel, 94
apollo_panelProd, 19, 96
apollo_prediction, 98
apollo_preEstimate, 99
apollo_prepareProb, 19, 101
apollo_preprocess, 103
apollo_print, 104
apollo_readBeta, 105
apollo_rrm, 106
apollo_saveOutput, 39, 108
apollo_searchStart, 110
apollo_setRows, 112
apollo_setWorkDir, 113
apollo_sharesTest, 113
apollo_sink, 115
apollo_speedTest, 115
apollo_swissRouteChoiceData, 117
apollo_timeUseData, 118
apollo_tobit, 119
apollo_unconditionals, 121
apollo_validate, 122
apollo_validateControl, 123, 125
apollo_validateData, 41, 125
apollo_validateHBControl, 125
apollo_validateInputs, 5, 6, 8, 10, 13, 15,
18, 21, 24, 27, 29, 30, 37, 40–42, 52,
54–58, 61, 62, 65, 73, 74, 76, 83, 93,
96, 98, 100, 102, 104, 111, 114–116,
121, 123, 125, 127, 127, 130–133,
135
apollo_varcov, 130
apollo_varList, 132
apollo_weighting, 132
apollo_writeF12, 134
apollo_writeTheta, 134
aux_validateRows, 135

bgw_mle, 37, 100

grad, 38, 101, 131

maxBFGS, 38, 101
maxBHHH, 38, 101
maxLik, 38, 100
maxNM, 38, 101

on.exit, 5

print.apollo, 136

summary.apollo, 136