

Package ‘datasusr’

September 25, 2026

Type Package

Title Fast Access to Brazilian Public Health Data from 'DATASUS'

Version 0.1.1

Description Provides fast, in-memory reading of 'DATASUS' 'DBC' files using native 'C' code, along with a catalog of public health data sources, 'FTP' file discovery, caching downloads, and a high-level `datasus_fetch()` function that lists, downloads, and reads files in a single call. Bundles the 'blast' decompressor from 'zlib' contrib/blast to decode 'PKWare DCL' compressed 'DBC' files and parses 'DBF' records directly for efficient import into tibbles. See the 'DATASUS' file transfer site <https://datasus.saude.gov.br> and Adler (2003) <https://github.com/madler/zlib/tree/master/contrib/blast> for details on the underlying data and compression format.

License MIT + file LICENSE

URL <https://strategicprojects.github.io/datasusr/>,
<https://github.com/StrategicProjects/datasusr>

BugReports <https://github.com/StrategicProjects/datasusr/issues>

Encoding UTF-8

Language en-US

Depends R (>= 4.1.0)

Imports cli, curl (>= 5.0.0), dplyr (>= 1.1.0), purrr, rlang (>= 1.0.0), stringr, tibble, tidyr

Suggests knitr, pkgdown, rmarkdown, testthat (>= 3.1.7)

VignetteBuilder knitr

Config/testthat/edition 3

NeedsCompilation yes

SystemRequirements C99

Config/roxygen2/version 8.0.0

Author Andre Leite [aut, cre] (ORCID: <<https://orcid.org/0000-0002-4718-9766>>),
Marcos Wasiliew [aut] (ORCID: <<https://orcid.org/0009-0004-4694-3159>>),
Hugo Vasconcelos [aut] (ORCID: <<https://orcid.org/0000-0001-6249-0920>>),
Carlos Amorim [aut] (ORCID: <<https://orcid.org/0000-0001-6315-8305>>),
Diogo Bezerra [aut] (ORCID: <<https://orcid.org/0000-0002-1216-8674>>),
Mark Adler [ctb, cph] (Author of bundled blast.c and blast.h from zlib
contrib/blast)

Maintainer Andre Leite <leite@castlab.org>

Repository CRAN

Date/Publication 2026-09-25 19:00:02 UTC

Contents

datasus_build_path	2
datasus_cache_clear	3
datasus_cache_dir	4
datasus_cache_info	4
datasus_cache_list	5
datasus_cache_prune	5
datasus_docs_url	6
datasus_download	7
datasus_fetch	8
datasus_file_types	10
datasus_ftp_ls	11
datasus_get_territory	11
datasus_list_files	13
datasus_modalities	14
datasus_sources	15
datasus_ufs	15
format_bytes	16
read_datasus_dbc	16
Index	19

datasus_build_path	<i>Build DATASUS FTP paths from filters</i>
--------------------	---

Description

Builds candidate FTP directories for a given source and file type. For SIH/SIA, the function selects historical vs. current trees by year/month. For SIM and SINASC, preliminary trees are included when requested.

Usage

```
datasus_build_path(  
  source,  
  file_type,  
  year = NULL,  
  month = NULL,  
  include_prelim = TRUE  
)
```

Arguments

source	Source code (e.g. "SIHSUS").
file_type	File type code (e.g. "RD").
year	Integer vector of years.
month	Integer vector of months.
include_prelim	Logical. Include preliminary trees when available (default TRUE).

Value

A tibble with columns source, file_type, period, and path.

Examples

```
datasus_build_path(source = "SIHSUS", file_type = "RD", year = 2024, month = 1)
```

datasus_cache_clear	<i>Clear cached DATASUS files</i>
---------------------	-----------------------------------

Description

Removes files from the cache directory. By default all cached files are removed; pass a character vector to files to remove specific paths.

Usage

```
datasus_cache_clear(cache_dir = NULL, files = NULL, verbose = TRUE)
```

Arguments

cache_dir	Optional cache directory.
files	Optional character vector of file paths to remove. When NULL, all cached files are removed.
verbose	Logical. Emit progress messages (default TRUE).

Value

A tibble with columns path and removed.

datasus_cache_dir	<i>Resolve the datasusr cache directory</i>
-------------------	---

Description

Returns the active cache directory path. Checks, in order: the `cache_dir` argument, the `DATASUSR_CACHE_DIR` environment variable, the `datasusr.cache_dir` option, and finally a session-scoped subdirectory of `tempdir()`. To opt in to a persistent cache across sessions, set the `DATASUSR_CACHE_DIR` environment variable, the `datasusr.cache_dir` option, or pass `cache_dir` explicitly (for example, `tools::R_user_dir("datasusr", "cache")`).

Usage

```
datasus_cache_dir(cache_dir = NULL)
```

Arguments

`cache_dir` Optional cache directory supplied by the caller.

Value

A single path string.

Examples

```
datasus_cache_dir()
```

datasus_cache_info	<i>Summarise the datasusr cache</i>
--------------------	-------------------------------------

Description

Returns a one-row tibble summarising the current cache: directory path, file count, total size, and modification time range.

Usage

```
datasus_cache_info(cache_dir = NULL, verbose = TRUE)
```

Arguments

`cache_dir` Optional cache directory.
`verbose` Logical. Print a summary to the console (default TRUE).

Value

A tibble with one row.

Examples

```
datasus_cache_info()
```

datasus_cache_list	<i>List cached DATASUS files</i>
--------------------	----------------------------------

Description

Returns a tibble describing every file currently stored in the cache directory.

Usage

```
datasus_cache_list(cache_dir = NULL)
```

Arguments

cache_dir Optional cache directory.

Value

A tibble with columns path, file_name, size_bytes, modified_time, and accessed_time.

Examples

```
datasus_cache_list()
```

datasus_cache_prune	<i>Prune the datasusr cache</i>
---------------------	---------------------------------

Description

Selectively removes cached files based on age and/or total size. Older and least-recently-accessed files are removed first.

Usage

```
datasus_cache_prune(
  cache_dir = NULL,
  max_size_bytes = NULL,
  older_than_days = NULL,
  verbose = TRUE
)
```

Arguments

cache_dir	Optional cache directory.
max_size_bytes	Maximum total cache size in bytes. When exceeded, the least-recently-accessed files are removed until the cache fits.
older_than_days	Age threshold in days. Files with a modification time older than this are removed.
verbose	Logical. Emit progress messages (default TRUE).

Value

A tibble with columns path, removed, and reason.

datasus_docs_url	<i>Get FTP URLs for DATASUS documentation</i>
------------------	---

Description

Returns the FTP URLs where documentation files (layouts, data dictionaries) for each source system can be found. Use [datasus_ftp_ls\(\)](#) to list the actual files at each URL.

Usage

```
datasus_docs_url(source = NULL)
```

Arguments

source	Optional source code to filter (e.g. "SIHSUS"). When NULL, all known documentation paths are returned.
--------	--

Value

A tibble with columns source and docs_url.

Examples

```
datasus_docs_url()
datasus_docs_url("CNES")

tryCatch({
  # List documentation files for CNES (network required).
  docs <- datasus_docs_url("CNES")
  datasus_ftp_ls(docs$docs_url[[1]], verbose = FALSE)
}, error = function(e) message("FTP unavailable: ", conditionMessage(e)))
```

datasus_download	<i>Download DATASUS files</i>
------------------	-------------------------------

Description

Downloads one or many DATASUS files. When `use_cache = TRUE`, files that already exist in the cache directory are reused instead of re-downloaded.

Usage

```
datasus_download(  
  files = NULL,  
  ...,  
  dest_dir = NULL,  
  overwrite = FALSE,  
  timeout = Inf,  
  use_cache = TRUE,  
  cache_dir = NULL,  
  refresh = FALSE,  
  verbose = TRUE  
)
```

Arguments

<code>files</code>	A tibble returned by <code>datasus_list_files()</code> . When <code>NULL</code> , additional filters are forwarded to <code>datasus_list_files()</code> .
<code>...</code>	Filters passed to <code>datasus_list_files()</code> when <code>files</code> is <code>NULL</code> .
<code>dest_dir</code>	Optional destination directory. When <code>NULL</code> , the package cache directory is used if <code>use_cache = TRUE</code> ; otherwise a fresh subdirectory of <code>tempdir()</code> is used.
<code>overwrite</code>	Logical. Re-download files even when they already exist at the destination (default <code>FALSE</code>).
<code>timeout</code>	Optional hard cap, in seconds, on the total transfer time of each file (default <code>Inf</code> , no cap). Stalled transfers are always detected independently: the connection must be established within 60 seconds and a transfer is aborted when it stays below 1 byte/s for 120 seconds. When <code>files</code> is <code>NULL</code> , a finite timeout is also used for the FTP listing (otherwise 120 seconds).
<code>use_cache</code>	Logical. Store and reuse downloads in the cache directory (default <code>TRUE</code>).
<code>cache_dir</code>	Optional cache directory.
<code>refresh</code>	Logical. Force re-download even when a cached file exists (default <code>FALSE</code>).
<code>verbose</code>	Logical. Emit progress messages (default <code>TRUE</code>).

Details

Files are stored as `<dir>/<source>/<file_type>/<period>/<file_name>`, where `<dir>` is `dest_dir` or the cache directory and `<period>` is the FTP tree the file came from ("current", "historical" or "prelim"). Keeping the period in the path means a preliminary file never shadows the final file of the same name. When files lacks the `source/file_type/period` columns, the corresponding path components are omitted.

Each file is first written to a temporary `<file_name>.part` file and only renamed to its final name when the transfer succeeds, so an interrupted or failed download never becomes a cache hit.

Value

The files tibble with additional columns: `local_file` (path to the local copy), `downloaded` (TRUE when the file was transferred in this call), `success` (TRUE when `local_file` is available, either downloaded or reused from the cache), `error` (the failure message, NA on success) and `cache_dir`.

Examples

```
tryCatch({
  files <- datasus_list_files(
    source = "SIHSUS", file_type = "RD",
    year = 2024, month = 1, uf = "AC",
    verbose = FALSE
  )
  downloads <- datasus_download(
    files,
    cache_dir = tempdir(),
    verbose = FALSE
  )
}, error = function(e) message("FTP unavailable: ", conditionMessage(e)))
```

datasus_fetch

Fetch DATASUS data in one step

Description

A convenience wrapper that lists, downloads, and reads DATASUS files in a single call. Particularly useful for interactive / exploratory work.

Usage

```
datasus_fetch(
  source,
  file_type,
  year = NULL,
  month = NULL,
  uf = NULL,
  ...,
```

```

    bind = TRUE,
    include_prelim = TRUE,
    timeout = Inf,
    use_cache = TRUE,
    cache_dir = NULL,
    refresh = FALSE,
    overwrite = FALSE,
    verbose = TRUE
  )

```

Arguments

source	Character vector of source codes.
file_type	Character vector of file type codes.
year	Integer vector of years.
month	Integer vector of months (required for monthly sources).
uf	Character vector of UF codes (required for UF-scoped sources).
...	Additional arguments forwarded to read_datasus_dbc() (e.g. select, col_types, parse_dates).
bind	Logical. When TRUE (the default), all files are row-bound into a single tibble. When FALSE, a list of tibbles is returned.
include_prelim	Logical. Include preliminary data trees (default TRUE).
timeout	Optional hard cap, in seconds, on each file transfer (default Inf, no cap); see datasus_download() . A finite value is also used for the FTP listing (otherwise 120 seconds).
use_cache	Logical. Reuse cached downloads (default TRUE).
cache_dir	Optional cache directory.
refresh	Logical. Force re-download even when a cached file exists (default FALSE). Forwarded to datasus_download() .
overwrite	Logical. Re-download files that already exist at the destination (default FALSE). Forwarded to datasus_download() .
verbose	Logical. Emit progress messages (default TRUE).

Details

Files that fail to download are skipped with a warning; if every download fails, an error is raised.

When the same file is available both as a final release and as a preliminary one (a SIM D0 year that has just been consolidated, or a SINAN file requested together with its SINAN_P alias), only the final version is read, so rows are not duplicated. A final file that could not be confirmed on the FTP does not suppress a preliminary copy that is known to exist. Use [datasus_list_files\(\)](#) and [datasus_download\(\)](#) directly to work with both copies.

Value

A tibble (when bind = TRUE) or a named list of tibbles. List names are the file names; when the same file name comes from more than one FTP tree they are prefixed with the period (e.g. "prelim/DOPE2022.dbc").

Examples

```
tryCatch({
  # Fetch a small SIHSUS slice into tempdir() (network required).
  df <- datasus_fetch(
    source      = "SIHSUS",
    file_type   = "RD",
    year        = 2024,
    month       = 1,
    uf          = "AC",
    select      = c("uf_zi", "ano_cmpt", "munic_res", "val_tot"),
    cache_dir   = tempdir(),
    verbose     = FALSE
  )
}, error = function(e) message("FTP unavailable: ", conditionMessage(e)))
```

datasus_file_types	<i>List DATASUS file types</i>
--------------------	--------------------------------

Description

Returns the internal catalog of file types. Optionally filtered by source and/or file type codes.

Usage

```
datasus_file_types(source = NULL, file_type = NULL)
```

Arguments

source	Optional character vector of source codes (e.g. "SIHSUS").
file_type	Optional character vector of file type codes (e.g. "RD").

Value

A tibble.

Examples

```
datasus_file_types()
datasus_file_types(source = "SIHSUS")
datasus_file_types(source = "CNES", file_type = "ST")
```

datasus_ftp_ls	<i>List files and directories from the DATASUS FTP</i>
----------------	--

Description

Fetches a raw directory listing from a DATASUS FTP path.

Usage

```
datasus_ftp_ls(path, timeout = 120, ftp_use_epsv = FALSE, verbose = TRUE)
```

Arguments

path	FTP path or full URL. Relative paths are prefixed with the DATASUS public FTP root.
timeout	Timeout in seconds (default 120).
ftp_use_epsv	Logical. Passed to curl (default FALSE).
verbose	Logical. Emit progress messages (default TRUE).

Value

A tibble with columns ftp_url and entry.

Examples

```
tryCatch(
  datasus_ftp_ls("SIHSUS/200801_/Dados/", verbose = FALSE),
  error = function(e) message("FTP unavailable: ", conditionMessage(e))
)
```

datasus_get_territory	<i>Download DATASUS territorial tables</i>
-----------------------	--

Description

Downloads and reads tables from the DATASUS territorial data section. The DATASUS FTP publishes a ZIP archive per year containing reference tables for municipalities, health regions, and other geographic divisions used by SUS, in CSV, DBF, and TXT formats.

Usage

```
datasus_get_territory(
  table = "tb_municip",
  year = NULL,
  format = "csv",
  cache_dir = NULL,
  verbose = TRUE
)
```

Arguments

<code>table</code>	Name of the table to read. Common values: "tb_municip" (municipalities), "tb_uf" (states), "tb_regsaud" (health regions), "tb_macsaud" (macro health regions), "tb_regiao" (geographic regions), "tb_micibge" (IBGE micro-regions), "tb_regmetr" (metropolitan regions), "tb_dsei" (indigenous health districts). Relationship tables start with "rl_" (e.g. "rl_municip_regsaud").
<code>year</code>	Year of the territorial table. Defaults to the current year. Use <code>datasus_ftp_ls("ftp://ftp.datasus.gov.br/territorio/anos/2014/territorio_2014.zip")</code> to see available years.
<code>format</code>	File format to extract from the ZIP: "csv" (default) or "dbf".
<code>cache_dir</code>	Optional cache directory.
<code>verbose</code>	Logical. Emit progress messages (default TRUE).

Value

A tibble with column names in snake_case.

Examples

```
tryCatch({
  # Download territorial tables into tempdir() (network required).
  municipios <- datasus_get_territory(
    "tb_municip",
    cache_dir = tempdir(),
    verbose = FALSE
  )
  ufs <- datasus_get_territory(
    "tb_uf",
    cache_dir = tempdir(),
    verbose = FALSE
  )
}, error = function(e) message("FTP unavailable: ", conditionMessage(e)))
```

datasus_list_files *List available DATASUS files*

Description

Builds candidate file names from the internal catalog and, optionally, validates them against the DATASUS FTP.

Usage

```
datasus_list_files(
  source,
  file_type,
  year = NULL,
  month = NULL,
  uf = NULL,
  include_prelim = TRUE,
  check_exists = TRUE,
  timeout = 120,
  ftp_use_epsv = FALSE,
  verbose = TRUE
)
```

Arguments

source	Character vector of source codes.
file_type	Character vector of file type codes.
year	Integer vector of years.
month	Integer vector of months (required for monthly sources).
uf	Character vector of UF codes (required for UF-scoped sources).
include_prelim	Logical. Include preliminary data trees (default TRUE).
check_exists	Logical. Query the FTP and keep only files that exist (default TRUE). File names are matched case-insensitively and the spelling used on the FTP is returned. If an FTP directory cannot be listed (e.g. a timeout), a warning is emitted and the candidate files of that directory are kept with exists = NA. Setting to FALSE skips FTP access and returns all candidate files (with exists = NA).
timeout	Timeout in seconds for FTP requests (default 120).
ftp_use_epsv	Logical. Passed to curl (default FALSE).
verbose	Logical. Emit progress messages (default TRUE).

Details

year must be between 1979 and next year, month between 1 and 12, and uf must be one of [datasus_ufs\(\)](#); invalid values raise an error before any network access. For SIM "D0" and SINASC "DN", uf = NULL means all UFs.

Value

A tibble with one row per file, including its FTP URL and metadata.

Examples

```
tryCatch(  
  datasus_list_files(  
    source = "SIHSUS",  
    file_type = "RD",  
    year = 2024,  
    month = 1,  
    uf = c("PE", "PB"),  
    verbose = FALSE  
  ),  
  error = function(e) message("FTP unavailable: ", conditionMessage(e))  
)
```

datasus_modalities	<i>List DATASUS modalities</i>
--------------------	--------------------------------

Description

Returns the available DATASUS data modalities (data, documentation, programs, etc.).

Usage

```
datasus_modalities()
```

Value

A tibble.

Examples

```
datasus_modalities()
```

datasus_sources	<i>List DATASUS data sources</i>
-----------------	----------------------------------

Description

Returns the internal catalog of DATASUS sources available in datasusr.

Usage

```
datasus_sources()
```

Value

A tibble with one row per source, including its code, description, default scope, and flags for monthly and UF support.

Examples

```
datasus_sources()
```

datasus_ufs	<i>List UF codes used by DATASUS downloads</i>
-------------	--

Description

Returns a character vector of the 27 Brazilian state abbreviations accepted by DATASUS file naming conventions.

Usage

```
datasus_ufs()
```

Value

A character vector of length 27.

Examples

```
datasus_ufs()
```

format_bytes	<i>Format byte sizes for display</i>
--------------	--------------------------------------

Description

Converts raw byte counts into human-readable strings (e.g. "1.23 MB").

Usage

```
format_bytes(x)
```

Arguments

`x` Numeric vector of byte sizes.

Value

A character vector with formatted sizes.

Examples

```
format_bytes(c(1024, 1048576, NA))
```

read_datasus_dbc	<i>Read DATASUS DBC files</i>
------------------	-------------------------------

Description

Reads a DATASUS .dbc file directly into R using native C code for PKWare DCL decompression and DBF parsing. The function always returns a tibble and is designed to work well with the tidyverse.

Usage

```
read_datasus_dbc(
  file,
  select = NULL,
  n_max = Inf,
  trim_ws = TRUE,
  encoding = "latin1",
  guess_types = TRUE,
  col_types = NULL,
  parse_dates = FALSE,
  clean_names = TRUE,
  verbose = TRUE
)
```

Arguments

file	Path to a .dbc or .dbf file. Both compressed (DBC) and uncompressed (DBF) formats are accepted.
select	Optional character vector of column names to keep. When NULL (the default), all columns are returned. Names are matched case-insensitively, so both "UF_ZI" and "uf_zi" work. Names that match no column trigger a warning.
n_max	Maximum number of rows to read. Defaults to Inf (all rows). Records flagged as deleted in the DBF are always skipped and do not count towards n_max.
trim_ws	Logical. Trim leading/trailing whitespace from character fields (default TRUE). Numeric, date and logical fields are always trimmed before parsing, regardless of this setting.
encoding	Encoding of the DBF character fields. One of "latin1" (the default for DATASUS files; the aliases "latin-1" and "ISO-8859-1" are accepted), "UTF-8" or "unknown" (native encoding). Matching is case-insensitive; any other value is an error.
guess_types	Logical. Inspect numeric fields to distinguish integer-like columns from double columns (default TRUE). Disable for faster reads when precise types are not needed.
col_types	Optional named character vector of explicit column types. Supported values: "character", "integer", "double", "logical", "date". Names are matched case-insensitively against the original DBF field names.
parse_dates	Logical. If TRUE, DBF date fields (D type) are returned as Date. Character fields are only parsed as dates when explicitly listed in col_types (default FALSE).
clean_names	Logical. If TRUE (the default), column names are converted to snake_case (lowercase with underscores). The original DATASUS names are uppercase (e.g. UF_ZI becomes uf_zi).
verbose	Logical. Emit progress messages (default TRUE).

Value

A tibble.

Examples

```
# The example downloads a small DATASUS file into tempdir() and reads it.
# Skipped automatically if the FTP is unreachable.
tmp <- file.path(tempdir(), "RDAC2401.dbc")
url <- paste0(
  "ftp://ftp.datasus.gov.br/dissemin/publicos/SIHSUS/200801_/Dados/",
  "RDAC2401.dbc"
)
ok <- tryCatch(
  {
    utils::download.file(url, tmp, mode = "wb", quiet = TRUE)
    TRUE
  },
  error = function(e) FALSE,
```

```
    warning = function(w) FALSE
  )

  if (ok) {
    # Basic read (column names in snake_case by default)
    x <- read_datasus_dbc(tmp, verbose = FALSE)

    # Select works with either case
    x <- read_datasus_dbc(
      tmp,
      select = c("uf_zi", "ano_cmpt", "val_tot"),
      verbose = FALSE
    )

    # Keep original uppercase names
    x <- read_datasus_dbc(tmp, clean_names = FALSE, verbose = FALSE)

    unlink(tmp)
  }
}
```

Index

`datasus_build_path`, [2](#)
`datasus_cache_clear`, [3](#)
`datasus_cache_dir`, [4](#)
`datasus_cache_info`, [4](#)
`datasus_cache_list`, [5](#)
`datasus_cache_prune`, [5](#)
`datasus_docs_url`, [6](#)
`datasus_download`, [7](#)
`datasus_download()`, [9](#)
`datasus_fetch`, [8](#)
`datasus_file_types`, [10](#)
`datasus_ftp_ls`, [11](#)
`datasus_ftp_ls()`, [6](#)
`datasus_get_territory`, [11](#)
`datasus_list_files`, [13](#)
`datasus_list_files()`, [7](#), [9](#)
`datasus_modalities`, [14](#)
`datasus_sources`, [15](#)
`datasus_ufs`, [15](#)
`datasus_ufs()`, [13](#)

`format_bytes`, [16](#)

`read_datasus_dbc`, [16](#)
`read_datasus_dbc()`, [9](#)

`tempdir()`, [4](#), [7](#)