

Package ‘gge’

September 3, 2026

Type Package

Title Genotype Plus Genotype-by-Environment Biplots

Version 1.11

Description Create biplots for GGE (genotype plus genotype-by-environment) and GGB (genotype plus genotype-by-block-of-environments) models. See Laffont et al. (2013) <[doi:10.2135/cropsci2013.03.0178](https://doi.org/10.2135/cropsci2013.03.0178)>.

License MIT + file LICENSE

URL <https://kwstat.github.io/gge/>, <http://kwstat.github.io/gge/>

BugReports <https://github.com/kwstat/gge/issues>

Imports nipals, dplyr, rlang, tibble, tidyr

Suggests agridat, knitr, lattice, rgl, rmarkdown, testthat

VignetteBuilder knitr

Encoding UTF-8

Config/roxygen2/version 8.1.0

NeedsCompilation no

Author Kevin Wright [aut, cre, cph] (ORCID: <<https://orcid.org/0000-0002-0617-8673>>),
Jean-Louis Laffont [aut]

Maintainer Kevin Wright <kw.stat@gmail.com>

Depends R (>= 4.1.0)

Repository CRAN

Date/Publication 2026-09-03 19:30:02 UTC

Contents

gge	2
RedGrayBlue	6
Index	7

`gge`*GGE and GGB biplots*

Description

Fit a GGE (genotype + genotype * environment) model and display the results.

Usage

```
gge(x, ...)  
  
## S3 method for class 'data.frame'  
gge(x, formula, gen.group = NULL, env.group = NULL, ggb = FALSE, ...)  
  
## S3 method for class 'matrix'  
gge(  
  x,  
  center = TRUE,  
  scale = TRUE,  
  gen.group = NULL,  
  env.group = NULL,  
  ggb = FALSE,  
  comps = c(1, 2),  
  method = "svd",  
  ...  
)  
  
## S3 method for class 'gge'  
plot(x, main = substitute(x), ...)  
  
## S3 method for class 'gge'  
biplot(  
  x,  
  main = substitute(x),  
  subtitle = "",  
  xlab = "auto",  
  ylab = "auto",  
  cex.gen = 0.6,  
  cex.env = 0.5,  
  col.gen = "darkgreen",  
  col.env = "orange3",  
  pch.gen = 1,  
  lab.env = TRUE,  
  comps = 1:2,  
  flip = "auto",  
  origin = "auto",  
  res.vec = TRUE,
```

```

    hull = FALSE,
    AEC = FALSE,
    zoom.gen = 1,
    zoom.env = 1,
    ...
)

biplot3d(x, ...)

## S3 method for class 'gge'
biplot3d(
  x,
  cex.gen = 0.6,
  cex.env = 0.5,
  col.gen = "darkgreen",
  col.env = "orange3",
  comps = 1:3,
  lab.env = TRUE,
  res.vec = TRUE,
  zoom.gen = 1,
  ...
)

```

Arguments

<code>x</code>	A matrix or data.frame.
<code>...</code>	Other arguments (e.g. <code>maxiter</code> , <code>gramschmidt</code>)
<code>formula</code>	A formula
<code>gen.group</code>	genotype group
<code>env.group</code>	env group
<code>ggb</code>	If TRUE, fit a GGB biplot model.
<code>center</code>	If TRUE, center values for each environment
<code>scale</code>	If TRUE, scale values for each environment
<code>comps</code>	Principal components to use for the biplot. Default <code>c(1,2)</code> .
<code>method</code>	method used to find principal component directions. Either "svd" or "nipals".
<code>main</code>	Title, by default the name of the data. Use NULL to suppress the title.
<code>subtitle</code>	Subtitle to put in front of options. Use NULL to suppress the subtitle.
<code>xlab</code>	Label along axis. Default "auto" shows percent of variation explained. Use NULL to suppress.
<code>ylab</code>	Label along axis. Default "auto" shows percent of variation explained. Use NULL to suppress.
<code>cex.gen</code>	Character expansion for genotype labels, default 0.6. Use 0 to omit genotype labels.
<code>cex.env</code>	Character expansion for environment labels/symbols. Use <code>lab.env=FALSE</code> to omit labels.

col.gen	Color for genotype labels. May be a single color for all genotypes, or a vector of colors for each genotype.
col.env	Color for environments. May be a single color for all environments, or a vector of colors for each environment.
pch.gen	Plot character for genotypes
lab.env	Label environments if TRUE.
flip	If "auto" then each axis is flipped so that the genotype ordinate is positively correlated with genotype means. Can also be a vector like c(TRUE,FALSE) for manual control.
origin	If "auto", the plotting window is centered on genotypes, otherwise the origin is at the middle of the window.
res.vec	If TRUE, for each group, draw residual vectors from the mean of the locs to the individual locs.
hull	If TRUE, show a which-won-where polygon.
AEC	If TRUE, draw the Average Environment Coordination (AEC) biplot. Environment vectors are suppressed. Instead, a vector is drawn to the average of all environment coordinates (the "average environment"), the AEC axis is extended as a line through the origin across the plot, and concentric circles are drawn centred on the average environment point as a guide to stability (distance from the average environment).
zoom.gen	Zoom factor for manual control of genotype xlim,ylim The default is 1. Values less than 1 may be useful if genotype names are long.
zoom.env	Zoom factor for manual control of environment xlim,ylim. The default is 1. Values less than 1 may be useful if environment names are long. Not used for 3D biplots.
data	Data frame

Details

If there is replication in G*E, then the replications are averaged together before constructing the biplot.

The singular value decomposition of x is used to calculate the principal components for the biplot. Missing values are NOT allowed.

The argument `method` can be either 'svd' for complete-data or 'nipals' for missing-data.

Value

A list of class `gge` containing:

<code>x</code>	The filled-in data
<code>x.orig</code>	The original data
<code>genCoord</code>	genotype coordinates
<code>locCoord</code>	loc coordinates
<code>blockCoord</code>	block coordinates

gen.group	If not NULL, use this to specify a column of the data.frame to classify genotypes into groups.
env.group	If not NULL, use this to specify a column of the data.frame to classify environments into groups.
ggb	If TRUE, create a GGB biplot
genMeans	genotype means
mosdat	mosaic plot data
R2	variation explained by each PC
center	Data centered?
scale	Data scaled?
method	Method used to calculate principal components.
pctMiss	Percent of x that is missing values
maxPCs	Maximum number of PCs

Author(s)

Kevin Wright, Jean-Louis Laffont

Jean-Louis Laffont, Kevin Wright

References

Jean-Louis Laffont, Kevin Wright and Mohamed Hanafi (2013). Genotype + Genotype x Block of Environments (GGB) Biplots. *Crop Science*, 53, 2332-2341. doi:10.2135/cropsci2013.03.0178.

Kroonenberg, Pieter M. (1997). *Introduction to Biplots for GxE Tables*, Research Report 51, Centre for Statistics, The University of Queensland, Brisbane, Australia. <https://three-mode.leidenuniv.nl/document/biplot.pdf>

Yan, W. and Kang, M.S. (2003). *GGE Biplot Analysis*. CRC Press.

Examples

```
# Example 1. Data is a data.frame in 'matrix' format
B <- matrix(c(50, 67, 90, 98, 120,
              55, 71, 93, 102, 129,
              65, 76, 95, 105, 134,
              50, 80, 102, 130, 138,
              60, 82, 97, 135, 151,
              65, 89, 106, 137, 153,
              75, 95, 117, 133, 155), ncol=5, byrow=TRUE)
rownames(B) <- c("G1", "G2", "G3", "G4", "G5", "G6", "G7")
colnames(B) <- c("E1", "E2", "E3", "E4", "E5")

library(gge)
m1 = gge(B)
plot(m1)
biplot(m1, main="Example biplot")
# biplot3d(m1)
```

```
if(require(agridat)){  
  # crossa.wheat biplot  
  
  # Specify env.group as column in data frame  
  data(crossa.wheat)  
  dat2 <- crossa.wheat  
  m2 <- gge(dat2, yield~gen*loc, env.group=locgroup, scale=FALSE)  
  plot(m2)  
  biplot(m2, lab.env=TRUE, main="crossa.wheat")  
  # biplot3d(m2)  
}
```

RedGrayBlue

Function to create a Red-Gray-Blue palette

Description

A function to create a Red-Gray-Blue palette.

Usage

```
RedGrayBlue(n)
```

Arguments

n	Number of colors to create
---	----------------------------

Details

Using gray instead of white allows missing values to appear as white (actually, transparent).

Value

A vector of n colors.

Author(s)

Kevin Wright

Examples

```
pie(rep(1,11), col=RedGrayBlue(11))  
title("RedGrayBlue(11)")
```

Index

`biplot.gge (gge)`, [2](#)

`biplot3d (gge)`, [2](#)

`gge`, [2](#)

`gge-package (gge)`, [2](#)

`gge.data.frame (gge)`, [2](#)

`gge.matrix (gge)`, [2](#)

`plot.gge (gge)`, [2](#)

`RedGrayBlue`, [6](#)