

Package ‘oosse’

July 17, 2026

Type Package

Title Out-of-Sample R^2 with Standard Error Estimation

Version 1.0.12

Maintainer Stijn Hawinkel <stijn.hawinkel@psb.ugent.be>

Description Estimates out-of-sample R^2 through bootstrap or cross-validation as a measure of predictive performance. In addition, a standard error for this point estimate is provided, and confidence intervals are constructed.

License GPL-2

Encoding UTF-8

Imports stats, BiocParallel, Matrix, methods, doParallel, Rdpack

RdMacros Rdpack

Suggests knitr, rmarkdown, testthat, randomForest, glmnet

LazyData true

VignetteBuilder knitr

Depends R (>= 4.2.0)

BugReports <https://github.com/sthawinke/oosse/issues>

Config/roxygen2/version 8.0.0

NeedsCompilation no

Author Stijn Hawinkel [cre, aut] (ORCID:
<<https://orcid.org/0000-0002-4501-5180>>)

Repository CRAN

Date/Publication 2026-07-17 14:10:02 UTC

Contents

boot632	2
boot632multiple	3
bootOob	3
Brassica	4

buildConfInt	5
checkFitFun	6
estCorMSEMST	6
estMSE	7
formatSeconds	8
getSEsNested	9
isPD	9
processOob	10
R2oosse	10
RsquaredSE	12
simpleCV	13

Index	14
--------------	-----------

boot632	<i>The .632 bootstrap estimation of the MSE</i>
---------	---

Description

The .632 bootstrap estimation of the MSE

Usage

boot632(y, x, id, fitFun, predFun)

Arguments

y	The vector of outcome values
x	The matrix of predictors
id	the sample indices resampled with replacement
fitFun	The function for fitting the prediction model
predFun	The function for evaluating the prediction model

Details

The implementation follows (Efron and Tibshirani 1997)

Value

The MSE estimate

References

Efron B, Tibshirani R (1997). “Improvements on cross-validation: The 632+ bootstrap method.” *J. Am. Stat. Assoc.*, **92**(438), 548 - 560.

See Also

[estMSE](#) [bootOob](#)

boot632multiple	<i>Repeated .632 bootstraps</i>
-----------------	---------------------------------

Description

Repeated .632 bootstraps

Usage

```
boot632multiple(nBootstraps, y, ...)
```

Arguments

nBootstraps	The number of .632 bootstraps
y	The vector of outcome values
...	passed onto boot632

Value

The estimated MSE

bootOob	<i>The oob bootstrap (smooths leave-one-out CV)</i>
---------	---

Description

The oob bootstrap (smooths leave-one-out CV)

Usage

```
bootOob(y, x, id, fitFun, predFun)
```

Arguments

y	The vector of outcome values
x	The matrix of predictors
id	sample indices sampled with replacement
fitFun	The function for fitting the prediction model
predFun	The function for evaluating the prediction model

Details

The implementation follows (Efron and Tibshirani 1997)

Value

matrix of errors and inclusion times

References

Efron B, Tibshirani R (1997). "Improvements on cross-validation: The 632+ bootstrap method." *J. Am. Stat. Assoc.*, **92**(438), 548 - 560.

See Also

[estMSE boot632](#)

Brassica

Gene expression and phenotypes of Brassica napus (rapeseed) plants

Description

RNA-sequencing data of genetically identical Brassica napus plants in autumn, with 5 phenotypes next spring, as published by De Meyer S, Cruz DF, De Swaef T, Lootens P, De Block J, Bird K, Sprenger H, Van de Voorde M, Hawinkel S, Van Hautegeem T, Inzé D, Nelissen H, Roldán-Ruiz I, Maere S (2023). "Predicting yield of individual field-grown rapeseed plants from rosette-stage leaf gene expression." *PLoS Comput. Biol.*, **19**(5), 1 - 42..

Usage

Brassica

Format

A list with two components Expr and Pheno

Expr Matrix with Rlog values of 1000 most expressed genes

Pheno Data frame with 5 phenotypes and x and y coordinates of the plants in the field

Source

[doi:10.1101/2022.10.21.513275](https://doi.org/10.1101/2022.10.21.513275)

References

(De Meyer et al. 2023)

buildConfInt	<i>Calculate a confidence interval for R², MSE and MST</i>
--------------	---

Description

Calculate a confidence interval for R², MSE and MST

Usage

```
buildConfInt(oosseObj, what = c("R2", "MSE", "MST"), conf = 0.95)
```

Arguments

oosseObj	The result of the R2oosse call
what	For which property should the ci be found: R ² (default), MSE or MST
conf	the confidence level required

Details

The upper bound of the interval is truncated at 1 for the R² and the lower bound at 0 for the MSE

The confidence intervals for R² and the MSE are based on standard errors and normal approximations. The confidence interval for the MST is based on the chi-squared distribution as in equation (16) of (Harding et al. 2014), but with inflation by a factor (n+1)/n. All quantities are out-of-sample.

Value

A vector of length 2 with lower and upper bound of the confidence interval

References

Harding B, Tremblay C, Cousineau D (2014). "Standard errors: A review and evaluation of standard error estimators using Monte Carlo simulations." *The Quantitative Methods for Psychology*, **10**(2), 107 - 123.

See Also

[R2oosse](#)

Examples

```
data(Brassica)
fitFunLM = function(y, x){lm.fit(y = y, x = cbind(1, x))}
predFunLM = function(mod, x) {cbind(1,x) %*% mod$coef}
R2lm = R2oosse(y = Brassica$Pheno$Leaf_8_width, x = Brassica$Expr[, 1:10],
fitFun = fitFunLM, predFun = predFunLM, nFolds = 10)
buildConfInt(R2lm)
buildConfInt(R2lm, what = "MSE")
buildConfInt(R2lm, what = "MST")
```

checkFitFun	<i>Check whether supplied prediction function meets the requirements</i>
-------------	--

Description

Check whether supplied prediction function meets the requirements

Usage

```
checkFitFun(fitFun, reqArgs = c("y", "x"))
```

Arguments

fitFun	The prediction function, or its name as character string
reqArgs	The vector of required arguments

Value

Throws an error when requirements not met, otherwise returns the function

estCorMSEMST	<i>Estimate correlation between MSE and MST estimators</i>
--------------	--

Description

Estimate correlation between MSE and MST estimators

Usage

```
estCorMSEMST(  
  y,  
  x,  
  fitFun,  
  predFun,  
  methodMSE,  
  methodCor,  
  nBootstrapsCor,  
  nFolds,  
  nBootstraps  
)
```

Arguments

y	The vector of outcome values
x	The matrix of predictors
fitFun	The function for fitting the prediction model
predFun	The function for evaluating the prediction model
methodMSE	The method to estimate the MSE, either "CV" for cross-validation or "bootstrap" for .632 bootstrap
methodCor	The method to estimate the correlation between MSE and MST estimators, either "nonparametric" or "jackknife"
nBootstrapsCor	The number of bootstraps to estimate the correlation
nFolds	The number of outer folds for cross-validation
nBootstraps	The number of .632 bootstraps

Value

the estimated correlation

estMSE	<i>Estimate MSE and its standard error</i>
--------	--

Description

Estimate MSE and its standard error

Usage

```
estMSE(
  y,
  x,
  fitFun,
  predFun,
  methodMSE,
  nFolds,
  nInnerFolds,
  cvReps,
  nBootstraps
)
```

Arguments

y	The vector of outcome values
x	The matrix of predictors
fitFun	The function for fitting the prediction model
predFun	The function for evaluating the prediction model

methodMSE	The method to estimate the MSE, either "CV" for cross-validation or "bootstrap" for .632 bootstrap
nFolds	The number of outer folds for cross-validation
nInnerFolds	The number of inner cross-validation folds
cvReps	The number of repeats for the cross-validation
nBootstraps	The number of .632 bootstraps

Details

The nested cross-validation scheme follows (Bates et al. 2023), the .632 bootstrap is implemented as in (Efron and Tibshirani 1997)

Value

A vector with MSE estimate and its standard error

References

Bates S, Hastie T, Tibshirani R (2023). “Cross-validation: What does it estimate and how well does it do it?” *J. Am. Stat. Assoc.*, **118**(ja), 1 - 22. doi:10.1080/01621459.2023.2197686. <https://doi.org/10.1080/01621459.2023.2197686>

Efron B, Tibshirani R (1997). “Improvements on cross-validation: The 632+ bootstrap method.” *J. Am. Stat. Assoc.*, **92**(438), 548 - 560.

formatSeconds	<i>Format seconds into human readable format</i>
---------------	--

Description

Format seconds into human readable format

Usage

```
formatSeconds(seconds, digits = 2)
```

Arguments

seconds	The number of seconds to be formatted
digits	the number of digits for rounding

Value

A character vector expressing time in human readable format

getSEsNested	<i>Calculate standard error on MSE from nested CV results</i>
--------------	---

Description

Calculate standard error on MSE from nested CV results

Usage

```
getSEsNested(cvSplitReps, nOuterFolds, n)
```

Arguments

cvSplitReps	The list of outer and inner CV results
nOuterFolds	The number of outer folds
n	The sample size

Details

The calculation of the standard error of the MSE as proposed by (Bates et al. 2023)

Value

The estimate of the MSE and its standard error

References

Bates S, Hastie T, Tibshirani R (2023). “Cross-validation: What does it estimate and how well does it do it?” *J. Am. Stat. Assoc.*, **118**(ja), 1 - 22. doi:10.1080/01621459.2023.2197686. <https://doi.org/10.1080/01621459.2023.2197686>

See Also

[estMSE](#)

isPD	<i>Helper function to check if matrix is positive definite</i>
------	--

Description

Helper function to check if matrix is positive definite

Usage

```
isPD(mat, tol = 1e-06)
```

Arguments

mat	The matrix
tol	The tolerance

Value

A boolean indicating positive definiteness

processOob	<i>Process the out-of-bag bootstraps to get to standard errors following Efron 1997</i>
------------	---

Description

Process the out-of-bag bootstraps to get to standard errors following Efron 1997

Usage

```
processOob(x)
```

Arguments

x	the list with out=of=bag bootstrap results
---	--

Value

out-of-bag MSE estimate and standard error

R2oosse	<i>Estimate out-of-sample R^2 and its standard error</i>
---------	---

Description

Estimate out-of-sample R^2 and its standard error

Usage

```
R2oosse(
  y,
  x,
  fitFun,
  predFun,
  methodMSE = c("CV", "bootstrap"),
  methodCor = c("nonparametric", "jackknife"),
  printTimeEstimate = TRUE,
```

```

    nFolds = 10L,
    nInnerFolds = nFolds - 1L,
    cvReps = 200L,
    nBootstraps = 200L,
    nBootstrapsCor = 50L,
    ...
  )

```

Arguments

<code>y</code>	The vector of outcome values
<code>x</code>	The matrix of predictors
<code>fitFun</code>	The function for fitting the prediction model
<code>predFun</code>	The function for evaluating the prediction model
<code>methodMSE</code>	The method to estimate the MSE, either "CV" for cross-validation or "bootstrap" for .632 bootstrap
<code>methodCor</code>	The method to estimate the correlation between MSE and MST estimators, either "nonparametric" or "jackknife"
<code>printTimeEstimate</code>	A boolean, should an estimate of the running time be printed?
<code>nFolds</code>	The number of outer folds for cross-validation
<code>nInnerFolds</code>	The number of inner cross-validation folds
<code>cvReps</code>	The number of repeats for the cross-validation
<code>nBootstraps</code>	The number of .632 bootstraps
<code>nBootstrapsCor</code>	The number of bootstraps to estimate the correlation
<code>...</code>	passed onto <code>fitFun</code> and <code>predFun</code>

Details

Implements the calculation of the R^2 and its standard error by (Hawinkel et al. 2023). Multithreading is used as provided by the `BiocParallel` or `doParallel` packages, A rough estimate of expected computation time is printed when `printTimeEstimate` is true, but this is purely indicative. The options to estimate the mean squared error (MSE) are cross-validation (Bates et al. 2023) or the .632 bootstrap (Efron and Tibshirani 1997).

Value

A list with components

<code>R2</code>	Estimate of the R^2 with standard error
<code>MSE</code>	Estimate of the MSE with standard error
<code>MST</code>	Estimate of the MST with standard error
<code>corMSEMST</code>	Estimated correlation between MSE and MST estimators
<code>params</code>	List of parameters used
<code>fullModel</code>	The model trained on the entire dataset using <code>fitFun</code>
<code>n</code>	The sample size of the training data

References

Bates S, Hastie T, Tibshirani R (2023). “Cross-validation: What does it estimate and how well does it do it?” *J. Am. Stat. Assoc.*, **118**(ja), 1 - 22. doi:10.1080/01621459.2023.2197686. <https://doi.org/10.1080/01621459.2023.2197686>.

Efron B, Tibshirani R (1997). “Improvements on cross-validation: The 632+ bootstrap method.” *J. Am. Stat. Assoc.*, **92**(438), 548 - 560.

Hawinkel S, Waegeman W, Maere S (2023). “Out-of-sample R2: Estimation and inference.” *Am. Stat.*, 1 - 16. doi:10.1080/00031305.2023.2216252. <https://doi.org/10.1080/00031305.2023.2216252>.

See Also

[buildConfInt](#)

Examples

```
data(Brassica)
#Linear model
fitFunLM = function(y, x){lm.fit(y = y, x = cbind(1, x))}
predFunLM = function(mod, x) {cbind(1,x) %*% mod$coef}
y = Brassica$Pheno$Leaf_8_width
R2lm = R2oosse(y = Brassica$Pheno$Leaf_8_width, x = Brassica$Expr[, 1:10],
fitFun = fitFunLM, predFun = predFunLM, nFolds = 10)
```

RsquaredSE	<i>Calculate out-of-sample R² and its standard error based on MSE estimates</i>
------------	--

Description

Calculate out-of-sample R² and its standard error based on MSE estimates

Usage

```
RsquaredSE(MSE, margVar, SEMSE, n, corMSEMST)
```

Arguments

MSE	An estimate of the mean squared error (MSE)
margVar	The marginal variance of the outcome, not scaled by (n+1)/n
SEMSE	The standard error on the MSE estimate
n	the sample size of the training data
corMSEMST	The correlation between MSE and marginal variance estimates

Details

This function is exported to allow the user to estimate the MSE and its standard error and the correlation between MSE and MST estimators himself. The marginal variance is scaled by $(n+1)/n$ to the out-of-sample MST, so the user does not need to do this.

Value

A vector with the R^2 and standard error estimates

References

Hawinkel S, Waegeman W, Maere S (2023). “Out-of-sample R^2 : Estimation and inference.” *Am. Stat.*, 1 - 16. doi:[10.1080/00031305.2023.2216252](https://doi.org/10.1080/00031305.2023.2216252). <https://doi.org/10.1080/00031305.2023.2216252>.

See Also

[R2oosse](#)

Examples

```
#The out-of-sample  $R^2$  calculated using externally provided estimates
RsquaredSE(MSE = 3, margVar = 4, SEMSE = 0.4, n = 50, corMSEMST = 0.75)
```

simpleCV

Perform simple CV, and return the MSE estimate

Description

Perform simple CV, and return the MSE estimate

Usage

```
simpleCV(y, x, fitFun, predFun, nFolds)
```

Arguments

y	The vector of outcome values
x	The matrix of predictors
fitFun	The function for fitting the prediction model
predFun	The function for evaluating the prediction model
nFolds	The number of outer folds for cross-validation

Value

The MSE estimate

Index

* datasets

Brassica, [4](#)

boot632, [2](#), [4](#)

boot632multiple, [3](#)

bootOob, [2](#), [3](#)

Brassica, [4](#)

buildConfInt, [5](#), [12](#)

checkFitFun, [6](#)

estCorMSEMST, [6](#)

estMSE, [2](#), [4](#), [7](#), [9](#)

formatSeconds, [8](#)

getSEsNested, [9](#)

isPD, [9](#)

processOob, [10](#)

R2oosse, [5](#), [10](#), [13](#)

RsquaredSE, [12](#)

simpleCV, [13](#)