

Package ‘rxode2ll’

September 15, 2026

Version 2.0.18

Title Log-Likelihood Functions for 'rxode2'

Maintainer Matthew L. Fidler <matthew.fidler@gmail.com>

Depends R (>= 4.0.0)

Suggests covr, testthat (>= 3.0.0)

Imports Rcpp (>= 1.0.8), checkmate

Description Provides the log-likelihoods with gradients from 'stan' (Carpenter et al (2015), <[doi:10.48550/arXiv.1509.07164](https://doi.org/10.48550/arXiv.1509.07164)>) needed for generalized log-likelihood estimation in 'nlmixr2' (Fidler et al (2019) <[doi:10.1002/psp4.12445](https://doi.org/10.1002/psp4.12445)>). This is split of to reduce computational burden of recompiling 'rxode2' (Wang, Hallow and James (2016) <[doi:10.1002/psp4.12052](https://doi.org/10.1002/psp4.12052)>) which runs the 'nlmixr2' models during estimation.

BugReports <https://github.com/nlmixr2/rxode2ll/issues/>

NeedsCompilation yes

License GPL (>= 3)

URL <https://nlmixr2.github.io/rxode2ll/>,
<https://github.com/nlmixr2/rxode2ll/>

Biarch true

LinkingTo Rcpp (>= 1.0.8), RcppEigen (>= 0.3.3.9.2), StanHeaders (>= 2.26), BH (>= 1.78.0.0), RcppParallel

Encoding UTF-8

Language en-US

Config/testthat/edition 3

Config/roxygen2/version 8.1.0

Author Matthew L. Fidler [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-8538-6691>>)

Repository CRAN

Date/Publication 2026-09-15 11:30:02 UTC

Contents

.rxode2llPtr	2
llikBeta	3
llikBetaProportion	4
llikBinom	4
llikCauchy	5
llikChisq	6
llikDblExp	7
llikExp	7
llikF	8
llikFrechet	9
llikGamma	9
llikGeom	10
llikGumbel	11
llikInvChisq	11
llikInvGamma	12
llikLnorm	12
llikLogis	13
llikNbinom	13
llikNbinomMu	14
llikNorm	15
llikPareto	15
llikParetoType2	16
llikPois	17
llikRayleigh	17
llikScaledInvChisq	18
llikT	18
llikUnif	19
llikWeibull	20
Index	21

.rxode2llPtr	<i>External pointers to rxode2ll's log-likelihood functions</i>
--------------	---

Description

Hands a consumer package the addresses of every rxLlik* function and its exact derivatives, so it can call them from C/C++ without an ABI dependency on this package.

Usage

.rxode2llPtr()

Details

`R_GetCCallable()` is not sufficient for that. It drops the link-time dependency, but the consumer still compiles in a typedef'd signature and caches a raw address: updating `rxode2ll` then requires the consumer to be rebuilt, and reloading `rxode2ll` leaves the cached pointers dangling. This is the same external-pointer handshake `rxode2`, `nlmixr2est`, `RcppTrust` and `n1qn1` already use, where the consumer re-reads the list in its own `.onLoad()` and therefore picks up an updated `rxode2ll` instead of baking one in.

The returned list is APPEND-ONLY and its order is fixed; see `inst/include/rxode2llPtrs.h`, which is the matching consumer header.

Value

list of external pointers, in the order documented in `rxode2llPtrs.h`

Examples

```
length(.rxode2llPtr())
```

<code>llikBeta</code>	<i>Calculate the log likelihood of the binomial function (and its derivatives)</i>
-----------------------	--

Description

Calculate the log likelihood of the binomial function (and its derivatives)

Usage

```
llikBeta(x, shape1, shape2, full = FALSE)
```

Arguments

<code>x</code>	Observation
<code>shape1, shape2</code>	non-negative parameters of the Beta distribution.
<code>full</code>	Add the data frame showing <code>x</code> , <code>mean</code> , <code>sd</code> as well as the <code>fx</code> and derivatives

Value

data frame with `fx` for the log pdf value of with `dShape1` and `dShape2` that has the derivatives with respect to the parameters at the observation time-point

Author(s)

Matthew L. Fidler

Examples

```
x <- seq(1e-4, 1 - 1e-4, length.out = 21)

llikBeta(x, 0.5, 0.5)

llikBeta(x, 1, 3, TRUE)
```

llikBetaProportion	<i>log likelihood of the BetaProportion distribution and its derivatives (from stan)</i>
--------------------	--

Description

log likelihood of the BetaProportion distribution and its derivatives (from stan)

Usage

```
llikBetaProportion(x, mu, kappa, full = FALSE)
```

Arguments

x	Observation
mu	distribution parameter
kappa	distribution parameter
full	return the input parameters alongside the result

Value

data frame with fx and the derivative of each parameter

llikBinom	<i>Calculate the log likelihood of the binomial function (and its derivatives)</i>
-----------	--

Description

Calculate the log likelihood of the binomial function (and its derivatives)

Usage

```
llikBinom(x, size, prob, full = FALSE)
```

Arguments

x	Number of successes
size	Size of trial
prob	probability of success
full	Add the data frame showing x, mean, sd as well as the fx and derivatives

Value

data frame with fx for the pdf value of with dProb that has the derivatives with respect to the parameters at the observation time-point

Author(s)

Matthew L. Fidler

Examples

```
llikBinom(46:54, 100, 0.5)

llikBinom(46:54, 100, 0.5, TRUE)
```

llikCauchy	<i>log likelihood of Cauchy distribution and it's derivatives (from stan)</i>
------------	---

Description

log likelihood of Cauchy distribution and it's derivatives (from stan)

Usage

```
llikCauchy(x, location = 0, scale = 1, full = FALSE)
```

Arguments

x	Observation
location, scale	location and scale parameters.
full	Add the data frame showing x, mean, sd as well as the fx and derivatives

Value

data frame with fx for the log pdf value of with dLocation and dScale that has the derivatives with respect to the parameters at the observation time-point

Author(s)

Matthew L. Fidler

Examples

```
x <- seq(-3, 3, length.out = 21)

llikCauchy(x, 0, 1)

llikCauchy(x, 3, 1, full=TRUE)
```

llikChisq	<i>log likelihood and derivatives for chi-squared distribution</i>
-----------	--

Description

log likelihood and derivatives for chi-squared distribution

Usage

```
llikChisq(x, df, full = FALSE)
```

Arguments

x	variable that is distributed by chi-squared distribution
df	degrees of freedom (non-negative, but can be non-integer).
full	Add the data frame showing x, mean, sd as well as the fx and derivatives

Value

data frame with fx for the log pdf value of with dDf that has the derivatives with respect to the df parameter the observation time-point

Author(s)

Matthew L. Fidler

Examples

```
llikChisq(1, df = 1:3, full=TRUE)

llikChisq(1, df = 6:9)
```

llikDblExp	<i>log likelihood of the DblExp distribution and its derivatives (from stan)</i>
------------	--

Description

log likelihood of the DblExp distribution and its derivatives (from stan)

Usage

```
llikDblExp(x, mu, sigma, full = FALSE)
```

Arguments

x	Observation
mu	distribution parameter
sigma	distribution parameter
full	return the input parameters alongside the result

Value

data frame with fx and the derivative of each parameter

llikExp	<i>log likelihood and derivatives for exponential distribution</i>
---------	--

Description

log likelihood and derivatives for exponential distribution

Usage

```
llikExp(x, rate, full = FALSE)
```

Arguments

x	variable that is distributed by exponential distribution
rate	vector of rates.
full	Add the data frame showing x, mean, sd as well as the fx and derivatives

Value

data frame with fx for the log pdf value of with dRate that has the derivatives with respect to the rate parameter the observation time-point

Author(s)

Matthew L. Fidler

Examples

```
llikExp(1, 1:3)

llikExp(1, 1:3, full=TRUE)
```

llikF

log likelihood and derivatives for F distribution

Description

log likelihood and derivatives for F distribution

Usage

```
llikF(x, df1, df2, full = FALSE)
```

Arguments

x	variable that is distributed by f distribution
df1, df2	degrees of freedom. Inf is allowed.
full	Add the data frame showing x, mean, sd as well as the fx and derivatives

Value

data frame with fx for the log pdf value of with dDf1 and dDf2 that has the derivatives with respect to the df1/df2 parameters at the observation time-point

Author(s)

Matthew L. Fidler

Examples

```
x <- seq(0.001, 5, length.out = 100)

llikF(x^2, 1, 5)
```

llikFrechet	<i>log likelihood of the Frechet distribution and its derivatives (from stan)</i>
-------------	---

Description

log likelihood of the Frechet distribution and its derivatives (from stan)

Usage

```
llikFrechet(x, alpha, sigma, full = FALSE)
```

Arguments

x	Observation
alpha	distribution parameter
sigma	distribution parameter
full	return the input parameters alongside the result

Value

data frame with fx and the derivative of each parameter

llikGamma	<i>log likelihood and derivatives for Gamma distribution</i>
-----------	--

Description

log likelihood and derivatives for Gamma distribution

Usage

```
llikGamma(x, shape, rate, full = FALSE)
```

Arguments

x	variable that is distributed by gamma distribution
shape	this is the distribution's shape parameter. Must be positive.
rate	this is the distribution's rate parameters. Must be positive.
full	Add the data frame showing x, mean, sd as well as the fx and derivatives

Value

data frame with fx for the log pdf value of with dProb that has the derivatives with respect to the prob parameters at the observation time-point

Author(s)

Matthew L. Fidler

Examples

```
llikGamma(1, 1, 10)
```

llikGeom

log likelihood and derivatives for Geom distribution

Description

log likelihood and derivatives for Geom distribution

Usage

```
llikGeom(x, prob, full = FALSE)
```

Arguments

x	variable distributed by a geom distribution
prob	probability of success in each trial. $0 < \text{prob} \leq 1$.
full	Add the data frame showing x, mean, sd as well as the fx and derivatives

Value

data frame with fx for the log pdf value of with dProb that has the derivatives with respect to the prob parameters at the observation time-point

Author(s)

Matthew L. Fidler

Examples

```
llikGeom(1:10, 0.2)
```

llikGumbel	<i>log likelihood of the Gumbel distribution and its derivatives (from stan)</i>
------------	--

Description

log likelihood of the Gumbel distribution and its derivatives (from stan)

Usage

```
llikGumbel(x, mu, beta, full = FALSE)
```

Arguments

x	Observation
mu	distribution parameter
beta	distribution parameter
full	return the input parameters alongside the result

Value

data frame with fx and the derivative of each parameter

llikInvChisq	<i>log likelihood of the InvChisq distribution and its derivatives (from stan)</i>
--------------	--

Description

log likelihood of the InvChisq distribution and its derivatives (from stan)

Usage

```
llikInvChisq(x, nu, full = FALSE)
```

Arguments

x	Observation
nu	distribution parameter
full	return the input parameters alongside the result

Value

data frame with fx and the derivative of each parameter

llikInvGamma	<i>log likelihood of the InvGamma distribution and its derivatives (from stan)</i>
--------------	--

Description

log likelihood of the InvGamma distribution and its derivatives (from stan)

Usage

```
llikInvGamma(x, alpha, beta, full = FALSE)
```

Arguments

x	Observation
alpha	distribution parameter
beta	distribution parameter
full	return the input parameters alongside the result

Value

data frame with fx and the derivative of each parameter

llikLnorm	<i>log likelihood of the Lnorm distribution and its derivatives (from stan)</i>
-----------	---

Description

log likelihood of the Lnorm distribution and its derivatives (from stan)

Usage

```
llikLnorm(x, meanlog, sdlog, full = FALSE)
```

Arguments

x	Observation
meanlog	distribution parameter
sdlog	distribution parameter
full	return the input parameters alongside the result

Value

data frame with fx and the derivative of each parameter

llikLogis	<i>log likelihood of the Logis distribution and its derivatives (from stan)</i>
-----------	---

Description

log likelihood of the Logis distribution and its derivatives (from stan)

Usage

```
llikLogis(x, location, scale, full = FALSE)
```

Arguments

x	Observation
location	distribution parameter
scale	distribution parameter
full	return the input parameters alongside the result

Value

data frame with fx and the derivative of each parameter

llikNbinom	<i>Calculate the log likelihood of the negative binomial function (and its derivatives)</i>
------------	---

Description

Calculate the log likelihood of the negative binomial function (and its derivatives)

Usage

```
llikNbinom(x, size, prob, full = FALSE)
```

Arguments

x	Number of successes
size	Dispersion parameter; may be non-integer
prob	probability of success
full	Add the data frame showing x, mean, sd as well as the fx and derivatives

Value

data frame with fx for the pdf value of with dProb that has the derivatives with respect to the parameters at the observation time-point

Author(s)

Matthew L. Fidler

Examples

```
llikNbinom(46:54, 100, 0.5)
```

```
llikNbinom(46:54, 100, 0.5, TRUE)
```

llikNbinomMu	<i>Calculate the log likelihood of the negative binomial function (and its derivatives)</i>
--------------	---

Description

Calculate the log likelihood of the negative binomial function (and its derivatives)

Usage

```
llikNbinomMu(x, size, mu, full = FALSE)
```

Arguments

x	Number of successes
size	Dispersion parameter; may be non-integer
mu	mu parameter for negative binomial
full	Add the data frame showing x, mean, sd as well as the fx and derivatives

Value

data frame with fx for the pdf value of with dProb that has the derivatives with respect to the parameters at the observation time-point

Author(s)

Matthew L. Fidler

Examples

```
llikNbinomMu(46:54, 100, 40)
```

```
llikNbinomMu(46:54, 100, 40, TRUE)
```

llikNorm	<i>Log likelihood for normal distribution</i>
----------	---

Description

Log likelihood for normal distribution

Usage

```
llikNorm(x, mean = 0, sd = 1, full = FALSE)
```

Arguments

x	Observation
mean	Mean for the likelihood
sd	Standard deviation for the likelihood
full	Add the data frame showing x, mean, sd as well as the fx and derivatives

Value

data frame with fx for the pdf value of with dMean and dSd that has the derivatives with respect to the parameters at the observation time-point

Author(s)

Matthew L. Fidler

Examples

```
llikNorm(0)

llikNorm(seq(-2,2,length.out=10), full=TRUE)
```

llikPareto	<i>log likelihood of the Pareto distribution and its derivatives (from stan)</i>
------------	--

Description

log likelihood of the Pareto distribution and its derivatives (from stan)

Usage

```
llikPareto(x, yMin, alpha, full = FALSE)
```

Arguments

x	Observation
yMin	distribution parameter
alpha	distribution parameter
full	return the input parameters alongside the result

Value

data frame with fx and the derivative of each parameter

llikParetoType2	<i>log likelihood of the ParetoType2 distribution and its derivatives (from stan)</i>
-----------------	---

Description

log likelihood of the ParetoType2 distribution and its derivatives (from stan)

Usage

```
llikParetoType2(x, mu, lambda, alpha, full = FALSE)
```

Arguments

x	Observation
mu	distribution parameter
lambda	distribution parameter
alpha	distribution parameter
full	return the input parameters alongside the result

Value

data frame with fx and the derivative of each parameter

llikPois	<i>log-likelihood for the Poisson distribution</i>
----------	--

Description

log-likelihood for the Poisson distribution

Usage

```
llikPois(x, lambda, full = FALSE)
```

Arguments

x	non negative integers
lambda	non-negative means
full	Add the data frame showing x, mean, sd as well as the fx and derivatives

Value

data frame with fx for the pdf value of with dLambda that has the derivatives with respect to the parameters at the observation time-point

Author(s)

Matthew L. Fidler

llikRayleigh	<i>log likelihood of the Rayleigh distribution and its derivatives (from stan)</i>
--------------	--

Description

log likelihood of the Rayleigh distribution and its derivatives (from stan)

Usage

```
llikRayleigh(x, sigma, full = FALSE)
```

Arguments

x	Observation
sigma	distribution parameter
full	return the input parameters alongside the result

Value

data frame with fx and the derivative of each parameter

llikScaledInvChisq	<i>log likelihood of the ScaledInvChisq distribution and its derivatives (from stan)</i>
--------------------	--

Description

log likelihood of the ScaledInvChisq distribution and its derivatives (from stan)

Usage

```
llikScaledInvChisq(x, nu, sigma, full = FALSE)
```

Arguments

x	Observation
nu	distribution parameter
sigma	distribution parameter
full	return the input parameters alongside the result

Value

data frame with fx and the derivative of each parameter

llikT	<i>Log likelihood of T and it's derivatives (from stan)</i>
-------	---

Description

Log likelihood of T and it's derivatives (from stan)

Usage

```
llikT(x, df, mean = 0, sd = 1, full = FALSE)
```

Arguments

x	Observation
df	degrees of freedom (> 0 , maybe non-integer). $df = \text{Inf}$ is allowed.
mean	Mean for the likelihood
sd	Standard deviation for the likelihood
full	Add the data frame showing x, mean, sd as well as the fx and derivatives

Value

data frame with fx for the log pdf value of with dDf dMean and dSd that has the derivatives with respect to the parameters at the observation time-point

Author(s)

Matthew L. Fidler

Examples

```
x <- seq(-3, 3, length.out = 21)

llikT(x, 7, 0, 1)

llikT(x, 15, 0, 1, full=TRUE)
```

llikUnif	<i>log likelihood and derivatives for Unif distribution</i>
----------	---

Description

log likelihood and derivatives for Unif distribution

Usage

```
llikUnif(x, alpha, beta, full = FALSE)
```

Arguments

x	variable distributed by a uniform distribution
alpha	is the lower limit of the uniform distribution
beta	is the upper limit of the distribution
full	Add the data frame showing x, mean, sd as well as the fx and derivatives

Value

data frame with fx for the log pdf value of with dProb that has the derivatives with respect to the prob parameters at the observation time-point

Author(s)

Matthew L. Fidler

Examples

```
llikUnif(1, -2, 2)
```

llikWeibull	<i>log likelihood and derivatives for Weibull distribution</i>
-------------	--

Description

log likelihood and derivatives for Weibull distribution

Usage

```
llikWeibull(x, shape, scale, full = FALSE)
```

Arguments

x	variable distributed by a Weibull distribution
shape, scale	shape and scale parameters, the latter defaulting to 1.
full	Add the data frame showing x, mean, sd as well as the fx and derivatives

Value

data frame with fx for the log pdf value of with dProb that has the derivatives with respect to the prob parameters at the observation time-point

Author(s)

Matthew L. Fidler

Examples

```
llikWeibull(1, 1, 10)
```

Index

.rxode2llPtr, [2](#)

llikBeta, [3](#)

llikBetaProportion, [4](#)

llikBinom, [4](#)

llikCauchy, [5](#)

llikChisq, [6](#)

llikDbExp, [7](#)

llikExp, [7](#)

llikF, [8](#)

llikFrechet, [9](#)

llikGamma, [9](#)

llikGeom, [10](#)

llikGumbel, [11](#)

llikInvChisq, [11](#)

llikInvGamma, [12](#)

llikLnorm, [12](#)

llikLogis, [13](#)

llikNbinom, [13](#)

llikNbinomMu, [14](#)

llikNorm, [15](#)

llikPareto, [15](#)

llikParetoType2, [16](#)

llikPois, [17](#)

llikRayleigh, [17](#)

llikScaledInvChisq, [18](#)

llikT, [18](#)

llikUnif, [19](#)

llikWeibull, [20](#)