

Package ‘scholar’

July 7, 2026

Type Package

Title Analyse Citation Data from Google Scholar

Version 1.0.0

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Description Provides tools to retrieve, analyse, and format publication and citation data from Google Scholar profiles. It supports profile lookup, publication records, citation histories, scholar comparison, coauthor networks, journal ranking queries, CV-ready publication lists, and citation metric summaries.

Depends R (>= 4.1.0)

Imports R.cache, dplyr, httr, rlang, rvest, stringr, xml2, tidygraph, ggraph, ggplot2

Suggests knitr, quarto, rmarkdown, roxygen2, spelling, testthat (>= 2.1.0), yulab.utils

VignetteBuilder quarto

License MIT + file LICENSE

URL <https://github.com/YuLab-SMU/scholar>

BugReports <https://github.com/YuLab-SMU/scholar/issues>

Encoding UTF-8

Language en-GB

Config/roxygen2/version 8.0.0

NeedsCompilation no

Author Guangchuang Yu [aut, cre] (ORCID: <<https://orcid.org/0000-0002-6485-8781>>),
James Keirstead [aut],
Gregory Jefferis [aut] (ORCID: <<https://orcid.org/0000-0002-0587-9355>>),
Gordon Getzinger [ctb],
Jorge Cimentada [ctb],
Max Czapanskiy [ctb],
Dominique Makowski [ctb]

Repository CRAN

Date/Publication 2026-07-07 08:50:02 UTC

Contents

author_position	2
compare_scholars	3
compare_scholar_careers	4
format_authors	5
format_publications	5
get_article_cite_history	6
get_article_scholar_url	6
get_citation_history	7
get_coauthors	7
get_complete_authors	8
get_journalrank	9
get_num_articles	10
get_num_distinct_journals	10
get_num_top_journals	11
get_oldest_article	11
get_profile	12
get_publications	13
get_publications_all_authors	14
get_publication_abstract	14
get_publication_data_extended	15
get_publication_date	15
get_publication_metrics	16
get_publication_url	16
get_scholar_id	17
get_scholar_metrics	17
get_scholar_resp	18
plot_coauthors	19
predict_h_index	19
search_scholar_ids	20
set_scholar_mirror	21
Index	22

author_position	<i>Get author order.</i>
-----------------	--------------------------

Description

Get author rank in authors list.

Usage

author_position(authorlist, author)

Arguments

authorlist	list of publication authors
author	author's name to look for

Value

dataframe with author's position and normalized position (a normalized index, with 0 corresponding, 1 to last and 0.5 to the middle. Note that single authorship will be considered as last, i.e., 1).

Author(s)

Dominique Makowski

Examples

```
## Not run:
library(scholar)

id <- "D05oG40AAAJ"

authorlist <- scholar::get_publications(id)$author
author <- scholar::get_profile(id)$name

author_position(authorlist, author)

## End(Not run)
```

compare_scholars	<i>Compare the citation records of multiple scholars</i>
------------------	--

Description

Compares the citation records of multiple scholars. This function compiles a data frame comparing the citations received by each of the scholar's publications by year of publication.

Usage

```
compare_scholars(ids, pagesize = 100)
```

Arguments

ids	a vector of Google Scholar IDs
pagesize	an integer specifying the number of articles to fetch for each scholar

Value

a data frame giving the ID of each scholar and the total number of citations received by work published in a year.

Examples

```
## Not run:
## How do Richard Feynmann and Stephen Hawking compare?
ids <- c("B7vSqZsAAAAJ", "D05oG40AAAAJ")
df <- compare_scholars(ids)

## End(Not run)
```

compare_scholar_careers

Compare the careers of multiple scholars

Description

Compares the careers of multiple scholars based on their citation histories. The scholar's *career* is defined by the number of citations to his or her work in a given year (i.e. the bar chart at the top of a scholar's profile). The function has a `career` option that allows users to compare scholars directly, i.e. relative to the first year in which their publications are cited.

Usage

```
compare_scholar_careers(ids, career = TRUE)
```

Arguments

<code>ids</code>	a character vector of Google Scholar IDs
<code>career</code>	a boolean, should a column be added to the results measuring the year relative to the first citation year. Default = TRUE

Examples

```
## How do Richard Feynmann and Stephen Hawking compare?
# Compare Feynman and Stephen Hawking
ids <- c("B7vSqZsAAAAJ", "D05oG40AAAAJ")
df <- compare_scholar_careers(ids)
```

format_authors	<i>format_authors</i>
----------------	-----------------------

Description

This function converts first and middle names to initials

Usage

```
format_authors(string)
```

Arguments

string	a character vector of names
--------	-----------------------------

format_publications	<i>format_publications</i>
---------------------	----------------------------

Description

Format publication list

Usage

```
format_publications(scholar.profile, author.name = NULL)
```

Arguments

scholar.profile	
	scholar profile ID
author.name	name of author to be highlighted using bold font

Value

a vector of formatted publications

Author(s)

R Thériault and modified by Guangchuang Yu

Examples

```
## Not run:  
library(scholar)  
format_publications("D05oG40AAAAJ")  
  
## End(Not run)
```

`get_article_cite_history`*Gets the citation history of a single article*

Description

Gets the citation history of a single article

Usage

```
get_article_cite_history(id, article)
```

Arguments

<code>id</code>	a character string giving the id of the scholar
<code>article</code>	a character string giving the article id.

Value

a data frame giving the year, citations per year, and publication id

`get_article_scholar_url`*Gets the URL to the google scholar website of an article.*

Description

Gets the URL to the google scholar website of an article.

Usage

```
get_article_scholar_url(id, pubid)
```

Arguments

<code>id</code>	a character string specifying the Google Scholar ID.
<code>pubid</code>	a character string specifying the article id.

Value

a String that contains the URL to the scholar website of the article

get_citation_history	<i>Get historical citation data for a scholar</i>
----------------------	---

Description

Gets the number of citations to a scholar's articles over the past nine years.

Usage

```
get_citation_history(id)
```

Arguments

id	a character string specifying the Google Scholar ID. If multiple ids are specified, only the first value is used and a warning is generated.
----	--

Details

This information is displayed as a bar plot at the top of a standard Google Scholar page and only covers the past nine years.

Value

a data frame giving the number of citations per year to work by the given scholar

get_coauthors	<i>Gets the network of coauthors of a scholar</i>
---------------	---

Description

Gets the network of coauthors of a scholar

Usage

```
get_coauthors(id, n_coauthors = 5, n_deep = 1)
```

Arguments

id	a character string specifying the Google Scholar ID. If multiple ids are specified, only the first value is used and a warning is generated.
n_coauthors	Number of coauthors to explore. This number should usually be between 1 and 10 as choosing many coauthors can make the network graph too messy.
n_deep	The number of degrees that you want to go down the network. When n_deep is equal to 1 then grab_coauthor will only grab the coauthors of Joe and Mary, so Joe -> Mary -> All coauthors. This can get out of control very quickly if n_deep is set to 2 or above. The preferred number is 1, the default.

Details

Considering that scraping each publication for all coauthors is error prone, `get_coauthors` grabs the coauthors listed by Google Scholar for the profile, not from all publications. It first tries Google Scholar's full colleagues list and falls back to the profile sidebar if that list is unavailable.

Value

A data frame with two columns showing all authors and coauthors.

See Also

[plot_coauthors](#)

Examples

```
## Not run:

library(scholar)
coauthor_network <- get_coauthors('amYIKXQAAAJ')
plot_coauthors(coauthor_network)

## End(Not run)
```

`get_complete_authors` *Get the Complete list of authors for a Publication*

Description

Found as Muhammad Qasim Pasta's solution here <https://github.com/jkeirstead/scholar/issues/21>

Usage

```
get_complete_authors(id, pubid, delay = 0.4, initials = TRUE)
```

Arguments

<code>id</code>	a Google Scholar ID
<code>pubid</code>	a Publication ID from a given google Scholar ID
<code>delay</code>	average delay between requests. A delay is needed to stop Google identifying you as a bot
<code>initials</code>	if TRUE (default), first and middle names will be abbreviated

Value

a string containing the complete list of authors

Author(s)

Muhammad Qasim Pasta

Abram B. Fleishman

James H. Conigrave

get_journalrank

*Get journal ranking.***Description**

Get SCImago journal ranking data.

Usage

```
get_journalrank(journals, max.distance = 0.05)
```

Arguments

journals	a character list giving the journal list. If missing, the full SCImago journal ranking table is returned.
max.distance	maximum distance allowed for a match between journal and journal list. Expressed either as integer, or as a fraction of the pattern length times the maximal transformation cost (will be replaced by the smallest integer not less than the corresponding fraction), or a list with possible components

Value

Journal ranking data.

Author(s)

Dominique Makowski and Guangchuang Yu

Examples

```
## Not run:
library(scholar)

id <- get_publications("bg0BZ-QAAAAJ&hl")
impact <- get_journalrank(journals=id$journal)

id <- cbind(id, impact)

## End(Not run)
```

get_num_articles	<i>Calculates how many articles a scholar has published</i>
------------------	---

Description

Calculate how many articles a scholar has published.

Usage

```
get_num_articles(id)
```

Arguments

id	a character string giving the Google Scholar ID
----	---

Value

an integer value (max 100)

get_num_distinct_journals	<i>Gets the number of distinct journals in which a scholar has published</i>
---------------------------	--

Description

Gets the number of distinct journals in which a scholar has published. Note that Google Scholar doesn't provide information on journals *per se*, but instead gives a title for the containing publication where applicable. So a *journal* here might actually be a journal, a book, a report, or some other publication outlet.

Usage

```
get_num_distinct_journals(id)
```

Arguments

id	a character string giving the Google Scholar id
----	---

Value

the number of distinct journals

get_num_top_journals	<i>Gets the number of top journals in which a scholar has published</i>
----------------------	---

Description

Gets the number of top journals in which a scholar has published. The definition of a 'top journal' comes from Acuna et al. and the original list was based on the field of neuroscience. This function allows users to specify that list for themselves, or use the default Acuna et al. list.

Usage

```
get_num_top_journals(id, journals)
```

Arguments

id	a character string giving a Google Scholar ID
journals	a character vector giving the names of the top journals. Defaults to Nature, Science, Nature Neuroscience, Proceedings of the National Academy of Sciences, and Neuron.

Source

DE Acuna, S Allesina, KP Kording (2012) Future impact: Predicting scientific success. Nature 489, 201-202. doi:[10.1038/489201a](https://doi.org/10.1038/489201a).

get_oldest_article	<i>Gets the year of the oldest article for a scholar</i>
--------------------	--

Description

Gets the year of the oldest article published by a given scholar.

Usage

```
get_oldest_article(id)
```

Arguments

id	a character string giving the Google Scholar ID
----	---

Value

the year of the oldest article

get_profile

Gets profile information for a scholar

Description

Gets profile information for a researcher from Google Scholar. Each scholar profile page gives the researcher's name, affiliation, their homepage (if specified), and a summary of their key citation and publication availability metrics. The scholar ID can be found by searching Google Scholar at <http://scholar.google.com>.

Usage

```
get_profile(id)
```

Arguments

id a character string specifying the Google Scholar ID. If multiple ids are specified, only the first value is used and a warning is generated. See the example below for how to profile multiple scholars.

Value

a list containing the scholar's name, affiliation, citations, impact and publication availability metrics, research interests, homepage and coauthors.

Metrics include:

- **total_cites** combined citations to all publications
- **h_index** the largest number h such that h publications each have at least h citations
- **i10_index** the number of publications that each have at least 10 citations
- **available** the number of publications that have a version online that can be read for free (though not necessarily reusable under an open access license)
- **not_available** the number of publications only available behind a paywall

Examples

```
## Gets profiles of some famous physicists
ids <- c("xJaxiEEAAAJ", "D05oG40AAAJ")
profiles <- lapply(ids, get_profile)
```

get_publications	<i>Gets the publications for a scholar</i>
------------------	--

Description

Gets the publications of a specified scholar.

Usage

```
get_publications(
    id,
    cstart = 0,
    cstop = Inf,
    pagesize = 100,
    flush = FALSE,
    sortby = "citation"
)
```

Arguments

id	a character string specifying the Google Scholar ID. If multiple IDs are specified, only the publications of the first scholar will be retrieved.
cstart	an integer specifying the first article to start counting. To get all publications for an author, omit this parameter.
cstop	an integer specifying the last article to process.
pagesize	an integer specifying the number of articles to fetch in one batch. It is recommended to leave the default value of 100 unless you experience time-out errors. Note this is <i>not</i> the total number of publications to fetch.
flush	should the cache be flushed? Search results are cached by default to speed up repeated queries. If this argument is TRUE, the cache will be cleared and the data reloaded from Google.
sortby	a character with value "citation" or value "year" specifying how results are sorted.

Details

Google uses two id codes to uniquely reference a publication. The results of this method includes cid which can be used to link to a publication's full citation history (i.e. if you click on the number of citations in the main scholar profile page), and pubid which links to the details of the publication (i.e. if you click on the title of the publication in the main scholar profile page.)

Value

a data frame listing the publications and their details. These include the publication title, author, journal, number, cites, year, and two id codes (see details).

`get_publications_all_authors`*Gets publications with complete author lists*

Description

Gets a scholar's publications and fills truncated author lists by calling [get_complete_authors](#) only for publications whose author field contains ...

Usage

```
get_publications_all_authors(id, delay = 0.8, initials = TRUE, ...)
```

Arguments

<code>id</code>	a character string specifying the Google Scholar ID.
<code>delay</code>	average delay between requests for complete author lists. See get_complete_authors .
<code>initials</code>	if TRUE, first and middle names in completed author lists will be abbreviated. See get_complete_authors .
<code>...</code>	additional arguments passed to get_publications .

Value

a data frame listing the publications and their details, with truncated author lists replaced where possible.

`get_publication_abstract`*Gets the abstract for a publication id.*

Description

Gets the abstract for a publication id.

Usage

```
get_publication_abstract(id, pub_id, flush = FALSE)
```

Arguments

<code>id</code>	a character string specifying the Google Scholar ID.
<code>pub_id</code>	a character string specifying the publication id.
<code>flush</code>	Whether or not to clear the cache

Value

a String that contains the abstract of the publication.

get_publication_data_extended
Gets the full data for a publication

Description

Gets the full data for a publication

Usage

```
get_publication_data_extended(id, pub_id, flush = FALSE)
```

Arguments

id	a character string specifying the Google Scholar ID.
pub_id	a character string specifying the publication id.
flush	Whether or not to clear the cache

Value

a list that contains the full data

get_publication_date *Gets the full date for a publication*

Description

Gets the full date for a publication

Usage

```
get_publication_date(id, pub_id, flush = FALSE)
```

Arguments

id	a character string specifying the Google Scholar ID.
pub_id	a character string specifying the publication id.
flush	Whether or not to clear the cache

Value

a String that contains the publication date

`get_publication_metrics`*Calculate citation metrics from publication data*

Description

Calculates common citation metrics from a publication data frame, such as the result returned by [get_publications](#).

Usage

```
get_publication_metrics(publications)
```

Arguments

`publications` a data frame containing a numeric `cites` column

Value

a data frame with h-index, g-index, i10-index, i50-index, i100-index, total citations, and publication count

`get_publication_url` *Gets the PDF URL for a publication id.*

Description

Gets the PDF URL for a publication id.

Usage

```
get_publication_url(id, pub_id, flush = FALSE)
```

Arguments

`id` a character string specifying the Google Scholar ID.
`pub_id` a character string specifying the publication id.
`flush` Whether or not to clear the cache

Value

a String that contains the URL to the PDF of the publication.

get_scholar_id	<i>Search for Google Scholar ID by name and affiliation</i>
----------------	---

Description

Search for Google Scholar ID by name and affiliation

Usage

```
get_scholar_id(last_name = "", first_name = "", affiliation = NA)
```

Arguments

last_name	Researcher last name.
first_name	Researcher first name.
affiliation	Researcher affiliation.

Value

Google Scholar ID as a character string.

Examples

```
get_scholar_id(first_name = "kristopher", last_name = "mcneill")

get_scholar_id(first_name = "michael", last_name = "sander", affiliation = NA)
get_scholar_id(first_name = "michael", last_name = "sander", affiliation = "eth")
get_scholar_id(first_name = "michael", last_name = "sander", affiliation = "ETH Zurich")
get_scholar_id(first_name = "michael", last_name = "sander", affiliation = "Mines")
get_scholar_id(first_name = "james", last_name = "babler")
```

get_scholar_metrics	<i>Calculate citation metrics for a scholar</i>
---------------------	---

Description

Fetches a scholar's publications with [get_publications](#) and calculates common citation metrics.

Usage

```
get_scholar_metrics(id, pagesize = 100, flush = FALSE)
```

Arguments

id	a character string specifying the Google Scholar ID
pagesize	an integer specifying the number of articles to fetch in one batch. See get_publications .
flush	should the publication cache be flushed?

Value

a data frame with h-index, g-index, i10-index, i50-index, i100-index, total citations, and publication count

get_scholar_resp	<i>Recursively try to GET a Google Scholar Page storing session cookies</i>
------------------	---

Description

see [scholar-package](#) documentation for details about Scholar session cookies.

Usage

```
get_scholar_resp(url, attempts_left = 5)
```

Arguments

url	URL to fetch
attempts_left	The number of times to try and fetch the page

Value

an [response][httr::response] object

See Also

[GET][httr::GET]

plot_coauthors	<i>Plot a network of coauthors</i>
----------------	------------------------------------

Description

Plot a network of coauthors

Usage

```
plot_coauthors(network, size_labels = 5)
```

Arguments

network	A data frame given by get_coauthors
size_labels	Size of the label names

Value

a ggplot2 object but prints a plot as a side effect.

See Also

[get_coauthors](#)

Examples

```
## Not run:
library(scholar)
coauthor_network <- get_coauthors('amYIKXQAAAAJ&hl')
plot_coauthors(coauthor_network)

## End(Not run)
```

predict_h_index	<i>Predicts the h-index for a researcher</i>
-----------------	--

Description

Predicts the h-index for a researcher each year for ten years into the future using Acuna et al's method (see source). The model was fit to data from neuroscience researchers with an h-index greater than 5 and between 5 to 12 years since publishing their first article. So naturally if this isn't you, then the results should be taken with a large pinch of salt.

Usage

```
predict_h_index(id, journals)
```

Arguments

`id` a character string giving the Google Scholar ID

`journals` optional character vector of top journals. See [get_num_top_journals](#) for more details.

Details

Since the model is calibrated to neuroscience researchers, it is entirely possible that very strange (e.g. negative) h-indices will be predicted if you are a researcher in another field. A warning will be displayed if the sequence of predicted h-indices contains a negative value or is non-increasing.

Value

a data frame giving predicted h-index values in future

Note

A scientist has an h-index of n if he or she publishes n papers with at least n citations each. Values returned are fractional so it's up to your own vanity whether you want to round up or down.

Source

DE Acuna, S Allesina, KP Kording (2012) Future impact: Predicting scientific success. Nature 489, 201-202. doi:[10.1038/489201a](#). Thanks to DE Acuna for providing the full regression coefficients for each year ahead prediction.

Examples

```
## Predict h-index of original method author
## Not run:
id <- "D05oG40AAAAJ"
df <- predict_h_index(id)

## End(Not run)
```

search_scholar_ids	<i>Search Google Scholar IDs by author name</i>
--------------------	---

Description

Searches Google Scholar author results and returns matching author IDs.

Usage

```
search_scholar_ids(name, max_pages = Inf, delay = 0)
```

Arguments

name	author search query
max_pages	maximum number of search result pages to fetch
delay	number of seconds to wait between result pages

Value

a data frame with columns id, name, affiliation, email, interests, and url

Examples

```
search_scholar_ids("hao xu", max_pages = 1)
```

set_scholar_mirror	<i>set_scholar_mirror</i>
--------------------	---------------------------

Description

set scholar mirror

Usage

```
set_scholar_mirror(mirror = NULL)
```

Arguments

mirror	compatible scholar mirror
--------	---------------------------

Details

setting google scholar mirror

Author(s)

Guangchuang Yu

Index

author_position, [2](#)

compare_scholar_careers, [4](#)
compare_scholars, [3](#)

format_authors, [5](#)
format_publications, [5](#)

get_article_cite_history, [6](#)
get_article_scholar_url, [6](#)
get_citation_history, [7](#)
get_coauthors, [7](#), [19](#)
get_complete_authors, [8](#), [14](#)
get_journalrank, [9](#)
get_num_articles, [10](#)
get_num_distinct_journals, [10](#)
get_num_top_journals, [11](#), [20](#)
get_oldest_article, [11](#)
get_profile, [12](#)
get_publication_abstract, [14](#)
get_publication_data_extended, [15](#)
get_publication_date, [15](#)
get_publication_metrics, [16](#)
get_publication_url, [16](#)
get_publications, [13](#), [14](#), [16–18](#)
get_publications_all_authors, [14](#)
get_scholar_id, [17](#)
get_scholar_metrics, [17](#)
get_scholar_resp, [18](#)

plot_coauthors, [8](#), [19](#)
predict_h_index, [19](#)

search_scholar_ids, [20](#)
set_scholar_mirror, [21](#)